

Inductors (Coils)

Product Top Page

Search by Part No.

Search by Characteristics

Cross Reference

Catalog

Tech Notes

Technical Support Tools

FAQ

MLF2012E100MT000



Applications



Commercial Grade

Feature

Shield

Magnetic Shield

Multilayer

Multilayer

Ferrite Core

Ferrite Core

Series

MLF

Status



Production



Images are for reference only and show exemplary products.

PDF file of this page



Buy Now



Contact



Documents

Catalog

RoHS Certificate

SVHC/REACH Certificate

Product Lineup

Technical Support Tools

S-parameter

SPICE Netlist (Simple)

Equivalent Circuit Model

Size

Length(L) 2.00mm ±0.20mm

Width(W) 1.25mm ±0.20mm

Thickness(T) 1.25mm ±0.20mm

Recommended Land Pattern (A) 0.80mm Nom.

Recommended Land Pattern (B) 1.00mm Nom.

Recommended Land Pattern (C) 1.20mm Nom.

Electrical Characteristics

Inductance 10μH ±20% at 2MHz

Rated Current (L Change) [Typ.]

Rated Current (L Change) [Max.]

Rated Current (Temperature Rise) [Typ.]

Rated Current (Temperature Rise) [Max.] 15mA

DC Resistance [Typ.] 400mΩ

DC Resistance [Max.] 800mΩ

Self Resonant Frequency [Min.] 30MHz

Self Resonant Frequency [Typ.] 50MHz

Q [Min.] 50

Q [Typ.] 75

Other

Operating Temp. Range (Including Self-Temp. Rise) -55 to 125°C

Soldering Method
Reflow
Iron Soldering

AEC-Q200 No

Packing Blister (Plastic)Taping [180mm Reel]

Package Quantity 2000pcs

Weight 0.014g


Characteristic Graph (This is reference data, and does not guarantee the products characteristics.)

Impedance

10k


Rac

10k




MLF2012E100MT000

Change settings




MLF2012E100MT000

Change settings




MLF2012E100MT000

Change settings




MLF2012E100MT000


Change settings



Change settings



Change settings



Change settings

Products

» [Search by Part No.](#) » [Search by Characteristics](#) » [Distributor Inventory Check](#)

- | | |
|--|---|
| » Capacitors | » Anechoic Chambers and Radio Wave Absorbers |
| » Inductors (Coils) | » Power Supplies |
| » EMC Components | » Magnets |
| » RF Components and Modules | » Flash Storages |
| » Voltage / Current / Temperature Protection Devices | » Wireless Power Transfer |
| » Sensors and Sensor Systems | » FA Systems |
| » Ceramic Switching / Heating, Piezo Components, | » Transparent Conductive Film |
| Buzzers and Microphones | » Micro Modules (Substrates with Built-in ICs, Products Utilizing with SESUB) |
| » Transformers | » Solar Cells |
| » Ferrites and Accessories | » Biosensor |
| » Noise Suppressing / Magnetic Sheet | |

Application Guides

Technical Support

Tech Library

Environment

Contact

News

Home



About TDK



TDK Worldwide

[Terms of Use](#) [Privacy Policy](#)

Copyright(c) 1996-2017 TDK Corporation. All rights reserved.
TDK logo is a trademark or registered trademark of TDK Corporation.

