

Circuit Board Indicators
Panel Mount Indicators
Solid State Lighting
Traffic Signals
Vehicle Lighting
Rail
Obstruction Lighting
Hazardous Area Lighting
Heliport Lighting
how to purchase
 [sales contacts](#)
 [stock check](#)
 [search](#)
 [Product Line Search](#)
Please select a Product Line to search.
Circuit Board Indicators
 [find](#)
 [Part # / Text Search](#)
Part No.:
Text Search:
 [search](#)
 [quick links](#)
Dialight Corporate Video
Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)
**Application Notes
FAQs**
Dialight Ltd (UK)
Dialight Garufo
Dialight BLP
LumiDrives
P/N# 5692213300F
3 mm Lens Single Color

Description	3 mm Bi-Level CBI Y-Y
Package Options	50 Pieces Per Bag
Product Type	Through Hole Indicators
Sub Product Type	with Bi-Level Housing
Configuration	3 mm Lens
Lamp Type	Single Color
Viewing	Right Angle
Viewing Angle	45
Test Current (mA)	10mA
Forward Current (mA)	20mA
LED Centerline	2.29
Polarity	Cathode Pin 1 & 3

Absolute Maximum Ratings (Ta = 25 °)

Reverse Current	100 @ Vr = 5V
Derating	from 50A° @ .25 mA/A°C
Reverse Voltage	5 V
Solder Temp	260A° for 5 sec
Operating Temp	-55 to +100° C
Storage Temp	-55 to +100° C


RoHS / pB Free
[view PDF](#)
Operating Characteristics

LED Position	1,2
Color	Yellow
Lamp Type	Single Color
LED Type	High Efficiency
Intensity Min (mcd)	10
Intensity Typ (mcd)	
Intensity Max (mcd)	50.0
Fwd Voltage Min	
Fwd Voltage Typ	
Fwd Voltage Max	
Dom Wavelength Min (nm)	
Dom Wavelength Typ (nm)	
Dom Wavelength Max (nm)	
Power Dissipation Max (mW)	60
Backlighting	
Pitch Between Vertical	4.57
Pitch Between Horizontal	
Lum Intensity Min	
Lum Intensity Typ	
Lum Intensity Max	

Distributor Stock Check
Check stock with our distributors now.
5692213300F
 [check stock](#)