

Uninterruptible power supply - TRIO- UPS-2G/1AC/1AC/230V/750VA - 2905909

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



1AC/1AC/750 VA uninterruptible power supply with integrated energy storage, lead AGM, VRLA technology, 24 V DC, 3.4 Ah for 230 V AC applications.

Product Description

UPS modules with integrated energy storage are particularly space saving: UPS module and energy storage are combined in one housing. It's just a case of connecting a power supply upstream.


The TRIO AC-UPS ensures seamless transition to battery operation thanks to the pure sine curve. Connected industrial PCs can be shut down safely via the integrated USB interface.

Why buy this product

- ✓ Smooth transition, thanks to the pure sine curve: the sine generated in battery operation is synchronous with the mains previously used for supply
- ✓ Space saving: UPS module and energy storage combined in one housing
- ✓ Long buffer times with integrated VRLA energy storage, can be extended with additional energy storage
- ✓ USB interface for connection to higher-level controllers such as industrial PCs
- ✓ Startup from energy storage possible, even without mains input



Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 007502
GTIN	4055626007502
Weight per Piece (excluding packing)	6,140.000 g
Custom tariff number	85371091
Country of origin	Germany

Technical data

Dimensions

Uninterruptible power supply - TRIO-UPS-2G/1AC/1AC/230V/750VA - 2905909

Technical data

Dimensions

Width	210 mm
Height	170 mm
Depth	136 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	-15 °C ... 40 °C (with charged power storage device)
Max. permissible relative humidity (operation)	≤ 95 % (25°C, non-condensing)
Noise immunity	Noise immunity according to EN 62040-2-2006
Installation height	≤ 3000 mm (> 2000 m, observe derating)

Input data

Nominal input voltage	230 V AC
Input voltage range	184 V AC ... 264 V AC
AC frequency range	45 Hz ... 55 Hz
Input fuse	10 A 400 V gRL
Permissible backup fuse	B6 B10 B16
Power factor (cos phi)	0.8

Output data

Nominal output voltage	230 V AC
Nominal output current (I _N)	3 A
Connection in parallel	No
Connection in series	No

General

Net weight	5.7 kg
Memory medium	Lead rechargeable battery module
Protection class	I
MTBF (IEC 61709, SN 29500)	> 206000 h (40°C)

Connection data, input

Connection method	Push-in connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section AWG min.	24

Uninterruptible power supply - TRIO-UPS-2G/1AC/1AC/230V/750VA - 2905909

Technical data

Connection data, input

Conductor cross section AWG max.	12
Stripping length	10 mm

Connection data, output

Connection method	Push-in connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12
Stripping length	10 mm

Connection data for signaling

Connection method	Push-in connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	1.5 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	1.5 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	16
Stripping length	8 mm

Charging process

Charging time	7 h
---------------	-----

Standards and Regulations

Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU
Shock	20g in all directions (EN 60068-2-27)
Noise immunity	Noise immunity according to EN 62040-2-2006
Standards/regulations	EN 61000-4-2
Contact discharge	4 kV (Test Level 2)
Standards/regulations	EN 61000-4-3
Frequency range	80 MHz ... 1 GHz
Test field strength	10 V/m
Standards/regulations	EN 61000-4-4
Comments	Criterion B
Standards/regulations	EN 61000-4-5

Uninterruptible power supply - TRIO-
UPS-2G/1AC/1AC/230V/750VA - 2905909


Technical data

Standards and Regulations

Signal	1 kV (Test Level 2 - asymmetrical)
Standards/regulations	EN 61000-4-6
Frequency range	0.15 MHz ... 80 MHz
Voltage	10 V
Standards/regulations	EN 61000-4-8
Vibration (operation)	5 Hz ... 100 Hz, 0.7g (EN 60068-2-6)
Low Voltage Directive	Conformance with Low Voltage Directive 2014/35/EC

Drawings

Block diagram



Classifications

eCl@ss

eCl@ss 5.1	27040603
eCl@ss 6.0	27040603
eCl@ss 8.0	27040602
eCl@ss 9.0	27040705

ETIM

ETIM 5.0	EC000382
ETIM 6.0	EC000382

UNSPSC

UNSPSC 13.2	39121011
-------------	----------

Uninterruptible power supply - TRIO-UPS-2G/1AC/1AC/230V/750VA - 2905909

Approvals

Approvals

Approvals

IECEE CB Scheme

Ex Approvals

Approval details

IECEE CB Scheme

CB
scheme

<http://www.iecee.org/>

DK-56005-M1-UL

Accessories

Accessories

Assembly adapter

Assembly adapters - UWA 130 - 2901664



2-piece universal wall adapter for securely mounting the power supply in the event of strong vibrations. The profiles that are screwed onto the side of the power supply are screwed directly onto the mounting surface. The universal wall adapter is attached on the left/right.

Battery unit

Energy storage - QUINT-BAT/24DC/ 3.4AH - 2866349



Energy storage device, lead AGM, VRLA technology, 24 V DC, 3.4 Ah. Connection via pin cable lug, 14 mm.

Data cable preassembled

Uninterruptible power supply - TRIO- UPS-2G/1AC/1AC/230V/750VA - 2905909

Accessories

Data cable - MINI-SCREW-USB-DATACABLE - 2908217



Used for communication between an industrial PC and Phoenix Contact devices with USB-Mini-B connection.

Fuse

Fuse - FUSE 10A/400V GRL - 2908358



Fuse, nominal current: 10 A, length: 31.8 mm, diameter: 6.35 mm

Fuse - FUSE 40A/32V ATOF - 2908357



Fuse, nominal current: 40 A, length: 19 mm, width: 5 mm, height: 18.8 mm