

## Features

- Spread spectrum for EMI reduction
  - Wide spread % option
    - Center spread: from  $\pm 0.125\%$  to  $\pm 2\%$ ,  $\pm 0.125\%$  step size
    - Down spread:  $-0.25\%$  to  $-4\%$  with  $-0.25\%$  step size
  - Spread profile option: Triangular, Hershey-kiss, Random
- Programmable rise/fall time for EMI reduction: 8 options, 0.25 to 40 ns
- AEC-Q100 with extended temperature range ( $-55^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ )
- Any frequency between 1 MHz and 150 MHz accurate to 6 decimal places
- 100% pin-to-pin drop-in replacement to quartz-based XO's
- Excellent total frequency stability as low as  $\pm 25$  ppm
  - [Contact SiTime](#) for  $\pm 20$  ppm option
- Low power consumption of 6.6 mA typical at 1.8 V
- Pin1 modes: Standby, output enable, or spread disable
- LVCMOS output
- Industry-standard packages
  - QFN:  $2.0 \times 1.6 \text{ mm}^2$ ,  $2.5 \times 2.0 \text{ mm}^2$ ,  $3.2 \times 2.5 \text{ mm}^2$
- RoHS and REACH compliant, Pb-free, Halogen-free and Antimony-free

## Applications

- Rear/Surround view camera
- Driver monitor
- ADAS ECU/CPU
- High speed serial link



## Electrical Specifications

**Table 1. Electrical Characteristics**

All Min and Max limits are specified over temperature and rated operating voltage with 15 pF output load unless otherwise stated. Typical values are at  $25^{\circ}\text{C}$  and 3.3 V supply voltage.

| Parameters                             | Symbol | Min. | Typ. | Max. | Unit | Condition                                                                                                                                            |
|----------------------------------------|--------|------|------|------|------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frequency Range                        |        |      |      |      |      |                                                                                                                                                      |
| Output Frequency Range                 | f      | 1    | –    | 150  | MHz  |                                                                                                                                                      |
| Frequency Stability and Aging          |        |      |      |      |      |                                                                                                                                                      |
| Frequency Stability <sup>[1]</sup>     | F_stab | -25  | –    | +25  | ppm  | Inclusive of initial tolerance at 25°C, 1st year aging at 25°C, and variations over operating temperature, rated power supply voltage. Spread = Off. |
|                                        |        | -50  | -    | +50  | ppm  |                                                                                                                                                      |
| Operating Temperature Range            |        |      |      |      |      |                                                                                                                                                      |
| Operating Temperature Range            | T_use  | -40  | –    | +85  | °C   | AEC-Q100 Grade 3                                                                                                                                     |
|                                        |        | -40  | –    | +105 | °C   | AEC-Q100 Grade 2                                                                                                                                     |
|                                        |        | -40  | –    | +125 | °C   | AEC-Q100 Grade 1                                                                                                                                     |
|                                        |        | -55  | –    | +125 | °C   | Extended cold AEC-Q100 Grade 1                                                                                                                       |
| Supply Voltage and Current Consumption |        |      |      |      |      |                                                                                                                                                      |
| Supply Voltage                         | Vdd    | 1.62 | 1.8  | 1.98 | V    |                                                                                                                                                      |
|                                        |        | 2.25 | 2.5  | 2.75 | V    |                                                                                                                                                      |
|                                        |        | 2.52 | 2.8  | 3.08 | V    |                                                                                                                                                      |
|                                        |        | 2.7  | 3.0  | 3.3  | V    |                                                                                                                                                      |
|                                        |        | 2.97 | 3.3  | 3.63 | V    |                                                                                                                                                      |
|                                        |        | 2.25 | –    | 3.63 | V    |                                                                                                                                                      |
| Current Consumption                    | Idd    | –    | 7.9  | 9.5  | mA   | No load condition, f = 148.5 MHz, Vdd = 2.5 V to 3.3 V                                                                                               |
|                                        |        | –    | 6.6  | 8.0  | mA   | No load condition, f = 148.5 MHz, Vdd = 1.8 V                                                                                                        |
| OE Disable Current                     | I_OD   | –    | 5.3  | 6.5  | mA   | f = 148.5 MHz, Vdd = 2.5 V to 3.3 V, OE = GND, Output in high-Z state                                                                                |
|                                        |        | –    | 5.0  | 6.0  | mA   | f = 148.5 MHz, Vdd = 1.8 V, OE = GND, Output in high-Z state                                                                                         |
| Standby Current                        | I_std  | –    | 2.6  | 9.0  | μA   | $\overline{\text{ST}}$ = GND, Vdd = 2.5 V to 3.3 V, Output is weakly pulled down                                                                     |
|                                        |        | –    | 0.6  | 5.0  | μA   | $\overline{\text{ST}}$ = GND, Vdd = 1.8 V, Output is weakly pulled down                                                                              |

Table 1. Electrical Characteristics(continued)

| Parameters                    | Symbol   | Min. | Typ.  | Max. | Unit | Condition                                                                                                    |
|-------------------------------|----------|------|-------|------|------|--------------------------------------------------------------------------------------------------------------|
| LVCMOS Output Characteristics |          |      |       |      |      |                                                                                                              |
| Duty Cycle                    | DC       | 45   | –     | 55   | %    | f = 1 to 137 MHz                                                                                             |
|                               |          | 43   | –     | 57   | %    | f = 137.000001 to 150 MHz                                                                                    |
| Rise/Fall Time                | Tr, Tf   | –    | 1.2   | 2.0  | ns   | 20% - 80%, default derive strength                                                                           |
| Output High Voltage           | VOH      | 90%  | –     | –    | Vdd  | IOH = -4 mA (Vdd = 3.0 V or 3.3 V)<br>IOH = -3 mA (Vdd = 2.8 V and Vdd = 2.5 V)<br>IOH = -2 mA (Vdd = 1.8 V) |
| Output Low Voltage            | VOL      | –    | –     | 10%  | Vdd  | IOL = 4 mA (Vdd = 3.0 V or 3.3 V)<br>IOL = 3 mA (Vdd = 2.8 V and Vdd = 2.5 V)<br>IOL = 2 mA (Vdd = 1.8 V)    |
| Input Characteristics         |          |      |       |      |      |                                                                                                              |
| Input High Voltage            | VIH      | 70%  | –     | –    | Vdd  | Pin 1, OE or $\overline{ST}$                                                                                 |
| Input Low Voltage             | VIL      | –    | –     | 30%  | Vdd  | Pin 1, OE or $\overline{ST}$                                                                                 |
| Input Leakage Current         | IL       | –    | -2.3  | –    | μA   | Pin1, $\overline{ST}$ logic low                                                                              |
|                               |          | –    | 2.8   | –    | μA   | Pin1, $\overline{ST}$ logic high                                                                             |
|                               |          | –    | -24.6 | –    | μA   | Pin1, OE / SD logic low                                                                                      |
|                               |          | –    | 3.2   | –    | μA   | Pin1, OE / SD logic high                                                                                     |
| Startup and Resume Timing     |          |      |       |      |      |                                                                                                              |
| Startup Time                  | T_start  | –    | –     | 10   | ms   | Measured from the time Vdd reaches its rated minimum value                                                   |
| Enable/Disable Time           | T_oe     | –    | –     | 215  | ns   | f = 148.5 MHz. For other frequencies, T_oe = 100 ns + 3 * cycles                                             |
| Resume Time                   | T_resume | –    | –     | 10   | ms   | Measured from the time ST pin crosses 50% threshold                                                          |
| Spread Enable Time            | T_sde    | –    | –     | 4    | μs   | Measured from the time SD pin crosses 50% threshold                                                          |
| Spread Disable Time           | T_sdde   | –    | –     | 55   | μs   | Measured from the time SD pin crosses 50% threshold                                                          |
| Jitter                        |          |      |       |      |      |                                                                                                              |
| Cycle-to-cycle jitter         | T_ccj    | –    | 10.5  | –    | ps   | f = 148.5 MHz, Vdd = 2.5 to 3.3 V, Spread = ON (or OFF)                                                      |
|                               |          | –    | 10.8  | –    | ps   | f = 148.5 MHz, Vdd = 1.8 V, Spread = ON (or OFF)                                                             |

Note:

1. Contact SiTime for ±20 ppm option.

Table 2. Spread Spectrum %<sup>[3]</sup>

| Ordering Code | Center Spread (%) | Down Spread (%) |
|---------------|-------------------|-----------------|
| A             | ±0.125            | -0.25           |
| B             | ±0.250            | -0.50           |
| C             | ±0.390            | -0.78           |
| D             | ±0.515            | -1.04           |
| E             | ±0.640            | -1.29           |
| F             | ±0.765            | -1.55           |
| G             | ±0.905            | -1.84           |
| H             | ±1.030            | -2.10           |
| I             | ±1.155            | -2.36           |
| J             | ±1.280            | -2.62           |
| K             | ±1.420            | -2.91           |
| L             | ±1.545            | -3.18           |
| M             | ±1.670            | -3.45           |
| N             | ±1.795            | -3.71           |
| O             | ±1.935            | -4.01           |
| P             | ±2.060            | -4.28           |

Table 3. Spread Profile<sup>[2,3]</sup>

| Spread Profile |
|----------------|
| Triangular     |
| Hershey-kiss   |
| Random         |

Notes:

2. In both Triangular and Hershey-kiss profiles, modulation rate is employed with a frequency of ~31.25 kHz. In random profile, modulation rate is ~ 8.6 kHz.
3. The random profile supports up to ±1.030% center spread or -2.10% down spread (ordering codes A through H).

Table 4. Pin Description

| Pin | Symbol                             | Functionality  |                                                                                                                                                             |
|-----|------------------------------------|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1   | OE/ $\overline{\text{ST}}$ / NC/SD | Output Enable  | H <sup>[4]</sup> : specified frequency output<br>L: output is high impedance. Only output driver is disabled.                                               |
|     |                                    | Standby        | H <sup>[4]</sup> : specified frequency output<br>L: output is low (weak pull down). Device goes to sleep mode. Supply current reduced to I <sub>std</sub> . |
|     |                                    | No Connect     | Pin1 has no function (Any voltage between 0 and Vdd or Open)                                                                                                |
|     |                                    | Spread Disable | H: Spread = ON<br>L: Spread = OFF                                                                                                                           |
| 2   | GND                                | Power          | Electrical ground                                                                                                                                           |
| 3   | OUT                                | Output         | Oscillator output                                                                                                                                           |
| 4   | VDD                                | Power          | Power supply voltage <sup>[5]</sup>                                                                                                                         |




Figure 1. Pin Assignments

**Notes:**

4. In OE or  $\overline{\text{ST}}$  mode, a pull-up resistor of 10 k $\Omega$  or less is recommended if pin 1 is not externally driven. If pin 1 needs to be left floating, use the NC option.
5. A capacitor of value 0.1  $\mu\text{F}$  or higher between Vdd and GND is required.

Table 5. Absolute Maximum Limits

Attempted operation outside the absolute maximum ratings may cause permanent damage to the part. Actual performance of the IC is only guaranteed within the operational specifications, not at absolute maximum ratings.

| Parameter                                                            | Min. | Max. | Unit               |
|----------------------------------------------------------------------|------|------|--------------------|
| Storage Temperature                                                  | -65  | 150  | $^{\circ}\text{C}$ |
| Vdd                                                                  | -0.5 | 4    | V                  |
| Electrostatic Discharge                                              | –    | 2000 | V                  |
| Soldering Temperature (follow standard Pb free soldering guidelines) | –    | 260  | $^{\circ}\text{C}$ |
| Junction Temperature <sup>[6]</sup>                                  | –    | 150  | $^{\circ}\text{C}$ |

**Note:**

6. Exceeding this temperature for extended period of time may damage the device.

Table 6. Maximum Operating Junction Temperature<sup>[7]</sup>

| Max Operating Temperature (ambient) | Maximum Operating Junction Temperature |
|-------------------------------------|----------------------------------------|
| 85 $^{\circ}\text{C}$               | 95 $^{\circ}\text{C}$                  |
| 105 $^{\circ}\text{C}$              | 115 $^{\circ}\text{C}$                 |
| 125 $^{\circ}\text{C}$              | 135 $^{\circ}\text{C}$                 |

**Note:**

7. Datasheet specifications are not guaranteed if junction temperature exceeds the maximum operating junction temperature.

Table 7. Environmental Compliance

| Parameter                  | Condition/Test Method         |
|----------------------------|-------------------------------|
| Mechanical Shock           | MIL-STD-883F, Method 2002     |
| Mechanical Vibration       | MIL-STD-883F, Method 2007     |
| Temperature Cycle          | JESD22, Method A104           |
| Solderability              | MIL-STD-883F, Method 2003     |
| Moisture Sensitivity Level | MSL1 @ 260 $^{\circ}\text{C}$ |

## Timing Diagrams




Figure 2. Startup Timing




Figure 3. Standby Resume Timing (ST Mode Only)




Figure 4. OE Enable Timing (OE Mode Only)




Figure 5. OE Disable Timing (OE Mode Only)




Figure 6. SD Enable Timing (SD Mode Only)




Figure 7. SD Diable Timing (SD Mode Only)

## Note:

8. SiT9025 has "no runt" pulses and "no glitch" output during startup or resume.

## Performance Plots




Figure 8. OE Disable Current vs Frequency




Figure 9. Current Consumption vs Frequency




Figure 10. Standby Current vs Frequency




Figure 11. Frequency vs Temperature




Figure 12. Cycle-to-cycle Jitter vs Frequency  
 (Spread profile: Triangular, Spread type: center,  
 Spread percentage:  $\pm 2.060\%$ )

## Rise/Fall Time (20% to 80%) vs C<sub>LOAD</sub> Tables

Table 8. V<sub>dd</sub> = 1.8 V Rise/Fall Times for Specific C<sub>LOAD</sub>

| Rise/Fall Time Typ (ns)            |      |       |       |       |       |
|------------------------------------|------|-------|-------|-------|-------|
| Drive Strength \ C <sub>LOAD</sub> | 5 pF | 15 pF | 30 pF | 45 pF | 60 pF |
| L                                  | 6.16 | 11.61 | 22.00 | 31.27 | 39.91 |
| A                                  | 3.19 | 6.35  | 11.00 | 16.01 | 21.52 |
| R                                  | 2.11 | 4.31  | 7.65  | 10.77 | 14.47 |
| B                                  | 1.65 | 3.23  | 5.79  | 8.18  | 11.08 |
| T                                  | 0.93 | 1.91  | 3.32  | 4.66  | 6.48  |
| E                                  | 0.78 | 1.66  | 2.94  | 4.09  | 5.74  |
| U                                  | 0.70 | 1.48  | 2.64  | 3.68  | 5.09  |
| F or "-": default                  | 0.65 | 1.30  | 2.40  | 3.35  | 4.56  |

Table 9. V<sub>dd</sub> = 2.5 V Rise/Fall Times for Specific C<sub>LOAD</sub>

| Rise/Fall Time Typ (ns)            |      |       |       |       |       |
|------------------------------------|------|-------|-------|-------|-------|
| Drive Strength \ C <sub>LOAD</sub> | 5 pF | 15 pF | 30 pF | 45 pF | 60 pF |
| L                                  | 4.13 | 8.25  | 12.82 | 21.45 | 27.79 |
| A                                  | 2.11 | 4.27  | 7.64  | 11.20 | 14.49 |
| R                                  | 1.45 | 2.81  | 5.16  | 7.65  | 9.88  |
| B                                  | 1.09 | 2.20  | 3.88  | 5.86  | 7.57  |
| T                                  | 0.62 | 1.28  | 2.27  | 3.51  | 4.45  |
| E or "-": default                  | 0.54 | 1.00  | 2.01  | 3.10  | 4.01  |
| U                                  | 0.43 | 0.96  | 1.81  | 2.79  | 3.65  |
| F                                  | 0.34 | 0.88  | 1.64  | 2.54  | 3.32  |

Table 10. V<sub>dd</sub> = 2.8 V Rise/Fall Times for Specific C<sub>LOAD</sub>

| Rise/Fall Time Typ (ns)            |      |       |       |       |       |
|------------------------------------|------|-------|-------|-------|-------|
| Drive Strength \ C <sub>LOAD</sub> | 5 pF | 15 pF | 30 pF | 45 pF | 60 pF |
| L                                  | 3.77 | 7.54  | 12.28 | 19.57 | 25.27 |
| A                                  | 1.94 | 3.90  | 7.03  | 10.24 | 13.34 |
| R                                  | 1.29 | 2.57  | 4.72  | 7.01  | 9.06  |
| B                                  | 0.97 | 2.00  | 3.54  | 5.43  | 6.93  |
| T                                  | 0.55 | 1.12  | 2.08  | 3.22  | 4.08  |
| E or "-": default                  | 0.44 | 1.00  | 1.83  | 2.82  | 3.67  |
| U                                  | 0.34 | 0.88  | 1.64  | 2.52  | 3.30  |
| F                                  | 0.29 | 0.81  | 1.48  | 2.29  | 2.99  |

Table 11. V<sub>dd</sub> = 3.0 V Rise/Fall Times for Specific C<sub>LOAD</sub>

| Rise/Fall Time Typ (ns)            |      |       |       |       |       |
|------------------------------------|------|-------|-------|-------|-------|
| Drive Strength \ C <sub>LOAD</sub> | 5 pF | 15 pF | 30 pF | 45 pF | 60 pF |
| L                                  | 3.60 | 7.21  | 11.97 | 18.74 | 24.30 |
| A                                  | 1.84 | 3.71  | 6.72  | 9.86  | 12.68 |
| R                                  | 1.22 | 2.46  | 4.54  | 6.76  | 8.62  |
| B                                  | 0.89 | 1.92  | 3.39  | 5.20  | 6.64  |
| T or "-": default                  | 0.51 | 1.00  | 1.97  | 3.07  | 3.90  |
| E                                  | 0.38 | 0.92  | 1.72  | 2.71  | 3.51  |
| U                                  | 0.30 | 0.83  | 1.55  | 2.40  | 3.13  |
| F                                  | 0.27 | 0.76  | 1.39  | 2.16  | 2.85  |

Table 12. V<sub>dd</sub> = 3.3 V Rise/Fall Times for Specific C<sub>LOAD</sub>

| Rise/Fall Time Typ (ns)            |      |       |       |       |       |
|------------------------------------|------|-------|-------|-------|-------|
| Drive Strength \ C <sub>LOAD</sub> | 5 pF | 15 pF | 30 pF | 45 pF | 60 pF |
| L                                  | 3.39 | 6.88  | 11.63 | 17.56 | 23.59 |
| A                                  | 1.74 | 3.50  | 6.38  | 8.98  | 12.19 |
| R                                  | 1.16 | 2.33  | 4.29  | 6.04  | 8.34  |
| B                                  | 0.81 | 1.82  | 3.22  | 4.52  | 6.33  |
| T or "-": default                  | 0.46 | 1.00  | 1.86  | 2.60  | 3.84  |
| E                                  | 0.33 | 0.87  | 1.64  | 2.30  | 3.35  |
| U                                  | 0.28 | 0.79  | 1.46  | 2.05  | 2.93  |
| F                                  | 0.25 | 0.72  | 1.31  | 1.83  | 2.61  |

## Programmable Drive Strength

The SiT9025 includes a programmable drive strength feature to provide a simple, flexible tool to optimize the clock rise/fall time for specific applications. Benefits from the programmable drive strength feature are:

- Improves system radiated electromagnetic interference (EMI) by slowing down the clock rise/fall time.
- Improves the downstream clock receiver's (RX) jitter by decreasing (speeding up) the clock rise/fall time.
- Ability to drive large capacitive loads while maintaining full swing with sharp edge rates.

For more detailed information about rise/fall time control and drive strength selection, see the [SiTime Application Notes](#) section.

## EMI Reduction by Slowing Rise/Fall Time

Figure 13 shows the harmonic power reduction as the rise/fall times are increased (slowed down). The rise/fall times are expressed as a ratio of the clock period. For the ratio of 0.05, the signal is very close to a square wave. For the ratio of 0.45, the rise/fall times are very close to near-triangular waveform. These results, for example, show that the 11<sup>th</sup> clock harmonic can be reduced by 35 dB if the rise/fall edge is increased from 5% of the period to 45% of the period.




Figure 13. Harmonic EMI reduction as a function of slower rise/fall time

## Jitter Reduction with Faster Rise/Fall Time

Power supply noise can be a source of jitter for the downstream chipset. One way to reduce this jitter is to increase rise/fall time (edge rate) of the input clock. Some chipsets would require faster rise/fall time in order to reduce their sensitivity to this type of jitter. The SiT9025 provides up to 3 additional high drive strength settings for very fast rise/fall time. Refer to the [Rise/Fall Time Tables](#) to determine the proper drive strength.

## High Output Load Capability

The rise/fall time of the input clock varies as a function of the actual capacitive load the clock drives. At any given drive strength, the rise/fall time becomes slower as the

output load increases. As an example, for a 3.3 V SiT9025 device with default drive strength setting, the typical rise/fall time is 1.1 ns for 15 pF output load. The typical rise/fall time slows down to 2.9 ns when the output load increases to 45 pF. One can choose to speed up the rise/fall time to 1.9 ns by then increasing the drive strength setting on the SiT9025.

The SiT9025 can support up to 60 pF or higher in maximum capacitive loads with up to 3 additional drive strength settings. Refer to the [Rise/Fall Time Tables](#) to determine the proper drive strength for the desired combination of output load vs. rise/fall time.

## SiT9025 Drive Strength Selection

Tables 8 through 12 define the rise/fall time for a given capacitive load and supply voltage.

1. Select the table that matches the SiT9025 nominal supply voltage (1.8 V, 2.5 V, 2.8 V, 3.3 V).
2. Select the capacitive load column that matches the application requirement (15 pF to 60 pF)
3. Under the capacitive load column, select the desired rise/fall times.
4. The left-most column represents the part number code for the corresponding drive strength.
5. Add the drive strength code to the part number for ordering purposes.

## Calculating Maximum Frequency

Based on the rise and fall time data given in Tables 8 through 12, the maximum frequency the oscillator can operate with guaranteed full swing of the output voltage over temperature as follows:

$$\text{Max Frequency} = \frac{1}{5 \times \text{Trf}_{20/80}}$$

where Trf<sub>20/80</sub> is the typical value for 20%-80% rise/fall time.

## Example 1

Calculate f<sub>MAX</sub> for the following condition:

- Vdd = 1.8 V ([Table 8](#))
- Capacitive Load: 30 pF
- Desired Tr/f time = 3 ns (rise/fall time part number code = E)

Part number for the above example:

SiT9025AAE12-18E-66.666660







Drive strength code is inserted here. Default setting is “-”


## Supplied Voltage

The supplied voltage must always stay within the range from minimum to maximum limits of rated operating voltage to guarantee specification performance. The supply voltage must drop below 0.6 V for the device to reset.

## Dimensions and Patterns

| Package Size – Dimensions (Unit: mm) <sup>[9]</sup>                                 |                         | Recommended Land Pattern (Unit: mm) <sup>[10]</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
|-------------------------------------------------------------------------------------|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------|--------|-----|-----|-----|-------------------|---|-------|-------|-------|-----------|----|-------|-------|-------|-----------|---|---|-------|-----|---|---|-------|-----|------------|---|-------|-------|-------|-------------|-------|-------|-------|-------------|------------|-------|-------|-------|----|-------------------|-----|-------|------------|---|---------------|-----|-------|--------|---|-------------|-----|-------|-------------------|-----|-------|---------|---------|-------------------------|-------------------|------------|------------------|------------|-------------|-----|-------|--|--|-------|---------|---------|-------------------------|-------------------|------------|------------------|------------|
| 2.0 x 1.6 x 0.75 mm                                                                 |                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
|    |                         | <table><thead><tr><th></th><th>SYMBOL</th><th>MIN</th><th>NOM</th><th>MAX</th></tr></thead><tbody><tr><td>PACKAGE THICKNESS</td><td>A</td><td>0.700</td><td>0.750</td><td>0.800</td></tr><tr><td>STAND OFF</td><td>A1</td><td>0.000</td><td>0.020</td><td>0.050</td></tr><tr><td rowspan="2">BODY SIZE</td><td>X</td><td>D</td><td>1.600</td><td>BSC</td></tr><tr><td>Y</td><td>E</td><td>2.000</td><td>BSC</td></tr><tr><td rowspan="2">LEAD WIDTH</td><td>b</td><td>0.430</td><td>0.480</td><td>0.530</td></tr><tr><td>b1</td><td>0.230</td><td>0.280</td><td>0.330</td></tr><tr><td rowspan="2">LEAD LENGTH</td><td>L</td><td>0.580</td><td>0.680</td><td>0.780</td></tr><tr><td>L1</td><td>0.100</td><td>REF</td><td></td></tr><tr><td>LEAD PITCH</td><td>e</td><td>0.930</td><td>BSC</td><td></td></tr><tr><td>RADIUS</td><td>F</td><td>0.100</td><td>REF</td><td></td></tr><tr><td>PACKAGE TOLERANCE</td><td>aaa</td><td>0.050</td><td></td><td></td></tr><tr><td>MOLD FLATNESS</td><td>bbb</td><td>0.100</td><td></td><td></td></tr><tr><td>COPLANARITY</td><td>ccc</td><td>0.080</td><td></td><td></td></tr></tbody></table> <p>NOTES</p> <p>1. Dimensioning and tolerance conform to ASME Y14.5-2009</p> <p>2. All dimensions are in millimeters.</p> <div></div> <table><tr><th>TITLE</th><th>DWG NO.</th></tr><tr><td>4L PQFN</td><td>POD-PQFN-004-X01620-026</td></tr><tr><td>1.60x2.00x0.75 mm</td><td>REV. SHEET</td></tr><tr><td>DATE 01-APR-2019</td><td>A02 1 OF 2</td></tr></table> |       |       | SYMBOL | MIN | NOM | MAX | PACKAGE THICKNESS | A | 0.700 | 0.750 | 0.800 | STAND OFF | A1 | 0.000 | 0.020 | 0.050 | BODY SIZE | X | D | 1.600 | BSC | Y | E | 2.000 | BSC | LEAD WIDTH | b | 0.430 | 0.480 | 0.530 | b1          | 0.230 | 0.280 | 0.330 | LEAD LENGTH | L          | 0.580 | 0.680 | 0.780 | L1 | 0.100             | REF |       | LEAD PITCH | e | 0.930         | BSC |       | RADIUS | F | 0.100       | REF |       | PACKAGE TOLERANCE | aaa | 0.050 |         |         | MOLD FLATNESS           | bbb               | 0.100      |                  |            | COPLANARITY | ccc | 0.080 |  |  | TITLE | DWG NO. | 4L PQFN | POD-PQFN-004-X01620-026 | 1.60x2.00x0.75 mm | REV. SHEET | DATE 01-APR-2019 | A02 1 OF 2 |
|                                                                                     | SYMBOL                  | MIN                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | NOM   | MAX   |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| PACKAGE THICKNESS                                                                   | A                       | 0.700                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0.750 | 0.800 |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| STAND OFF                                                                           | A1                      | 0.000                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0.020 | 0.050 |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| BODY SIZE                                                                           | X                       | D                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 1.600 | BSC   |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
|                                                                                     | Y                       | E                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 2.000 | BSC   |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| LEAD WIDTH                                                                          | b                       | 0.430                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0.480 | 0.530 |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
|                                                                                     | b1                      | 0.230                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0.280 | 0.330 |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| LEAD LENGTH                                                                         | L                       | 0.580                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0.680 | 0.780 |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
|                                                                                     | L1                      | 0.100                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | REF   |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| LEAD PITCH                                                                          | e                       | 0.930                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | BSC   |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| RADIUS                                                                              | F                       | 0.100                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | REF   |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| PACKAGE TOLERANCE                                                                   | aaa                     | 0.050                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| MOLD FLATNESS                                                                       | bbb                     | 0.100                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| COPLANARITY                                                                         | ccc                     | 0.080                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| TITLE                                                                               | DWG NO.                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| 4L PQFN                                                                             | POD-PQFN-004-X01620-026 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| 1.60x2.00x0.75 mm                                                                   | REV. SHEET              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| DATE 01-APR-2019                                                                    | A02 1 OF 2              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| 2.5 x 2.0 x 0.75 mm                                                                 |                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
|  |                         | <table><thead><tr><th></th><th>SYMBOL</th><th>MIN</th><th>NOM</th><th>MAX</th></tr></thead><tbody><tr><td>PACKAGE THICKNESS</td><td>A</td><td>0.700</td><td>0.750</td><td>0.800</td></tr><tr><td>THICKNESS</td><td>A1</td><td>0.000</td><td>0.020</td><td>0.050</td></tr><tr><td rowspan="2">BODY SIZE</td><td>X</td><td>D</td><td>2.000</td><td>BSC</td></tr><tr><td>Y</td><td>E</td><td>2.500</td><td>BSC</td></tr><tr><td>LEAD WIDTH</td><td>b</td><td>0.300</td><td>0.350</td><td>0.400</td></tr><tr><td>LEAD LENGTH</td><td>L</td><td>0.650</td><td>0.750</td><td>0.850</td></tr><tr><td>LEAD PITCH</td><td>e</td><td>1.250</td><td>BSC</td><td></td></tr><tr><td>PACKAGE TOLERANCE</td><td>aaa</td><td>0.050</td><td></td><td></td></tr><tr><td>MOLD FLATNESS</td><td>bbb</td><td>0.100</td><td></td><td></td></tr><tr><td>COPLANARITY</td><td>ccc</td><td>0.080</td><td></td><td></td></tr></tbody></table> <p>NOTES</p> <p>1. Dimensioning and tolerance conform to ASME Y14.5-2009</p> <p>2. All dimensions are in millimeters.</p> <div></div> <table><tr><th>TITLE</th><th>DWG NO.</th></tr><tr><td>4L PQFN</td><td>POD-PQFN-004-X02025-010</td></tr><tr><td>2.00x2.50x0.75 mm</td><td>REV. SHEET</td></tr><tr><td>DATE 01-APR-2019</td><td>A02 1 OF 2</td></tr></table>                                                                                                                                                                                                                 |       |       | SYMBOL | MIN | NOM | MAX | PACKAGE THICKNESS | A | 0.700 | 0.750 | 0.800 | THICKNESS | A1 | 0.000 | 0.020 | 0.050 | BODY SIZE | X | D | 2.000 | BSC | Y | E | 2.500 | BSC | LEAD WIDTH | b | 0.300 | 0.350 | 0.400 | LEAD LENGTH | L     | 0.650 | 0.750 | 0.850       | LEAD PITCH | e     | 1.250 | BSC   |    | PACKAGE TOLERANCE | aaa | 0.050 |            |   | MOLD FLATNESS | bbb | 0.100 |        |   | COPLANARITY | ccc | 0.080 |                   |     | TITLE | DWG NO. | 4L PQFN | POD-PQFN-004-X02025-010 | 2.00x2.50x0.75 mm | REV. SHEET | DATE 01-APR-2019 | A02 1 OF 2 |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
|                                                                                     | SYMBOL                  | MIN                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | NOM   | MAX   |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| PACKAGE THICKNESS                                                                   | A                       | 0.700                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0.750 | 0.800 |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| THICKNESS                                                                           | A1                      | 0.000                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0.020 | 0.050 |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| BODY SIZE                                                                           | X                       | D                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 2.000 | BSC   |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
|                                                                                     | Y                       | E                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 2.500 | BSC   |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| LEAD WIDTH                                                                          | b                       | 0.300                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0.350 | 0.400 |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| LEAD LENGTH                                                                         | L                       | 0.650                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0.750 | 0.850 |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| LEAD PITCH                                                                          | e                       | 1.250                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | BSC   |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| PACKAGE TOLERANCE                                                                   | aaa                     | 0.050                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| MOLD FLATNESS                                                                       | bbb                     | 0.100                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| COPLANARITY                                                                         | ccc                     | 0.080                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| TITLE                                                                               | DWG NO.                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| 4L PQFN                                                                             | POD-PQFN-004-X02025-010 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| 2.00x2.50x0.75 mm                                                                   | REV. SHEET              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |
| DATE 01-APR-2019                                                                    | A02 1 OF 2              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |       |       |        |     |     |     |                   |   |       |       |       |           |    |       |       |       |           |   |   |       |     |   |   |       |     |            |   |       |       |       |             |       |       |       |             |            |       |       |       |    |                   |     |       |            |   |               |     |       |        |   |             |     |       |                   |     |       |         |         |                         |                   |            |                  |            |             |     |       |  |  |       |         |         |                         |                   |            |                  |            |

Dimensions and Patterns



Notes:

- Top marking: Y denotes manufacturing origin and XXXX denotes manufacturing lot number. The value of "Y" will depend on the assembly location of the device.
- A capacitor of value 0.1  $\mu$ F or higher between Vdd and GND is required.

## Ordering Information

The following part number guide is for reference only. To customize and build an exact part number, use the SiTime [Part Number Generator](#).

### SiT9025AA-73-18E A 25.000625D

|                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |       |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|---------|-------|-----|-------------|-------|-----|-------------|-------|-----|-------------|-------|-----|-------------|-------|-----|-------------|-------|-----|-------------|-------|-----|-------------|-------|-----|-------------|-------|-----|-------------|-------|-----|-------------|-------|-----|-------------|-------|-----|-------------|-------|-----|-------------|-------|-----|-------------|-------|-----|-------------|-------|-----|-------------|-------|
| <b>Part Family</b><br>"SiT9025"                                                                                                                                                                                                                                                 | <b>Packing Method</b><br>"D": 8 mm Tape & Reel, 3 ku reel<br>"E": 8 mm Tape & Reel, 1 ku reel<br>Blank for Bulk                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |       |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| <b>Revision Letter</b><br>"A" is the revision                                                                                                                                                                                                                                   | <b>Frequency</b> <sup>[12]</sup><br>1.000000 to 150.000000 MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |       |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| <b>Temperature Range</b><br>"I" -40°C to 85°C, AEC-Q100 Grade3<br>"E" -40°C to 105°C, AEC-Q100 Grade2<br>"A" -40°C to 125°C, AEC-Q100 Grade1<br>"M" -55°C to 125°C, Ext cold AEC-Q100 Grade1                                                                                    | <b>Spread Percentage</b> <sup>[13]</sup><br>"-" no spread<br><table><tr><td></td><td>Center:</td><td>Down:</td></tr><tr><td>"A"</td><td>for ±0.125,</td><td>-0.25</td></tr><tr><td>"B"</td><td>for ±0.250,</td><td>-0.50</td></tr><tr><td>"C"</td><td>for ±0.390,</td><td>-0.78</td></tr><tr><td>"D"</td><td>for ±0.515,</td><td>-1.04</td></tr><tr><td>"E"</td><td>for ±0.640,</td><td>-1.29</td></tr><tr><td>"F"</td><td>for ±0.765,</td><td>-1.55</td></tr><tr><td>"G"</td><td>for ±0.905,</td><td>-1.84</td></tr><tr><td>"H"</td><td>for ±1.030,</td><td>-2.10</td></tr><tr><td>"I"</td><td>for ±1.155,</td><td>-2.36</td></tr><tr><td>"J"</td><td>for ±1.280,</td><td>-2.62</td></tr><tr><td>"K"</td><td>for ±1.420,</td><td>-2.91</td></tr><tr><td>"L"</td><td>for ±1.545,</td><td>-3.18</td></tr><tr><td>"M"</td><td>for ±1.670,</td><td>-3.45</td></tr><tr><td>"N"</td><td>for ±1.795,</td><td>-3.71</td></tr><tr><td>"O"</td><td>for ±1.935,</td><td>-4.01</td></tr><tr><td>"P"</td><td>for ±2.060,</td><td>-4.28</td></tr></table> |       | Center: | Down: | "A" | for ±0.125, | -0.25 | "B" | for ±0.250, | -0.50 | "C" | for ±0.390, | -0.78 | "D" | for ±0.515, | -1.04 | "E" | for ±0.640, | -1.29 | "F" | for ±0.765, | -1.55 | "G" | for ±0.905, | -1.84 | "H" | for ±1.030, | -2.10 | "I" | for ±1.155, | -2.36 | "J" | for ±1.280, | -2.62 | "K" | for ±1.420, | -2.91 | "L" | for ±1.545, | -3.18 | "M" | for ±1.670, | -3.45 | "N" | for ±1.795, | -3.71 | "O" | for ±1.935, | -4.01 | "P" | for ±2.060, | -4.28 |
|                                                                                                                                                                                                                                                                                 | Center:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Down: |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "A"                                                                                                                                                                                                                                                                             | for ±0.125,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -0.25 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "B"                                                                                                                                                                                                                                                                             | for ±0.250,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -0.50 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "C"                                                                                                                                                                                                                                                                             | for ±0.390,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -0.78 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "D"                                                                                                                                                                                                                                                                             | for ±0.515,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -1.04 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "E"                                                                                                                                                                                                                                                                             | for ±0.640,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -1.29 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "F"                                                                                                                                                                                                                                                                             | for ±0.765,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -1.55 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "G"                                                                                                                                                                                                                                                                             | for ±0.905,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -1.84 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "H"                                                                                                                                                                                                                                                                             | for ±1.030,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -2.10 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "I"                                                                                                                                                                                                                                                                             | for ±1.155,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -2.36 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "J"                                                                                                                                                                                                                                                                             | for ±1.280,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -2.62 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "K"                                                                                                                                                                                                                                                                             | for ±1.420,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -2.91 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "L"                                                                                                                                                                                                                                                                             | for ±1.545,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -3.18 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "M"                                                                                                                                                                                                                                                                             | for ±1.670,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -3.45 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "N"                                                                                                                                                                                                                                                                             | for ±1.795,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -3.71 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "O"                                                                                                                                                                                                                                                                             | for ±1.935,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -4.01 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "P"                                                                                                                                                                                                                                                                             | for ±2.060,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -4.28 |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| <b>Output Drive Strength</b><br>"-" Default (datasheet limits)<br><a href="#">See Tables 8 to 12 for rise/fall times</a><br><table><tr><td>"L"</td><td>"T"</td></tr><tr><td>"A"</td><td>"E"</td></tr><tr><td>"R"</td><td>"U"</td></tr><tr><td>"B"</td><td>"F"</td></tr></table> | "L"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | "T"   | "A"     | "E"   | "R" | "U"         | "B"   | "F" |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "L"                                                                                                                                                                                                                                                                             | "T"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |       |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "A"                                                                                                                                                                                                                                                                             | "E"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |       |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "R"                                                                                                                                                                                                                                                                             | "U"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |       |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| "B"                                                                                                                                                                                                                                                                             | "F"                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |       |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| <b>Package Size</b><br>"7" 2.0 mm x 1.6 mm<br>"1" 2.5 mm x 2.0 mm<br>"2" 3.2 mm x 2.5 mm                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |       |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| <b>Frequency Stability</b> <sup>[11]</sup><br>"3" for ±50 ppm<br>"2" for ±25 ppm                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |       |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
| <b>Spread Type and Profile</b><br>"-" Center spread & Triangular (Default)<br>"H" Center spread & Hershey Kiss<br>"R" Center spread & Random<br>"D" Down spread & Triangular<br>"G" Down spread & Hershey Kiss<br>"Q" Down spread & Random                                      | <b>Feature Pin</b><br>"E" for Output Enable<br>"S" for Standby<br>"N" for No Connect<br>"D" for Spread Disabled                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |       |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |
|                                                                                                                                                                                                                                                                                 | <b>Supply Voltage</b><br>"18" for 1.8 V ±10%<br>"25" for 2.5 V ±10%<br>"28" for 2.8 V ±10%<br>"30" for 3.0 V ±10%<br>"33" for 3.3 V ±10%<br>"XX" for 2.5 V -10% to 3.3 V +10%                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |       |         |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |     |             |       |

**Note:**

11. [Contact SiTime](#) for ±20 ppm option.
12. Refer to the [Supported Frequencies](#) tables below.
13. The random profile supports up to ±1.030% center spread or -2.10% down spread (ordering codes A through H).

## Supported Frequencies Tables

**Table 13. Supported Frequencies**  
(-40 to +85°C, Center spread)

| Spread Percentage (%) | Supported Frequencies (MHz) |           |
|-----------------------|-----------------------------|-----------|
| Center spread         | Min.                        | Max.      |
| "A": ±0.125           | 1.000000                    | 150.00000 |
| "B": ±0.250           |                             |           |
| "C": ±0.390           |                             |           |
| "D": ±0.515           |                             |           |
| "E": ±0.640           |                             |           |
| "F": ±0.765           |                             |           |
| "G": ±0.905           |                             |           |
| "H": ±1.030           |                             |           |
| "I": ±1.155           |                             |           |
| "J": ±1.280           |                             |           |
| "K": ±1.420           |                             |           |
| "L": ±1.545           |                             |           |
| "M": ±1.670           |                             |           |
| "N": ±1.795           |                             |           |
| "O": ±1.935           |                             |           |
| "P": ±2.060           |                             |           |

**Table 14. Supported Frequencies**  
(-40 to +85°C, Down spread)

| Spread Percentage (%) | Supported Frequencies (MHz) |           |
|-----------------------|-----------------------------|-----------|
| Down spread           | Min.                        | Max.      |
| "A": -0.25            | 1.000000                    | 150.00000 |
| "B": -0.50            |                             |           |
| "C": -0.78            |                             |           |
| "D": -1.04            |                             |           |
| "E": -1.29            |                             |           |
| "F": -1.55            |                             |           |
| "G": -1.84            |                             |           |
| "H": -2.10            |                             |           |
| "I": -2.36            |                             |           |
| "J": -2.62            |                             |           |
| "K": -2.91            |                             |           |
| "L": -3.18            |                             |           |
| "M": -3.45            |                             |           |
| "N": -3.71            |                             |           |
| "O": -4.01            |                             |           |
| "P": -4.28            |                             |           |

**Table 15. Supported Frequencies**  
(-40 to +105°C or -40 to +125°C, Center spread)

| Spread Percentage (%) | Supported Frequencies (MHz) |            |
|-----------------------|-----------------------------|------------|
| Center spread         | Min.                        | Max.       |
| "A": ±0.125           | 1.000000                    | 150.000000 |
| "B": ±0.250           |                             |            |
| "C": ±0.390           |                             |            |
| "D": ±0.515           |                             |            |
| "E": ±0.640           |                             |            |
| "F": ±0.765           |                             |            |
| "G": ±0.905           |                             |            |
| "H": ±1.030           |                             |            |
| "I": ±1.155           |                             |            |
| "J": ±1.280           |                             |            |
| "K": ±1.420           | 1.000000                    | 149.900000 |
| "L": ±1.545           | 1.000000                    | 120.100000 |
|                       | 120.700000                  | 149.800000 |
| "M": ±1.670           | 1.000000                    | 119.900000 |
|                       | 124.500000                  | 149.600000 |
| "N": ±1.795           | 1.000000                    | 100.100000 |
|                       | 102.700000                  | 119.600000 |
|                       | 128.400000                  | 149.300000 |
| "O": ±1.935           | 1.000000                    | 85.800000  |
|                       | 86.100000                   | 100.100000 |
|                       | 103.400000                  | 119.400000 |
|                       | 129.200000                  | 149.100000 |
| "P": ±2.060           | 1.000000                    | 74.500000  |
|                       | 75.800000                   | 85.400000  |
|                       | 88.500000                   | 99.300000  |
|                       | 106.200000                  | 119.200000 |
|                       | 132.700000                  | 148.900000 |

**Table 16. Supported Frequencies**  
(-40 to +105°C or -40 to +125°C, Down spread)

| Spread Percentage (%)                                                                                                                                                              | Supported Frequencies (MHz) |            |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|------------|
| Down spread                                                                                                                                                                        | Min.                        | Max.       |
| "A": -0.25<br>"B": -0.50<br>"C": -0.78<br>"D": -1.04<br>"E": -1.29<br>"F": -1.55<br>"G": -1.84<br>"H": -2.10<br>"I": -2.36<br>"J": -2.62<br>"K": -2.91<br>"L": -3.18<br>"M": -3.45 | 1.000000                    | 150.000000 |
| "N": -3.71                                                                                                                                                                         | 1.000000                    | 120.100000 |
|                                                                                                                                                                                    | 123.200000                  | 150.000000 |
| "O": -4.01                                                                                                                                                                         | 1.000000                    | 100.100000 |
|                                                                                                                                                                                    | 101.600000                  | 120.100000 |
|                                                                                                                                                                                    | 127.000000                  | 150.000000 |
| "P": -4.28                                                                                                                                                                         | 1.000000                    | 85.800000  |
|                                                                                                                                                                                    | 87.400000                   | 100.100000 |
|                                                                                                                                                                                    | 102.400000                  | 102.900000 |
|                                                                                                                                                                                    | 104.800000                  | 120.100000 |
|                                                                                                                                                                                    | 128.100000                  | 128.600000 |
|                                                                                                                                                                                    | 131.100000                  | 150.000000 |

**Table 17. Supported Frequencies**  
**(-55 to +125°C, Center spread)**

| Spread Percentage (%)                                                                                                                                                                                | Supported Frequencies (MHz) |            |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|------------|
| Center spread                                                                                                                                                                                        | Min.                        | Max.       |
| "A": $\pm 0.125$<br>"B": $\pm 0.250$<br>"C": $\pm 0.390$<br>"D": $\pm 0.515$<br>"E": $\pm 0.640$<br>"F": $\pm 0.765$<br>"G": $\pm 0.905$<br>"H": $\pm 1.030$<br>"I": $\pm 1.155$<br>"J": $\pm 1.280$ | 1.000000                    | 150.000000 |
| "K": $\pm 1.420$                                                                                                                                                                                     | 1.000000                    | 120.100000 |
|                                                                                                                                                                                                      | 120.900000                  | 149.900000 |
| "L": $\pm 1.545$                                                                                                                                                                                     | 1.000000                    | 120.100000 |
|                                                                                                                                                                                                      | 124.700000                  | 149.800000 |
| "M": $\pm 1.670$                                                                                                                                                                                     | 1.000000                    | 100.100000 |
|                                                                                                                                                                                                      | 102.900000                  | 119.800000 |
|                                                                                                                                                                                                      | 128.600000                  | 149.600000 |
| "N": $\pm 1.795$                                                                                                                                                                                     | 1.000000                    | 85.800000  |
|                                                                                                                                                                                                      | 86.300000                   | 100.100000 |
|                                                                                                                                                                                                      | 103.500000                  | 119.600000 |
|                                                                                                                                                                                                      | 129.400000                  | 149.300000 |
| "O": $\pm 1.935$                                                                                                                                                                                     | 1.000000                    | 74.600000  |
|                                                                                                                                                                                                      | 75.900000                   | 85.600000  |
|                                                                                                                                                                                                      | 88.600000                   | 99.500000  |
|                                                                                                                                                                                                      | 106.300000                  | 119.400000 |
|                                                                                                                                                                                                      | 132.900000                  | 149.100000 |
| "P": $\pm 2.060$                                                                                                                                                                                     | 1.000000                    | 60.100000  |
|                                                                                                                                                                                                      | 60.200000                   | 66.500000  |
|                                                                                                                                                                                                      | 67.700000                   | 74.500000  |
|                                                                                                                                                                                                      | 77.400000                   | 85.400000  |
|                                                                                                                                                                                                      | 90.300000                   | 99.300000  |
|                                                                                                                                                                                                      | 108.400000                  | 119.100000 |
|                                                                                                                                                                                                      | 135.500000                  | 148.900000 |

**Table 18. Supported Frequencies**  
**(-55 to +125°C, Down spread)**

| Spread Percentage (%)                                                                                                                                                | Supported Frequencies (MHz) |            |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|------------|
| Down spread                                                                                                                                                          | Min.                        | Max.       |
| "A": -0.25<br>"B": -0.50<br>"C": -0.78<br>"D": -1.04<br>"E": -1.29<br>"F": -1.55<br>"G": -1.84<br>"H": -2.10<br>"I": -2.36<br>"J": -2.62<br>"K": -2.91<br>"L": -3.18 | 1.000000                    | 150.000000 |
| "M": -3.45                                                                                                                                                           | 1.000000                    | 120.100000 |
|                                                                                                                                                                      | 123.400000                  | 150.000000 |
| "N": -3.71                                                                                                                                                           | 1.000000                    | 100.100000 |
|                                                                                                                                                                      | 101.800000                  | 120.100000 |
|                                                                                                                                                                      | 127.300000                  | 150.000000 |
| "O": -4.01                                                                                                                                                           | 1.000000                    | 85.800000  |
|                                                                                                                                                                      | 87.500000                   | 100.100000 |
|                                                                                                                                                                      | 102.600000                  | 102.800000 |
|                                                                                                                                                                      | 105.000000                  | 120.100000 |
|                                                                                                                                                                      | 128.200000                  | 128.500000 |
|                                                                                                                                                                      | 131.300000                  | 150.000000 |
| "P": -4.28                                                                                                                                                           | 1.000000                    | 75.100000  |
|                                                                                                                                                                      | 75.600000                   | 85.800000  |
|                                                                                                                                                                      | 88.200000                   | 100.100000 |
|                                                                                                                                                                      | 105.800000                  | 120.100000 |
|                                                                                                                                                                      | 132.300000                  | 150.000000 |

Table 19. Additional information

| Document               | Description                                                                | Download Link                                                                                                             |
|------------------------|----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Manufacturing Notes    | Tape & Reel dimension, reflow profile and other manufacturing related info | <a href="http://www.sitime.com/manufacturing-notes">http://www.sitime.com/manufacturing-notes</a>                         |
| Qualification Reports  | RoHS report, reliability reports, composition reports                      | <a href="http://www.sitime.com/support/quality-and-reliability">http://www.sitime.com/support/quality-and-reliability</a> |
| Termination Techniques | Termination design recommendations                                         | <a href="http://www.sitime.com/support/application-notes">http://www.sitime.com/support/application-notes</a>             |
| Layout Techniques      | Layout recommendations                                                     | <a href="http://www.sitime.com/support/application-notes">http://www.sitime.com/support/application-notes</a>             |

Table 20. Revision history

| Version | Release Date | Change Summary                                                                                                                                                 |
|---------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.0     | 9-Jun-2020   | Final release<br>Formatting updates                                                                                                                            |
| 1.01    | 9-Sep-2020   | Supply voltage information update<br>Added $\pm 25$ ppm frequency stability<br>Figure 8 and 9 captions fix<br>Changed date format in rev table to d/month/yyyy |

---

**SiTime Corporation**, 5451 Patrick Henry Drive, Santa Clara, CA 95054, USA | **Phone:** +1-408-328-4400 | **Fax:** +1-408-328-4439

---

© SiTime Corporation 2019-2020. The information contained herein is subject to change at any time without notice. SiTime assumes no responsibility or liability for any loss, damage or defect of a Product which is caused in whole or in part by (i) use of any circuitry other than circuitry embodied in a SiTime product, (ii) misuse or abuse including static discharge, neglect or accident, (iii) unauthorized modification or repairs which have been soldered or altered during assembly and are not capable of being tested by SiTime under its normal test conditions, or (iv) improper installation, storage, handling, warehousing or transportation, or (v) being subjected to unusual physical, thermal, or electrical stress.

**Disclaimer:** SiTime makes no warranty of any kind, express or implied, with regard to this material, and specifically disclaims any and all express or implied warranties, either in fact or by operation of law, statutory or otherwise, including the implied warranties of merchantability and fitness for use or a particular purpose, and any implied warranty arising from course of dealing or usage of trade, as well as any common-law duties relating to accuracy or lack of negligence, with respect to this material, any SiTime product and any product documentation. Products sold by SiTime are not suitable or intended to be used in a life support application or component, to operate nuclear facilities, or in other mission critical applications where human life may be involved or at stake. All sales are made conditioned upon compliance with the critical uses policy set forth below.

**CRITICAL USE EXCLUSION POLICY**

**BUYER AGREES NOT TO USE SITIME'S PRODUCTS FOR ANY APPLICATION OR IN ANY COMPONENTS USED IN LIFE SUPPORT DEVICES OR TO OPERATE NUCLEAR FACILITIES OR FOR USE IN OTHER MISSION-CRITICAL APPLICATIONS OR COMPONENTS WHERE HUMAN LIFE OR PROPERTY MAY BE AT STAKE.**

SiTime owns all rights, title and interest to the intellectual property related to SiTime's products, including any software, firmware, copyright, patent, or trademark. The sale of SiTime products does not convey or imply any license under patent or other rights. SiTime retains the copyright and trademark rights in all documents, catalogs and plans supplied pursuant to or ancillary to the sale of products or services by SiTime. Unless otherwise agreed to in writing by SiTime, any reproduction, modification, translation, compilation, or representation of this material shall be strictly prohibited.