

Dual Band Swivel Mount Dipole RP-TNC Blade

2.40-2.50/4.90-5.90 GHz

R380500314

Series: ANTENNA



All dimensions are inches

Issue : 1735

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe.

Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.



Dual Band Swivel Mount Dipole RP-TNC Blade

2.40-2.50/4.90-5.90 GHz

R380500314

Series: ANTENNA

ELECTRICAL SPECIFICATIONS

Frequency :.....	2.40-2.50/4.90-5.90 GHz
Nominal Impedance :.....	50 Ω
VSWR :.....	2.5:1 Max
Gain (Radiating element) :.....	1.6/5.0 dBi ± 1 dB
Radiation Pattern	
HPBW in Horizontal Plane :	360 ° ± 2 °
Ripple level in Horizontal Plane :	±3 dB Max
HPBW in Elevation	
Low Band :	85 °
High Band :	30 °
Polarization :	Linear Vertical
Connector type :	Reverse Polarity TNC
Cable type :	RG316

Issue : 1735

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe.

Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.



Dual Band Swivel Mount Dipole RP-TNC Blade

2.40-2.50/4.90-5.90 GHz

R380500314

Series: ANTENNA

MECHANICAL SPECIFICATIONS

Plastic radome :	ABS+PC
Color :	Black
Flammability Rating :	V-0 UL 94
Weight :	1.2 oz
Overall length :	6.9 Inches
Bent	5.9 Inches
Fixing system :	
Azimuth adjustment	$^{\circ} \pm 4^{\circ}$
Elevation adjustment	$^{\circ} \pm 4^{\circ}$

ENVIRONMENTAL SPECIFICATIONS

Operating temperature :	-30/+70 ° C
Storage temperature :	-40/+85 ° C
Humidity :	95% @ 24° C

OTHER SPECIFICATIONS

Issue : 1735

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

CONFIDENTIAL AND PROPRIETARY INFORMATION

This document contains confidential and proprietary information of Pulse Electronics, Inc. (Pulse) and is protected by copyright, trade secret and other state and federal laws. Its receipt or possession does not convey any rights to reproduce, disclose its contents, or to manufacture, use or sell anything it may describe.

Reproduction, disclosure or use without specific written authorization of Pulse is strictly forbidden.

