

PB Busway Tap Off Unit, 1x3 pole 5 Wires 30A, 1 Drop Cord, 3ft, L21-30, 208Y/120V

PBP4A13L2130F

! Discontinued on: Nov 28, 2023



Overview

Presentation	Factory-assembled and tested, the tap off units house standard circuit breakers and a pre-terminated cord set. No tools required for installation on any iBusway for Data Center busway straight section.
Lead time	Usually Ships within 3 Weeks

Main

Provided equipment	208 V	
Main Output Voltage	120 V	

Physical

Colour	Black
Height	30.5 cm
Width	22.9 cm
Depth	14 cm
net weight	10.43 kg
Mounting preference	No preference
mounting mode	Not rack-mountable

Input

Network frequency 60 Hz

Output

Max current draw	30 A
Number of power socket outlets	1 NEMA L6-30R
Power cable length	0.9 m

Conformance

Product certifications	cUL listed	
	CSA	
	UL listed	

Environmental

ambient air temperature for	-1040 °C	
ambient all temperature for	-1040 C	
operation		
operation		

Relative humidity	095 %
Operating altitude	010000 ft
ambient air temperature for storage	-3070 °C
Storage Relative Humidity	095 %
Storage altitude	0.0000000004572.000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	35.9 cm
Package 1 Width	85.1 cm
Package 1 Length	35.9 cm
Package 1 Weight	16.36 kg

Contractual warranty

Warranty 1 year (parts only)

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Eu Rohs Directive

Under investigation

Image of product / Alternate images

Alternative

