



Grove - RTC

SKU 101020013

★★★★★

3 Reviews

Real-Time Clock (RTC) counts into seconds with Leap-Year compensation valid up to 2100 Powered with CR 1225 lithium cell battery 56-Byte, Battery-Backed, Nonvolatile (NV)RAM for data storage

- 1 +

US Warehouse



Add to Cart

Tags: clock coin battery enviroment
arduino Grove time Sensor linkit one
rtc IoT

Description Documents Learn Reviews FAQs

The RTC module is a member of Twig. It is based on the clock chip DS1307 which supports the I2C protocol. It uses a Lithium cell battery (CR1225). The clock/calendar provides seconds, minutes, hours, day, date,month, and year information. The end of the month date is automatically adjusted for months with fewer than 31 days, including corrections for leap year. The clock operates in either the 24-hour or 12-hour format with AM/PM indicator.
Note: Battery is not included.

Features

- Real-Time Clock (RTC) counts seconds, minutes, hours, date of the month, month, day of the week, and year with Leap-Year compensation valid up to 2100
- 56-Byte, Battery-Backed, Nonvolatile (NV)RAM for data storage
- I2C serial interface
- 5V DC supply
- Programmable Square-Wave output signal
- Automatic Power-Fail detect and switch circuitry
- Consumes less than 500nA in Battery-Backup Mode with Oscillator Running

Documents

- For all Grove users (especially beginners), we provide you guidance PDF documents. Please download and read through [Preface - Getting Started](#) and [Introduction to Grove](#) before your using of the product.

Technical details

Dimensions	130mm x80mm x10mm
Weight	G.W 10g
Battery	Exclude

Part List

Grove - RTC	1
Grove Cable	1

ECCN/HTS

ECCN	EAR99
HSCODE	9114909000
UPC	841454107736
ROHS	1

Company

Official Website
About Seeed
Solution
Distributors
Careers
Contacts

Help Center

How to Get Help
FAQ
Technical Support
Shipping & Order
Warranty & Returns
Payment Information

Community

Project Hub
Forum
Blog
Wiki

Stay Tuned

Enter Email Address



