

COAXIAL SURGE PROTECTOR DEVICE, Quarter-wave stub
technology
3400.17.0235

Properties

- Maintenance-free products
- Highest current handling capability up to 100 kA max.
- Best PIM performance
- Available in several frequency ranges from 380MHz up until 18GHz
- Inertion loss not exceeding 0.2 dB max.



Product configuration	
Main path connectors	Port 1: unprotected, N jack (female) Port 2: protected, N jack (female)
Mounting and grounding	MH25 (bulkhead mounting), M8 (screw)
EMP can be install reversed	YES
Interface and material data	
Housing material / plating	Brass / SUCOPLATE (R) Plating
Center contact, material / plating	Port 1: Copper Beryllium Alloy / Gold Plating (without Nickel underplating)
	Port 2: Copper Beryllium Alloy / Gold Plating (without Nickel underplating)
Electrical data	
Impedance	50 Ω
Frequency frame	5000 MHz to 7000 MHz
Return loss typical	≥ 20 dB
Insertion loss typical	≤ 0.25 dB
CW power frame	≤ 300 W
Residual pulse energy (typ.)	5 μJ (test pulse 4 kV 1.2/50 μs; 2 kA 8/20 μs)
Surge current handling capability	50 kA multiple (test pulse 8/20 μs)
	25 kA multiple (test pulse 10/350 μs)
Electrical remarks	
Gas tube	No DC / shorted QW or LC

COAXIAL SURGE PROTECTOR DEVICE, Quarter-wave stub technology
3400.17.0235

Mechanical data	
Weight	308 g
Mating cycles	500

Environmental data	
Operation temperature	-40 °C ... 85 °C
Storage temperature	-40 °C ... 85 °C
Ingress protection (IP Rating)	Mated / IP65, according to IEC 60529
Thermal shock according	MIL-STD-202, Method 107, Cond. B
Vibration according	MIL-STD-202, Method 204, Cond. A
Moisture resistance according	MIL-STD-202, Method 106

Compliance			
Item number	Directive / Regulation	Rating	Exemptions / Details
23002654	RoHS 2011/65/EU and (EU) 2015/863	Compliant with exemption	6c
	REACH 1907/2006 Article 33 SVHC	Contains one or more SVHC >0,1%	CAS: 7439-92-1 Lead

Comment	
Flange mounting (MH 25)	

Ordering Information Table	
Item number	Item description
23002654	3400.17.0235

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2073 / Date of publication: 28.02.2025 / uncontrolled copy