

## Test adapter - PAI-4 - 3030925

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Test adapter, for 4 mm test plug and terminal blocks with 4.2 mm ... 8.2 mm pitch, color: gray

### Your advantages

- ✓ The small outside diameter of the test socket means that touch-proof safety plugs can also be used
- ✓ Reliable contacting of test plugs with a 4 mm diameter in the function shaft
- ✓ Test adapter for accommodating safety test plugs with a 4 mm diameter



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	 4 017918 183196
GTIN	4017918183196
Weight per Piece (excluding packing)	2.340 g
Custom tariff number	85366990
Country of origin	Poland

### Technical data

#### General

Note	Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in
	Do not plug in while the power is connected
Color	gray

#### Dimensions

# Test adapter - PAI-4 - 3030925

## Technical data

### Dimensions

Height	53.8 mm
Length	5.8 mm
Width	5.8 mm
Diameter	5.8 mm
Pin diameter	4.6 mm

Material	Copper
Max. voltage	250 V
Maximum load current	10 A

### Ambient conditions

Operating temperature	-60 °C ... 105 °C (max. short-term operating temperature 130 °C)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Permissible humidity (storage/transport)	30 % ... 70 %
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Classifications

### eCl@ss

eCl@ss 10.0.1	27141148
eCl@ss 11.0	27141148
eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141148
eCl@ss 9.0	27141148

### ETIM

ETIM 2.0	EC000897
----------	----------

## Test adapter - PAI-4 - 3030925

### Classifications

#### ETIM

ETIM 3.0	EC000897
ETIM 4.0	EC002255
ETIM 6.0	EC002555
ETIM 7.0	EC002555

#### UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	20122006
UNSPSC 18.0	20122006
UNSPSC 19.0	20122006
UNSPSC 20.0	20122006
UNSPSC 21.0	20122006

### Approvals

#### Approvals

---


Approvals

EAC

---

Ex Approvals

#### Approval details

EAC		RU C- DE.BL08.B.00511
-----	---	--------------------------