

8-Pin DIP Low Input Current High Gain Split Darlington Optocouplers


Single-Channel: 6N138M, 6N139M
Dual-Channel: HCPL2730M, HCPL2731M



PDIP8 6.6x3.81, 2.54P
CASE 646BW



PDIP8 9.655x6.6, 2.54P
CASE 646CQ



PDIP8 GW
CASE 709AC

Description

The single−channel, 6N138M, 6N139M and dual−channel HCPL2730M, HCPL2731M optocouplers consist of an AlGaAs LED optically coupled to a high gain split darlington photodetector.

The split darlington configuration separating the input photodiode and the first stage gain from the output transistor permits lower output saturation voltage and higher speed operation than possible with conventional darlington phototransistor optocoupler. In the dual channel devices, HCPL2730M and HCPL2731M, an integrated emitter−base resistor provides superior stability over temperature.

The combination of a very low input current of 0.5 mA and a high current transfer ratio of 2000% makes this family particularly useful for input interface to MOS, CMOS, LSTTL and EIA RS232C, while output compatibility is ensured to CMOS as well as high fan−out TTL requirements. An internal noise shield provides exceptional common mode rejection of 10 kV/μs.


Features

- Low Current – 0.5 mA
- Superior CTR – 2000%
- Superior CMR – 10 kV/μs
- CTR Guaranteed 0 to 70°C
- Dual Channel – HCPL2730M, HCPL2731M
- Safety and Regulatory Approvals
- UL1577, 5,000 VAC_{RMS} for 1 Minute
- DIN EN/IEC60747−5−5
- These are Pb−Free Devices

Applications

- Digital Logic Ground Isolation
- Telephone Ring Detector
- EIA−RS−232C Line Receiver
- High Common Mode Noise Line Receiver
- μP Bus Isolation
- Current Loop Receiver

MARKING DIAGRAM



6N138	= Device Number
V	= DIN EN/IEC60747−5−5 Option (only appears on component ordered with this option)
XX	= Two−Digit Year Code, e.g., ‘16’
YY	= Two−Digit Work Week, Ranging from ‘01’ to ‘53’
B	= Assembly Package Code

ORDERING INFORMATION


See detailed ordering and shipping information on page 11 of this data sheet.

Related Resources

- https://www.onsemi.com/products/interfaces/high−performance−optocouplers/high−performance−transistor−optocouplers
- https://www.onsemi.com/products/interfaces/high−performance−optocouplers/high−performance−transistor−optocouplers/hcpl0700
- https://www.onsemi.com/products/interfaces/high−performance−optocouplers/high−performance−transistor−optocouplers/hcpl0731

© Semiconductor Components Industries, LLC, 2009

Downloaded from Arrow.com.



6N138M / 6N139M HCPL2730M / HCPL2731M

Figure 1. Schematics

SAFETY AND INSULATION RATINGS (As per DIN EN/IEC 60747−5−5, this optocoupler is suitable for “safe electrical insulation” only within the safety limit data. Compliance with the safety ratings shall be ensured by means of protective circuits.)

Parameter		Characteristics
Installation Classifications per DIN VDE 0110/1.89 Table 1, For Rated Mains Voltage	<150 V_{RMS}	I−IV
	<300 V_{RMS}	I−IV
	<450 V_{RMS}	I−III
	<600 V_{RMS}	I−III
	<1,000 V_{RMS} (Option T, TS)	I−III
Climatic Classification		40/100/21
Pollution Degree (DIN VDE 0110/1.89)		2
Comparative Tracking Index		175

Symbol	Parameter	Value	Unit
V_{PR}	Input−to−Output Test Voltage, Method A, V_{IORM} x 1.6 = V_{PR}, Type and Sample Test with t_m = 10 s, Partial Discharge < 5 pC	2,262	V_{peak}
	Input−to−Output Test Voltage, Method B, V_{IORM} x 1.875 = V_{PR}, 100% Production Test with t_m = 1 s, Partial Discharge < 5 pC	2,651	V_{peak}
V_{IORM}	Maximum Working Insulation Voltage	1,414	V_{peak}
V_{IOTM}	Highest Allowable Over−Voltage	6,000	V_{peak}
	External Creepage	≥8.0	mm
	External Clearance	≥7.4	mm
	External Clearance (for Option TV, 0.4” Lead Spacing)	≥10.16	mm
DTI	Distance Through Insulation (Insulation Thickness)	≥0.5	mm
T_S	Case Temperature (Note 1)	150	°C
$I_{S,INPUT}$	Input Current (Note 1)	200	mA
$P_{S,OUTPUT}$	Output Power (Duty Factor ≤ 2.7%) (Note 1)	300	mW
R_{IO}	Insulation Resistance at T_S, V_{IO} = 500 V (Note 1)	$>10^9$	Ω

1. Safety limit value − maximum values allowed in the event of a failure.

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)

Symbol	Parameter	Device	Value	Unit
T_{STG}	Storage Temperature		−40 to +125	°C
T_{OPR}	Operating Temperature		−40 to +100	°C
T_J	Junction Temperature		−40 to +125	°C
T_{SOL}	Lead Solder Temperature		260 for 10 s	°C
EMITTER				
I_F (avg)	DC/Average Forward Input Current Per Channel	All	20	mA
I_F (pk)	Peak Forward Input Current Per Channel (50% Duty Cycle, 1 ms P.W.)	All	40	mA
I_F (trans)	Peak Transient Input Current Per Channel (≤1 μs P.W., 300 pps)	All	1	A
V_R	Reverse Input Voltage Per Channel	All	5	V
P_D	Input Power Dissipation Per Channel (Note 2)	All	35	mW
DETECTOR				
I_O (avg)	Average Output Current Per Channel	All	60	mA
V_{ER}	Emitter−Base Reverse Voltage	6N138M, 6N139M	0.5	V
V_{CC}, V_O	Supply Voltage, Output Voltage	6N138M, HCPL2730M	−0.5 to 7.0	V
		6N139M, HCPL2731M	−0.5 to 18.0	
P_O	Output Power Dissipation Per Channel	All	100	mW

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

2. No derating required for devices operated within the T_{OPR} specification (6N138M and 6N139M only).

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Device	Test Conditions	Min	Typ	Max	Unit
INDIVIDUAL COMPONENT CHARACTERISTICS (V_{CC} = 5.0 V, T_A = 0°C to 70°C unless otherwise specified. Typical value is measured at T_A = 25°C.)							
EMITTER							
V_F	Input Forward Voltage	All	I_F = 1.6 mA, T_A = 25°C	–	1.30	1.70	V
			I_F = 1.6 mA	–	–	1.75	
BV_R	Input Reverse Breakdown Voltage	All	I_R = 10 μA, T_A = 25°C	5.0	19.0	–	V
$\Delta V_F / \Delta T_A$	Temperature Coefficient of Forward Voltage	All	I_F = 1.6 mA	–	−1.94	–	mV/°C
DETECTOR							
I_{CCL}	Logic Low Supply Current	6N138M, 6N139M	I_F = 1.6 mA, V_O = Open, V_{CC} = 18 V	–	0.4	1.5	mA
		HCPL2730M	V_{CC} = 7 V; $I_{F1} = I_{F2}$ = 1.6 mA, $V_{O1} = V_{O2}$ = Open	–	1.25	3	
		HCPL2731M	V_{CC} = 18 V; $I_{F1} = I_{F2}$ = 1.6 mA, $V_{O1} = V_{O2}$ = Open	–	1.25	3	
I_{CCH}	Logic High Supply Current	6N138M, 6N139M	I_F = 0 mA, V_O = Open, V_{CC} = 18 V	–	0.0003	10	μA
		HCPL2730M	V_{CC} = 7 V; $I_{F1} = I_{F2}$ = 0 mA, $V_{O1} = V_{O2}$ = Open	–	0.0003	20	
		HCPL2731M	V_{CC} = 18 V; $I_{F1} = I_{F2}$ = 0 mA, $V_{O1} = V_{O2}$ = Open	–	0.0003	20	
TRANSFER CHARACTERISTICS							
COUPLED							
CTR	Current Transfer Ratio (Note 3) (Note 4)	6N138M	I_F = 1.6 mA, V_O = 0.4 V, V_{CC} = 4.5 V	300	1600	–	%
		HCPL2730M			2400		
		6N139M	I_F = 0.5 mA, V_O = 0.4 V, V_{CC} = 4.5 V	400	2000	–	
		HCPL2731M			3500		
		6N139M	I_F = 1.6 mA, V_O = 0.4 V, V_{CC} = 4.5 V	500	1600	–	
		HCPL2731M			2400		
I_{OH}	Logic High Output Current	6N138M	I_F = 0 mA, V_O = V_{CC} = 7 V	–	0.001	250	μA
		HCPL2730M					
		6N139M	I_F = 0 mA, V_O = V_{CC} = 18 V	–	0.0036	100	
		HCPL2731M					
V_{OL}	Logic Low Output Voltage (Note 4)	6N138M	I_F = 1.6 mA, I_O = 4.8 mA, V_{CC} = 4.5 V	–	0.06	0.4	V
		HCPL2730M			0.05		
		6N139M	I_F = 0.5 mA, I_O = 2 mA, V_{CC} = 4.5 V	–	0.05	0.4	
		6N139M	I_F = 1.6 mA, I_O = 8 mA, V_{CC} = 4.5 V	–	0.093	0.4	
		HCPL2731M			0.08		
		6N139M	I_F = 5 mA, I_O = 15 mA, V_{CC} = 4.5 V	–	0.13	0.4	
		HCPL2731M			0.12		
		6N139M	I_F = 12 mA, I_O = 24 mA, V_{CC} = 4.5 V	–	0.18	0.4	
		HCPL2731M			0.17		

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

ELECTRICAL CHARACTERISTICS (continued)

Symbol	Parameter	Device	Test Conditions	Min	Typ	Max	Unit
SWITCHING CHARACTERISTICS (V_{CC} = 5.0 V, T_A = 0°C to 70°C unless otherwise specified. Typical value is measured at T_A = 25°C.)							
t_{PHL}	Propagation Delay Time to Logic LOW (Note 4) (Figure 14)	6N139M	R_L = 270 Ω, I_F = 12 mA	–	0.2	2	μs
		HCPL2730M, HCPL2731M	R_L = 270 Ω, I_F = 12 mA	–	0.5	3	
		6N138M	R_L = 2.2 kΩ, I_F = 1.6 mA	–	1.0	15	
		HCPL2730M, HCPL2731M	R_L = 2.2 kΩ, I_F = 1.6 mA	–	2.5	25	
		6N139M	R_L = 4.7 kΩ, I_F = 0.5 mA	–	2.5	30	
		HCPL2731M	R_L = 4.7 kΩ, I_F = 0.5 mA	–	8.4	120	
t_{PLH}	Propagation Delay Time to Logic HIGH (Note 4) (Figure 14)	6N139M	R_L = 270 Ω, I_F = 12 mA	–	1.3	10	μs
		HCPL2730M, HCPL2731M	R_L = 270 Ω, I_F = 12 mA	–	1.0	15	
		6N138M, HCPL2730M, HCPL2731M	R_L = 2.2 kΩ, I_F = 1.6 mA	–	7.3	50	
		6N139M, HCPL2731M	R_L = 4.7 kΩ, I_F = 0.5 mA	–	13.6	90	
$\|CM_H\|$	Common Mode Transient Immunity at Logic High (Note 5) (Figure 15)	All	I_F = 0 mA, $\|V_{CM}\|$ = 10 V_{P-P}, R_L = 2.2 kΩ, T_A = 25°C	1,000	10,000	–	V/μs
$\|CM_L\|$	Common Mode Transient Immunity at Logic Low (Note 5) (Figure 15)	All	I_F = 1.6 mA, $\|V_{CM}\|$ = 10 V_{P-P}, R_L = 2.2 kΩ, T_A = 25°C	1,000	10,000	–	V/μs
ISOLATION CHARACTERISTICS (T_A = 25°C unless otherwise specified.)							
V_{ISO}	Withstand Insulation Test Voltage (Note 6) (Note 7)	All	RH ≤ 50%, T_A = 25°C, I_{I-O} ≤ 10 μA, t = 1 min, f = 50 Hz	5,000	–	–	VAC_{RMS}
R_{I-O}	Resistance (Input to Output) (Note 6)	All	V_{I-O} = 500 V_{DC}	–	10^{11}	–	Ω
C_{I-O}	Capacitance (Input to Output) (Note 6) (Note 8)	All	f = 1 MHz, V_{I-O} = 0 V	–	1	–	pF
I_{I-I}	Input−Input Insulation Leakage Current (Note 9)	HCPL2730M, HCPL2731M	RH ≤ 45%, V_{I-I} = 500 V_{DC}, t = 5 s	–	0.005	–	μA
R_{I-I}	Input−Input Resistance (Note 9)	HCPL2730M, HCPL2731M	V_{I-I} = 500 V_{DC}	–	10^{11}	–	Ω
C_{I-I}	Input−Input Capacitance (Note 9)	HCPL2730M, HCPL2731M	f = 1 MHz	–	0.03	–	pF

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Current Transfer Ratio is defined as a ratio of output collector current, I_O, to the forward LED input current, I_F, times 100%.
4. Pin 7 open. (6N138M and 6N139M only)
5. Common mode transient immunity in logic HIGH level is the maximum tolerable (positive) dV_{cm}/dt on the leading edge of the common mode pulse signal V_{CM}, to assure that the output will remain in a logic HIGH state (i.e., V_O > 2.0 V). Common mode transient immunity in logic LOW level is the maximum tolerable (negative) dV_{cm}/dt on the trailing edge of the common mode pulse signal, V_{CM}, to assure that the output will remain in a logic LOW state (i.e., V_O < 0.8 V).
6. Device is considered a two terminal device: Pins 1, 2, 3 and 4 are shorted together and Pins 5, 6, 7 and 8 are shorted together.
7. 5000 VAC_{RMS} for 1 minute duration is equivalent to 6000 VAC_{RMS} for 1 second duration.
8. For dual channel devices, C_{I-O} is measured by shorting pins 1 and 2 or pins 3 and 4 together and pins 5 through 8 shorted together.
9. Measured between pins 1 and 2 shorted together, and pins 3 and 4 shorted together.

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

ELECTRICAL CHARACTERISTICS (continued)
(T_A = 25°C unless otherwise specified.)

Current Limiting Resistor Calculations:

$$R_1 \text{ (Non−Invert)} = \frac{V_{CC1} - V_{DF} - V_{OL1}}{I_F} \quad \text{(eq. 1)}$$

$$R_1 \text{ (Invert)} = \frac{V_{CC1} - V_{OH1} - V_{DF}}{I_F} \quad \text{(eq. 2)}$$

$$R_2 = \frac{V_{CC2} - V_{OLX} (@\ I_L - I_2)}{I_L} \quad \text{(eq. 3)}$$

Where:
V_{CC1} = Input Supply Voltage
V_{CC2} = Output Supply Voltage
V_{DF} = Diode Forward Voltage
V_{OL1} = Logic “0” Voltage of Driver
V_{OH1} = Logic “1” Voltage of Driver
I_F = Diode Forward Current
V_{OLX} = Saturation Voltage of Output Transistor
I_L = Load Current Through Resistor R_2
I_2 = Input Current of Output Gate

INPUT CONFIGURATION		R_1 (Ω)	R_2 (Ω) @ OUTPUT CONFIGURATION						
			CMOS @ 5 V	CMOS @ 10 V	74XX	74LXX	74SXX	74LSXX	74HXX
CMOS @ 5 V	NON−INV.	2000	1000	2200	750	1000	1000	1000	560
	INV.	510							
CMOS @ 10 V	NON−INV.	5100							
	INV.	4700							
74XX	NON−INV.	2200							
	INV.	180							
74LXX	NON−INV.	1800							
	INV.	100							
74SXX	NON−INV.	2000							
	INV.	360							
74LSXX	NON−INV.	2000							
	INV.	180							
74HXX	NON−INV.	2000							
	INV.	180							

Figure 2. Resistor Values for Logic Interface




Figure 3. Non−Inverting Logic Interface




Figure 4. Inverting Logic Interface

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

Typical Performance Curves




Figure 5. LED Forward Current vs. Forward Voltage




Figure 6. LED Forward Current vs. Temperature




Figure 7. Current Transfer Ratio vs. Forward Current (6N138M / 6N139M Only)




Figure 8. Normalized Current Transfer Ratio vs. Ambient Temperature (6N138M / 6N139M Only)




Figure 9. Current Transfer Ratio vs. Base−Emitter Resistance (6N138M / 6N139M Only)




Figure 10. Output Current vs. Input Diode Forward Current (6N138M / 6N139M Only)

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

Typical Performance Curves (continued)




Figure 11. Output Current vs Output Voltage (6N138M / 6N139M Only)




Figure 12. Logic Low Supply Current vs. Input Diode Forward Current (6N138M / 6N139M Only)





Figure 13. Propagation Delay vs. Temperature (6N138M / 6N139M Only)


Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

Test Circuits



Test Circuit for 6N138M, 6N139M



Test Circuit for HCPL2730M and HCPL2731M






Figure 14. Switching Time Test Circuit



Test Circuit for 6N138M and 6N139M



Test Circuit for HCPL2730M and HCPL2731M





Figure 15. Common Mode Immunity Test Circuit

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

Reflow Profile



Profile Freature	Pb−Free Assembly Profile
Temperature Min. (Tsmin)	150°C
Temperature Max. (Tsmax)	200°C
Time (t_S) from (Tsmin to Tsmax)	60 – 120 seconds
Ramp−up Rate (t_L to t_P)	3°C/second max.
Liquidous Temperature (T_L)	217°C
Time (t_L) Maintained Above (T_L)	60 – 150 seconds
Peak Body Package Temperature	260°C +0°C / –5°C
Time (t_P) within 5°C of 260°C	30 seconds
Ramp−down Rate (T_P to T_L)	6°C/second max.
Time 25°C to Peak Temperature	8 minutes max.

Figure 16. Reflow Profile

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

ORDERING INFORMATION

Part Number	Package	Shipping†
6N138M	DIP 8−Pin (Pb−Free)	50 Units / Tube
6N138SM	SMT 8−Pin (Lead Bend) (Pb−Free)	50 Units / Tube
6N138SDM	SMT 8−Pin (Lead Bend) (Pb−Free)	1,000 Units / Tape & Reel
6N139M	DIP 8−Pin (Pb−Free)	50 Units / Tube
6N139SM	SMT 8−Pin (Lead Bend) (Pb−Free)	50 Units / Tube
6N139SDM	SMT 8−Pin (Lead Bend) (Pb−Free)	1,000 Units / Tape & Reel
6N139VM	DIP 8−Pin, DIN EN/IEC 60747−5−5 Option (Pb−Free)	50 Units / Tube
6N139SVM	SMT 8−Pin (Lead Bend), DIN EN/IEC 60747−5−5 Option (Pb−Free)	50 Units / Tube
6N139SDVM	SMT 8−Pin (Lead Bend), DIN EN/IEC 60747−5−5 Option (Pb−Free)	1,000 Units / Tape & Reel
6N139TVM	DIP 8−Pin, 0.4” Lead Spacing, DIN EN/IEC 60747−5−5 Option (Pb−Free)	50 Units / Tube
HCPL2730M	DIP 8−Pin (Pb−Free)	50 Units / Tube
HCPL2730SM	SMT 8−Pin (Lead Bend) (Pb−Free)	50 Units / Tube
HCPL2730SDM	SMT 8−Pin (Lead Bend) (Pb−Free)	1,000 Units / Tape & Reel
HCPL2731M	DIP 8−Pin (Pb−Free)	50 Units / Tube
HCPL2731SM	SMT 8−Pin (Lead Bend) (Pb−Free)	50 Units / Tube
HCPL2731SDM	SMT 8−Pin (Lead Bend) (Pb−Free)	1,000 Units / Tape & Reel
HCPL2731VM	DIP 8−Pin, DIN EN/IEC 60747−5−5 Option (Pb−Free)	50 Units / Tube


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

PDIP8 6.6x3.81, 2.54P
CASE 646BW
ISSUE O

DATE 31 JUL 2016



NOTES:
A) NO STANDARD APPLIES TO THIS PACKAGE
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSION


DOCUMENT NUMBER:	**98AON13445G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**PDIP8 6.6X3.81, 2.54P**		**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

Downloaded from Arrow.com.

PDIP8 9.655x6.6, 2.54P
CASE 646CQ
ISSUE O

DATE 18 SEP 2017



NOTES:
A) NO STANDARD APPLIES TO THIS PACKAGE
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSION


DOCUMENT NUMBER:	**98AON13446G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**PDIP8 9.655X6.6, 2.54P**		**PAGE 1 OF 1**


onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

Downloaded from Arrow.com.


PDIP8 GW
CASE 709AC
ISSUE O


DATE 31 JUL 2016





LAND PATTERN RECOMMENDATION





NOTES:
A) NO STANDARD APPLIES TO THIS PACKAGE
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSION

DOCUMENT NUMBER:	**98AON13447G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**PDIP8 GW**		**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

Downloaded from Arrow.com.

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

◊

Downloaded from Arrow.com.