



NETWORK-ATTACHED
USB HUB



ANYWHEREUSB®

Network-attached USB hub connects USB peripheral devices anywhere on a LAN – without a locally-attached host PC

AnywhereUSB products are network-attached USB hubs that connect USB peripheral devices to a PC over a Local Area Network. The AnywhereUSB TS model also adds four RS-232 serial ports, enabling the mixing of USB and serial ports over the same network connection.

The AnywhereUSB software drivers are loaded onto a host PC or server so that USB devices attached to the AnywhereUSB hub may communicate with the host PC without changing existing device application software. AnywhereUSB drivers work equally well on physical servers or virtual machines in virtualized environments. Peripheral USB devices can be

centrally managed and monitored from a remote server or PC. The Multi-Host Connections feature allows multiple host PCs to establish connections with the AnywhereUSB hub concurrently, where each PC takes ownership of a group of USB ports on the AnywhereUSB hub.

Relocating the host PC to a remote location translates to smaller workstations, enabling deployment without a local PC in kiosks, ATMs, restaurant kitchens, manufacturing lines or any hostile or non-secure area where having a local PC is not practical.

USB storage devices and USB modems are not supported.
Digi's Edgeport/1 USB-to-serial converter may be used to connect a serial modem.

BENEFITS

- Network-attached USB hub easily connects remote USB devices to a LAN
- Ideal for connecting USB devices over the network in virtualized environments such as VMware®
- AnywhereUSB/14 rack mountable product has two built-in power supplies and two Ethernet connections for redundancy
- Access and monitor USB and serial devices over a TCP/IP connection
- Digi Remote Manager® provides centralized configuration, security management, and SUB port monitoring. Complimentary usage with Digi's cellular routers.

RELATED PRODUCTS



Digi TransPort®
LR54



Digi ConnecPort®
TS



Hubport®




Edgeport®
Family




TransPort®
WR21

APPLICATION EXAMPLE




SPECIFICATIONS	AnywhereUSB®/2 AnywhereUSB®/5 AnywhereUSB®/5M AnywhereUSB® TS AnywhereUSB®/14				
INTERFACES					
10/100BASE-T ETHERNET	1 RJ-45	1 RJ-45	1 RJ-45	1 RJ-45	2 RJ-45
USB	2	5	5	4	14
SERIAL	N/A	N/A	N/A	4 RS-232 RJ-45	1 RS-232 DB9
FEATURES					
IP ADDRESS	1 static (fixed) address per unit				
LEDS	System and Port status				
POWER SUPPLY	Ships with 120-240 VAC 50-60 Hz at 5 VDC @ 3 amps max w/ locking barrel	Ships with 120-240 VAC 50-60 Hz at 5 VDC @ 3 amps max w/ locking barrel	Ships with 120-240 VAC 50-60 Hz at 5 VDC @ 3 amps max w/ locking barrel	Ships with 120-240 VAC 50-60 Hz at 5 VDC @ 3 amps max w/ locking barrel	Includes 2 120-230 VAC 50-60 Hz @ 8 amps max
MANAGEMENT	CLI and AnywhereUSB web configuration tool, Digi Remote Manager® (cloud based) firmware uploads and monitoring of ports				
SECURITY	SSL/TLS 1.2				
OTHER SHARED FEATURES	Remote configuration utility; Multiple units supported per server; Field-upgradable software and firmware; Patented RealPort® (serial over IP) and RealPort USB (USB over IP); Port naming				
SERIAL DATA RATES	N/A	N/A	N/A	Up to 230 Kbps per port	Up to 230 Kbps per port
USB DOWNSTREAM POWER	500 mA per USB device				
USB COMPATIBILITY	USB 2.0, 1.1, 1.0 Note: USB storage devices and USB modems are not supported. Digi's Edgeport®/1 USB-to-serial converter may be used to connect a serial modem.				
OPERATING SYSTEMS	Windows® Server 2016, Windows® 10, Windows® 8, Windows® 7, Windows Vista®, Windows Server® 2012 R2, Windows® Server 2008 R2, Windows® Server 2003, Windows XP®, Windows XP® Embedded				
MULTI-HOST CONNECTIONS	N/A	N/A	Yes	N/A	Yes
DIMENSIONS (L X W X H)	2.38 in x 3.9 in x 1.0 in (6.04 cm x 10.0 cm x 2.54 cm)	4.35 in x 7.20 in x 1.03 in (11.05 cm x 18.29 cm x 2.61 cm)	4.35 in x 7.20 in x 1.03 in (11.05 cm x 18.29 cm x 2.61 cm)	4.35 in x 7.20 in x 1.03 in (11.05 cm x 18.29 cm x 2.61 cm)	4.97 in x 17.00 in x 1.74 in (12.62 cm x 43.18 cm x 4.42 cm), Rack mountable 1U
WEIGHT	5.0 oz (141.8 g)	10.0 oz (283.5 g)	10.0 oz (283.5 g)	10.0 oz (283.5 g)	40 oz (1134 g)
ENVIRONMENTAL					
OPERATING TEMPERATURE	32° F to 140° F (0° C to 60° C)	32° F to 140° F (0° C to 60° C)	32° F to 140° F (0° C to 60° C)	32° F to 140° F (0° C to 60° C)	32° F to 131° F (0° C to 55° C)
STORAGE TEMPERATURE	-40° F to +185° F (-40° C to +85° C)				
RELATIVE HUMIDITY	0% to 95% (non-condensing)				
NETWORK AND DEVICE RECOMMENDATIONS					
NETWORK TYPE	10/100 Mb switched Ethernet	10/100 Mb switched Ethernet	10/100 Mb switched Ethernet	10/100 Mb switched Ethernet	Dual 10/100 Mb switched Ethernet
USB DEVICE TYPES	Compatible with bulk or interrupt type USB devices; Isochronous devices not supported				
REGULATORY APPROVALS					
SAFETY	UL 1950/CSA 2.2 No. 950, EN60950, IEC-950				
EMISSIONS/IMMUNITY	CE, FCC Part 15 (Class B), EN55022, EN55024				


AnywhereUSB/5 AnywhereUSB/5M - Front




AnywhereUSB/2 - Front




AnywhereUSB TS - Front




AnywhereUSB/14 - Front




AnywhereUSB/5 AnywhereUSB/5M - Back




AnywhereUSB/2 - Back



AnywhereUSB TS - Back



AnywhereUSB/14 - Back



PART NUMBERS	DESCRIPTION
14-PORT MODEL	
AW-USB-14	AnywhereUSB/14 with Multi-Host Connections (Worldwide)
2-PORT MODEL	
AW-USB-2	AnywhereUSB/2 (Worldwide)
5-PORT MODEL	
AW-USB-5	AnywhereUSB/5 Gen 2 (Worldwide)
AW-USB-5M	AnywhereUSB/5 with Multi-Host Connections (Worldwide)
TS MODEL	
AW-TS-44	AnywhereUSB TS - 4 serial and 4 USB ports (Worldwide)

FOR MORE INFORMATION
PLEASE VISIT WWW.DIGI.COM

DIGI SERVICE AND SUPPORT / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit www.digi.com/support.

© 1996-2018 Digi International Inc. All rights reserved.
All trademarks are the property of their respective owners.

91001219
F5/718

DIGI INTERNATIONAL WORLDWIDE HQ
877-912-3444 / 952-912-3444 / www.digi.com

DIGI INTERNATIONAL GERMANY
+49-89-540-428-0

DIGI INTERNATIONAL JAPAN
+81-3-5428-0261 / www.digi-intl.co.jp

DIGI INTERNATIONAL SINGAPORE
+65-6213-5380

DIGI INTERNATIONAL CHINA
+86-21-50492199 / www.digi.com.cn

