

HD6/9.2G.3G



TE Connectivity has acquired the DIN Rail Terminal Block product range from ABB

Products → Low Voltage Products and Systems → Connection Devices → Terminal Blocks
→ Railway Terminal Blocks

General Information

| | |
|-------------------------------|--|
| Extended Product Type: | HD6/9.2G.3G |
| Product ID: | 1SNA160564R0100 |
| EAN: | 3472591605648 |
| Catalog Description: | HD6/9.2G.3G - Quick-connect terminal blocks - 5 tabs - Beige |
| Long Description: | - 2 circuits: 1 circuit with 3 vertical tabs for quick-connect 6.3 x 0.8 mm 0.248 x 0.031 in, marked in red and 1 circuit with 2 vertical tabs for quick-connect 6.3 x 0.8 mm 0.248 x 0.031 in, possibility of testing and transverse connection, - Use of jumper bars requires to cut out the precut partition, - NF F 61-017 designation: BK0009-3G/2Ge (1SNA160564R0100). |

Ordering

| | |
|--------------------------------|----------|
| Color: | Beige |
| Minimum Order Quantity: | 25 piece |
| Customs Tariff Number: | 85369010 |

Popular Downloads

| | |
|---|----------------------|
| Data Sheet, Technical Information: | 1SNC160001C0205_CHD3 |
| Instructions and Manuals: | 1SNC160001C0205_CHD3 |

Dimensions

| | |
|------------------------------------|---------|
| Product Net Width: | 9 mm |
| Product Net Height: | 61.5 mm |
| Product Net Depth / Length: | 29.5 mm |
| Product Net Weight: | 13 g |

Technical

| | |
|---------------------------------------|--|
| Rated Cross-Section: | 6 mm ² |
| Spacing: | 9 mm |
| Connection Type: | Quick-connect |
| Function: | Feed-through |
| Number of Levels: | 1 |
| Rated Current (I_n): | Main Circuit 25 A |
| Dielectric Test Voltage: | 2950 V |
| Degree of Protection: | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Insulation Material: | Polyamide |

| | |
|------------------------------|--|
| Mounting on DIN Rail: | Type 2 (21.8 x 8.2 mm Mounting Rail) acc. to NFC 93461 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 |
|------------------------------|--|

Technical UL/CSA

| | |
|--|-----------------|
| Connecting Capacity UL/CSA: | Stranded 10 AWG |
| Flammability According to UL94: | V0 |

Environmental

| | |
|---------------------------------|---|
| Ambient Air Temperature: | Operation -55 ... +110 °C Storage -55 ... +110 °C |
| RoHS Status: | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

Certificates and Declarations (Document Number)

| | |
|--|----------------------|
| Declaration of Conformity - CE: | 1SND225001U1000 |
| EAC Certificate: | 1SND161009A1100 |
| Environmental Information: | 1SND220040E1002 |
| Instructions and Manuals: | 1SNC160001C0205_CHD3 |
| RoHS Information: | 1SND230014F0202 |

Classifications

| | |
|------------------------------------|--|
| Object Classification Code: | X |
| ETIM 4: | EC000897 - Feed-through terminal block |
| ETIM 5: | EC000897 - Feed-through terminal block |
| ETIM 6: | EC000897 - Feed-through terminal block |

Container Information

| | |
|--|---------------|
| Package Level 1 Units: | 25 piece |
| Package Level 1 Width: | 70 mm |
| Package Level 1 Depth / Length: | 225 mm |
| Package Level 1 Height: | 42 mm |
| Package Level 1 Gross Weight: | 0.325 kg |
| Package Level 1 EAN: | 3472591605648 |
| Package Level 2 Units: | 500 piece |
| Package Level 2 Width: | 300 mm |
| Package Level 2 Depth / Length: | 500 mm |
| Package Level 2 Height: | 150 mm |
| Package Level 3 Units: | 24000 piece |
| Product Packing Type: | Box |

