



NOTES:

- 1. Material: Corrosion resistant steel (CRES) per ASTM A582/A582M, type 303 (UN S30330) or 303SE (UNS S30323) or XM-1 (UMS S20300), condition A
- 2. Finish: Passivate per AMS2700, Method 1, Class 4
- 3. All Drawing Dimensions are in Inches [mm]
- 4. Unless otherwise specified, Edge Breaks, Radii or Countersinks 0.005-0.015
- 5. All features in accordance with NAS1831

	TM
(DA	(=)
VAL	

95 Silvermine Rd., Seymour CT 06483 Tel: 203-888-2133, Fax: 203-888-9860

This Drawing is the Property of RAF. It contains confidential, proprietary information that is RAF property. Do not disclose to or duplicate for others except as authorized by RAF.

TOLERANCES ALL DIMENSIONS ARE INCHES (UNLESS OTHERWISE SPECIFIED) METALLIC LENGTHS </=: 6 INCHES ± 0.005

LENGTH >: 6 INCHES ± 0.010 DIAMETERS: ± 0.005 **NON-METALLIC**

LENGTH: ±0.010 DIAMETERS: ± 0.010 INTERNAL THREADS: MINIMUM THREAD DEPTH

COMPONENT

FEMALE FEMALE STANDOFF

NAS1831C4C08

1/4 Female Female Standoff

SCALE REV 4.00 04 SHEET

1 of 1

Downloaded from Arrow.com.