TE Internal #: 1116062-2

RJ45 Connector, Single Port, 1 x 1, Jack, Shielded, Cat 5, Standard - Latch Down, 8 Position, Low Profile, Through Hole - Solder, Right

Angle

View on TE.com >




#### Connectors > Modular Jacks & Plugs > RJ45 Connectors











Modular Jack & Plug Interface Type: RJ45

Port Configuration: Single Port
Port Matrix Configuration: 1 x 1

Modular Jacks & Plugs Products: RJ Type Jacks & Plugs

Connector Contact Density: Standard

### **Features**

# Product Type Features

Connector Product Type	Connector Assembly
Modular Jack & Plug Interface Type	RJ45
Modular Jacks & Plugs Products	RJ Type Jacks & Plugs
Modular Connector Style	Jack
Grounding Options	PCB and Panel Ground
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	

#### Configuration Features

Comiguration realtires	
Number of PCB Ground Tabs	2
Panel Ground Location	Top and Side
Port Configuration	Single Port
Port Matrix Configuration	1 x 1
Connector Contact Density	Standard
Number of Positions	8
Number of Loaded Positions	8
PCB Mount Orientation	Right Angle



## **Body Features**

Shield Plating Material	Tin
Shield Material	Copper Zinc Alloy
PCB Ground Tab Location	-3.05 mm[12 in]
Modular Jack Latch Orientation	Standard - Latch Down
Connector Profile	Low

#### **Contact Features**

Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Current Rating (Max)	.2 A, 1.5 A
Contact Mating Area Plating Material	Gold (Au)
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material Thickness	1.27 μm[50 μin]

#### **Termination Features**

Termination Method to PCB	Through Hole - Solder
Termination Post & Tail Length	3.48 mm[.137 in]

#### Mechanical Attachment

Panel Mount Feature	Without
Connector Mounting Type	Panel Mount

## **Housing Features**

Mating Entry Location	Side
Centerline (Pitch)	1.02 mm[.04 in]
Housing Color	Black
Housing Material	High Temperature Nylon

#### Dimensions

PCB Thickness (Recommended)	1.57 mm[.062 in]
Connector Height	9.58 mm[.377 in]

# **Usage Conditions**

Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]

## Operation/Application

Indicator Type	No Indicator	
----------------	--------------	--



Shielded	Yes
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Performance Category	Cat 5
Packaging Features	
Packaging Method	Box & Tray, Tray

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





# Customers Also Bought



TE Part #354175-E MSPEED 50 F SMDTHR F4 B AB VV 137 094 \*



TE Part #374722-E MSPEED 50 M SMDTHR \* 90BE AB VV 137 094



TE Part #1-178315-3 DYNAMIC S/ROW HDR 5P V ASSY PdNi PL



TE Part #1376164-1 BATTERY HOLDER ML621 ASSY



TE Part #1-1469491-3













### **Documents**

**Product Drawings** 

MJ,10MM,8P,BEZEL PNL TABS,SN

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1116062-2\_K.2d\_dxf.zip



English

**Customer View Model** 

ENG\_CVM\_CVM\_1116062-2\_K.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1116062-2\_K.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

82066 - Modular Jacks and MRJ21 Product catalog - Single Port Modular Jacks section

English

1-1773464-9\_MODULAR\_JACKS\_SINGLE\_PORT\_PCB\_MOUNT

English

**Product Specifications** 

**Application Specification** 

English

**Agency Approvals** 

**UL Report** 

English