





_			2	3	4	5		6		7	8
				HPCE PART NUMBER	(TABLE 3)						
А	PART NUMBER	TAIL TYPE	ORIENTATION KEY	DIM "A" TYPICAL TAIL LENGTH	DIM "B" RECOMMENDED BOARD THICKNESS	DIM "C" REF PEGS LENGTH		CIFICED ATION TOOL			A
	10118251-001LF			── 3.17 ±0.25	1.59 - 2.38	4.00	NO				DETAIL VIEW FOR AROUND ENHANCE WALL
	10118251-002LF										AITOOIND LIVITAINGL WALL
	10118251-003	PRESS-FIT YES									
	10118251-003LF	PRESS-FIT	YES	── 3.17 ±0.25	I.57 MIN	4.00	YES NOTE II				
В	10118251-004	PRESS-FIT	NO								В
	10118251-004LF	PRESS-FIT	NO								
	10118251-005LF		YES	- 3.17 ±0.25	1.59 - 2.38	2.26	NO	NO			
	10118251-006LF	SOLDER	NO					NO			
С	10118251-007LF		YES	2 17 10 25	1.57	2 20	YE:	YES			C
	10118251-008LF	PRESS-FIT	NO	3.17 ±0.25	MIN	2.26	N	OTE II		SI-	IORT PEGS VIEW
Copyright FCI.	HOUS CONT 2. CONTACT 3. PRODUCT 4. APPLICAT 5. PRODUCT 6. PACKAGIN 7. HOUSING FOR 60 S 8. COPPER P 9. ALL HOLE 10 MOUNTING	ACTS: HIG FINISH REF. GS SPECIFICATION: ION SPECIFICAT MARKING (FCI - G MEETS FCI SP COMPONENT WILL ECONDS IN A CC LATING THICKNE SIZES ARE FIN HOLES ARE UNP .40 +/- 0.1 FO .10 +/- 0.1 FO .10 +/- 0.03 F	UL 94V-0 COSH PERFORMANCE COPIES - 12-604 SECTION 5 GS-12-604 SECTION 5 GS-12-604. TION: GS-20-128. PART NUMBER & DATE OF VIOLES IN CENTER OF VIOLES OF VIOLES OF TAILS OR SOLDER TAILS WITH SOL	PER ALLOY. .2. TE CODE) ON HOUSING IN -937. RE TO 260°C PEAK TEMPE ED, OR VAPOR PHASE REF IA-HOLE CAN BE NO MORE	RATURE LOW OVEN. THAN 0.003 LESS THAN OT	LONG PEGS FOR P/Ns 10118251-001LF/002LF/0		OO4/OO4LF (SEE dr eng chr app	Wei-Long Zhang Wei-Long Zhang Pei-Ming Zheng Pei-Ming Zheng WE R HIGH	SHORT PEGS FOR P/Ns 10118251-005LF/006LF/007LF RT RECT (36P 24S) H POWER CARD EDGE	Size Scale A2 4:1 ecn no ELX-DG-012747-1 CARD EDGE rel level Released of the property of th
ownloaded from	Pro/E File · REV C - 2009-06-09		2	3	4	5		PDS: R	w.fci.com cat. no.		t - Customer Drw sheet 4 of 4 Printed: Sep 18, 2012