

Products

Industries & Solutions

Resources

TE Store

Sign In





Cable Assemblies > Copper Cable Assemblies > Sensor Cable Assemblies > M12 A-CODE MS-FR DOUBLE ENDED CABLE

T4162114005-004

Downloaded from Arrow.com.

RPC-M12-5MS-3.0SH-M12-5FR-PVC



TE Internal #: T4162114005-004

TE Internal Description: RPC-M12-5MS-3.0SH-

M12-5FR-PVC

All M12 A-CODE MS-FR DOUBLE ENDED

CABLE (112)

Connector Type: Plug/Receptacle


Number of Positions: 5

Keying: A

Housing Material: GF Nylon Cable Assembly Type: M12 to M12







Documents	Features	Product Compliance				
Product Description	M12 A-code Male Straight to Female R/A Assemblies are offered in 2 up to 5 positions PUR/PVC, Shielded & non-shielded, up to 10m length. View All M12 A-CODE MS-FR DOUBLE ENDED CABLE (112)					
Product Drawings	RPC-M12-5MS-3.0SH-M12-5FR-PVC RPC-M12-5MS-3.0SH-M12-5FR-PVC English					
CAD Files	3D PDF 3D_CVM_CVM_T Customer View Mod ENG_CVM_CVM_ 004_A.2d_dxf.zip E ENG_CVM_CVM_ 004_A.3d_igs.zip Er	_T4162114005- nglish _T4162114005-				
	ENG_CVM_CVM_T4162114005- 004_A.3d_stp.zip English					
Datasheets & Catalog Pages	M8/M12 Sensor Actuator Cable Assemblies Datasheet LENG_DS_1-1773966-2_0119.pdf English					
Product	Product Specification					

⁸-106140_A3.pdf English



M12 A-code Male Straight to Female R/A Assemblies

are offered in 2 up to 5 positions PUR/PVC, Shielded & non-shielded, up to 10m length.

View All M12 A-CODE MS-FR DOUBLE

ENDED CABLE (112)

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features Assembly Type: Pigtail

Connector Type: **Plug/Receptacle**Cable Assembly Type: **M12 to M12**

Shielded: **Yes**Cable Type: **PVC**

Product Type: Cable Assembly

LED: Without

Configuration

Number of Positions: 5

Features Keying: A

Configuration: Double Ended

Electrical Characteristics Operating Voltage (VDC): **60**Operating Voltage (VAC): **60**

Body Features Cable

Cable Jacket Color: **Black**Insulation Material: **PVC**

Wire Color: Brown, White, Blue, Black, Gray

Connector Color: Blue

Conductor Material: Copper Alloy Environmental Protection: With Cable Exit Angle: Right Angle

Contact Features

Contact Current Rating (A): 4

Mechanical Attachment Screw & Hole Thread Size: M12 x M12

Housing Features

Housing Material : **GF Nylon**

Dimensions

Wire Size (mm²): .34

Wire Size (AWG): 22

Cable Assembly Length (mm): 3000

Operation/Application M8/M12 Application Type: Sensor/Actuator

Other Field Serviceable : **Yes**

EU RoHS Directive 2011/65/EU Exemptions:

6(c) - Pb-Alloy in Copper

This declaration covers EU Directive 2011/65/EU incl. Delegated Directive 2015/863/EU. The restrictions under 2015/863/EU apply as of 22 July 2021 for EEE categories 8 (medical devices) and 9 (monitoring and control equipment).

EU ELV Directive 2000/53/EC

China RoHS 2 Directive MIIT Order No 32, 2016

部件名称 (Component Name) T4162114005-004	有害物质 (Hazardous Substance)						
	铅 (Pb)	汞 (Hg)	镉 (Cd)	六价 铬 (Cr6)	多溴联 苯 (PBB)	多 <mark>溴二苯</mark> 醚 (PBDE)	
连 接器系 统 (Connector Systems)	X	0	0	0	0	0	

本表格依据SJ/T 11364标准的规定编制。This table is compiled according to SJ/T 11364 standard.

〇:表示该有害物质在该部件所有均质材料中的含量均在GB/T 26572标准规定的限量要求以下。

Indicates that the concentration of the hazardous substance in all homogeneous materials of the part is below the relevant threshold of the GB/T 26572 standard.

X: 表示该有害物质至少在该部件的某一均质材料中的含量超出GB/T 26572标准规 定的限量要求。

Indicates that the concentration of the hazardous substance in at least one homogeneous material of the part is above the relevant threshold of the GB/T 26572 standard.

电子电气产品的环保使用期限依据SJ/T 11388标准的规定确定。 The EFUP value of EEP is defined according to SJ/T 11388 standard.

EU REACH Regulation (EC) No. 1907/2006 Current ECHA Candidate List: JAN 2019 (197)

Halogen Content

Solder Process Capability Not applicable for solder process capability

Statement of Compliance

Statement of Compliance pdf

Compliance Documents

There may be Environmental Compliance related documents on the DOCUMENTATION Tab

documents on the bocowientation is

Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they

provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Products with Similar Specs

THIS PRODUCT

M8/M12 SENSOR CABLE ASSEMBLIES T4162114005-004

RPC-M12-5MS-3.0SH-M12-5FR-PVC



In-Stock

Connector Type:

Plug/Receptacle

Number of Positions: 5

Keying: A

Housing Material: **GF Nylon**Cable Assembly Type: **M12 to**

M12

TOP RESULTS ②



T4162113005-004

RPC-M12-5MS-3.0SH-M12-5FS-PVC



Non-Stocked

${\tt Connector\,Type:}$

Plug/Receptacle

Number of Positions: 5

Keying: A

Housing Material: **GF Nylon**Cable Assembly Type: **M12 to**

M12

View All Similar Products

ABOUT TE CONNECTIVITY FOR PARTNERS SUPPORT CALL US LIVE CHAT UNITED STATES (EN)