


NLCV32T-2R2M-PFR



Applications	Commercial Grade
Feature	No Directivity
	Wire Wound
	Ferrite Core
Series Type	NLCV32-PFR
Status	EOL announced
	Recommended Alternate Part No. : NLCV32T-2R2M-EFR (Interchangeability is not guaranteed.)
	Discontinue Issue Date : Nov.19, 2024
	Last Purchase Order Date : Mar.31, 2026
Brand	Last Shipment Date : Sep.30, 2026
	TDK



Size	
Length(L)	3.20mm ±0.20mm
Width(W)	2.50mm ±0.20mm
Thickness Height	2.20mm ±0.20mm
Recommended Land Pattern (A)	1.20mm Nom.
Recommended Land Pattern (B)	2.00mm Nom.
Recommended Land Pattern (C)	2.00mm Nom.

Electrical Characteristics	
Inductance	2.2μH ±20% at 7.96MHz
Rated Current	1.2A
DC Resistance [Typ.]	115mΩ
DC Resistance [Max.]	138mΩ
Self Resonant Frequency [Min.]	68MHz
Self Resonant Frequency [Typ.]	
Q [Min.]	
Q [Typ.]	15 at 7.96MHz

Other	
Operating Temp. Range	-40 to 125°C (Including Self-Temp. Rise)
Soldering Method	Wave (Flow)
	Reflow
	Iron Soldering
AEC-Q200	NO
Packing	Embossed (Plastic)Taping [180mm Reel]

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

NLCV32T-2R2M-PFR









Package Quantity	2000pcs
Weight	0.05g

NLCV32T-2R2M-PFR




Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)



NLCV32T-2R2M-PFR



Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)



NLCV32T-2R2M-PFR



Associated Images

