

LTC2871IUHF

RS232/RS485 Multiprotocol Transceiver with Integrated Termination

DESCRIPTION

Demonstration circuit 1786A showcases the LTC2871 RS232/RS485 multiprotocol transceiver with integrated termination. Separate supply inputs power the interface and logic sections, permitting operation of the logic control and I/O down to 1.7V. LEDs indicate when supplies are present. All control pins are accessible via a turret for external connections, or they may be set by jumpers. All logic I/O and interface I/O lines are routed to turrets. The RS485 interface lines are also available at a terminal

block for convenient connection of a transmission line. Because the LTC2871 contains half-/full-duplex switching control it is unnecessary to jumper A and B to Y and Z for half-duplex operation.

Design files for this circuit board are available at <http://www.linear.com/demo>

LT, LTC, LTM, μ Module, Linear Technology and the Linear logo are registered trademarks of Linear Technology Corporation. All other trademarks are the property of their respective owners.

QUICK START PROCEDURE

The LTC2871 multiprotocol transceiver contains two RS232 drivers, two RS232 receivers, one RS485 driver and one RS485 receiver. All drivers and receivers may be accessed independently and simultaneously. The LTC2871 also includes on-chip supply generation for RS232, permitting operation from a single 3V to 5.5V V_{CC} supply. A separate logic I/O supply pin (V_L) permits the LTC2871 to adapt to any logic level ranging from 1.7V up to V_{CC} .

The LTC2871 also includes selectable RS485 terminations, as well as switching for half- and full-duplex modes, eliminating the need for external jumpers or relays for configuration in different modes.

DC1786A Includes:

- Bananas and turrets for supply connections along the upper edge of the board
- Turrets for logic I/O along the left edge of the board
- Turrets for RS232 and RS485 interface connections along the right edge of the board
- A terminal block, J5, for RS485 connections
- Turrets and jumpers for selecting modes along bottom edge of board. There are no pull-up or pull-down resistors on the control lines; known states must be asserted by jumpers or by applying a definitive logic level to the turrets.
- Green LEDs to indicate the presence of V_{CC} and V_L . Note that the V_L LED, D1, unavoidably dims and extinguishes at $V_L < 2V$.
- 10k pull-up resistors on DI, DIN1 and DIN2 to assert a known logic-1 state when these turrets are left open

QUICK START PROCEDURE

In summary, DC1786A features a turret for each and every LTC2871 logic, interface and supply pin. In addition the supply pins have banana jacks, and the control pins are connected to jumper blocks to establish their states.

Components

Components on DC1495A are divided into four basic groups:

R1-R9: 100 Ω resistors included in series with the control signal turrets to limit fault current arising from any accidental misconnections of the turrets or jumpers.

D1, D2, R11, R15: V_{CC} and V_L supply indicator LEDs and current limiting resistors.

R12, R13, R14: 10k pull-ups to V_L on DI and DIN1, DIN2.

C1-C5, L1: supply generation and bypassing components for the LTC2871 (U1).

LTC2871 Operation

The LTC2871 contains two RS232 drivers, two RS232 receivers, one RS485 driver and one RS485 receiver. The input(s) and output(s) of each of these elements is separately available and can be interconnected with other elements without conflict between abs max ratings or loading in the disabled state.

The RS485 transceiver includes a special half-/full-duplex switching feature. In full-duplex mode, the receiver inputs are connected to the A and B pins, while the driver is connected to Y and Z. In half-duplex mode, the receiver inputs are moved to Y and Z so that there is no need to jumper A-B to Y-Z when switching between half- and full-duplex modes.

Lastly, RS485 terminations are included in the LTC2871. The terminations can be engaged or disengaged as controlled by a termination enable control line, TE485.

Jumpers

Jumper blocks are included to set the state of each control pin to V_L or GND. If the shorting jumper is set in the EXT position, the control pin is connected to its associated turret and external signalling may be applied. Failure to select one of the three positions results in a floating control pin. The turret is disconnected and there are no internal or on-board pull-ups to establish the logic state if the jumper block is open.

As shipped, jumpers on DC1786A are set to enable all transmitters and receivers, with RS485 set to full duplex with terminations enabled.

See the data sheet Pin Functions and Function tables for a complete description of the control pin functions. A brief summary is given here:

JP1, LB: Loopback Enable. A logic high loops driver input signals immediately back to associated receiver outputs. Loopback is interrupted when a receiver is disabled. Default position low, loopback disabled.

JP2, H/ $\bar{F}$: RS485 Half-Duplex Select Input. A logic low selects full-duplex operation where the RS485 receiver responds to signals on the A and B pins. A logic high selects half-duplex operation where the RS485 receiver responds to signals on the Y and Z pins. Default position low, full duplex enabled.

JP3, TE485: RS485 Termination Enable. A logic high enables 120 Ω terminations across A-B and Y-Z. Default position high, RS485 terminations enabled.

JP4, CH2: RS232 Channel 2 Disable. A logic high disables RS232 driver 2 and receiver 2, independent of RX232 and DX232. Default position low, RS232 CH2 enabled.

JP5, RX485: RS485 Receiver Enable. A logic low enables the RS485 receiver. Default position low, RS485 receiver enabled.

JP6, DX485: RS485 Driver Enable. A logic high enables the RS485 driver. Default position high, RS485 driver enabled.

JP7, DX232: RS232 Driver Enable. A logic high enables the RS232 driver. Default position high, RS232 driver enabled.

JP8, RX232: RS232 Receiver Enable. A logic low enables the RS232 receiver. Default position low, RS232 receiver enabled.

JP9, FEN: Fast Enable. A logic high enables fast enable mode; the internal supply generator remains operational regardless of the state of the driver, receiver and termination enables. Default position low, fast enable disabled.

Probe Pads

Probe pads are included on the bottom of the board for examination of the V_{CC} , V_{DD} , V_{EE} , SW and CAP pins. A GND probe pad is included nearby. V_{DD} and V_{EE} are also accessible from the top.

J5

Terminal block J5 is included for easy connection of an RS485 cable. For half-duplex operation only Y and Z need be connected. Terminal block J5 is hardwired to turrets A, B, Y and Z.

How to Operate DC-1786A

Operation of DC1486A is straightforward: connect a V_{CC} supply of 3V to 5.5V, and a V_L supply of 1.7V up to V_{CC} . There are no special supply sequencing restrictions, although if $V_L > V_{CC}$ the logic I/O signalling may not operate properly. Note that D1, the V_L supply indicating LED will extinguish at $V_L < 2V$.

Once power is connected, all drivers and receivers will be active.


The LTC2871 may be made to self-oscillate by connecting all of the drivers and receivers in one all-encompassing loop, and adding one inversion. The inversion may be introduced with a logic inverter, or by cross-connecting the RS485 driver and receiver (connect Y to B and Z to A). With $V_{CC} = V_L = 3.3V$, the frequency of oscillation is typically 275kHz. Use the default jumper positions for this test.

DEMO MANUAL DC1786A

PARTS LIST

ITEM	QTY	REFERENCE	PART DESCRIPTION	MANUFACTURER/PART NUMBER
1	1	C1	CAP, 0805 220nF 10% 25V X7R	AVX 08053C224KATxA
2	2	C2,C3	CAP, 0805 1µF 10% 25V X7R	TDK C2012X7R1E105K
3	1	C4	CAP, 0805 2.2µF 10% 25V X7R	AVX 08053C225KAT2A
4	1	C5	CAP, 0805 100nF 10% 25V X7R	AVX 08053C104KAT2A
5	2	D1,D2	LED, GREEN	PANASONIC LN1351C
6	34	E1-E9, E14-E38	TURRET	MILL-MAX 2308-2-00-80-00-00-07-0
7	4	E10, E11, E12, E13	TURRET	MILL-MAX 2501-2-00-80-00-00-07-0
8	9	JP1-JP9	HEADER, 3PIN, DBL ROW 2mm	SAMTEC TMM 103-02-L-D
9	4	J1, J2, J3, J4	JACK, BANANA	KEYSTONE 575-4
10	1	J5	TERMINAL BLOCK, 5 POSITION, 3.5mm	ON-SHORE TECH OSTTV051150
11	1	L1	IND, 2016 (mm) 10µH 200mA	TAIYO YUDEN CB2016T100M
12	9	R1-R9	RES, 1206 100Ω 5% 1/4W	VISHAY CRCW1206100RJNEA
13	2	R11, R15	RES, 0603 330Ω 5% 1/10W	NIC NRC0603J331TRF
14	3	R12, R13, R14	RES, 0603 10kΩ 5% 1/10W	VISHAY CRCW060310K0JNEA
15	1	U1	IC, RS232/RS485 TRANSCEIVER	LINEAR TECH. LTC2871IUHF
16	9	JP1-JP9	SHUNT, 2mm	SAMTEC 2SN-BK-G
17	4		STANDOFF, SNAP ON	KEYSTONE_8832

SCHEMATIC DIAGRAM



DEMO MANUAL DC1786A

DEMONSTRATION BOARD IMPORTANT NOTICE

Linear Technology Corporation (LTC) provides the enclosed product(s) under the following **AS IS** conditions:

This demonstration board (DEMO BOARD) kit being sold or provided by Linear Technology is intended for use for **ENGINEERING DEVELOPMENT OR EVALUATION PURPOSES ONLY** and is not provided by LTC for commercial use. As such, the DEMO BOARD herein may not be complete in terms of required design-, marketing-, and/or manufacturing-related protective considerations, including but not limited to product safety measures typically found in finished commercial goods. As a prototype, this product does not fall within the scope of the European Union directive on electromagnetic compatibility and therefore may or may not meet the technical requirements of the directive, or other regulations.

If this evaluation kit does not meet the specifications recited in the DEMO BOARD manual the kit may be returned within 30 days from the date of delivery for a full refund. THE FOREGOING WARRANTY IS THE EXCLUSIVE WARRANTY MADE BY THE SELLER TO BUYER AND IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED, IMPLIED, OR STATUTORY, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. EXCEPT TO THE EXTENT OF THIS INDEMNITY, NEITHER PARTY SHALL BE LIABLE TO THE OTHER FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.

The user assumes all responsibility and liability for proper and safe handling of the goods. Further, the user releases LTC from all claims arising from the handling or use of the goods. Due to the open construction of the product, it is the user's responsibility to take any and all appropriate precautions with regard to electrostatic discharge. Also be aware that the products herein may not be regulatory compliant or agency certified (FCC, UL, CE, etc.).

No License is granted under any patent right or other intellectual property whatsoever. **LTC assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or any other intellectual property rights of any kind.**

LTC currently services a variety of customers for products around the world, and therefore this transaction **is not exclusive**.

Please read the DEMO BOARD manual prior to handling the product. Persons handling this product must have electronics training and observe good laboratory practice standards. **Common sense is encouraged.**

This notice contains important safety information about temperatures and voltages. For further safety concerns, please contact a LTC application engineer.

Mailing Address:

Linear Technology
1630 McCarthy Blvd.
Milpitas, CA 95035

Copyright © 2004, Linear Technology Corporation

dc1786af