

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of NFM41PC155B1E3# from the official website of Murata Manufacturing Co., Ltd.

"#"at the end indicates the package specification code.

http://www.murata.com/en-gb/products/productdetail?partno=NFM41PC155B1E3%23

NFM41PC155B1E3#

In Production RoHS REACH 85 EMI Low ESL Reflow Flow OK

< List of part numbers with package codes > NFM41PC155B1E3L

Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment,Industrial Equipment,Mobile Electronics,Medical
	equipment [GHTF A/B/C] except for
	implant equipment,Automotive
	infotainment/comfort equipment
Specific Applications	Please refer to Our Website and
	specifications, etc. for information about
	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.




Packaging	Specifications	Standard Packing Quantity
L	180Embossed Tape	4000

ss (typ.)		
1 piece	38.7mg	

Appearance & Shape





1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





NFM41PC155B1E3#

Note: This datasheet may be out of date. Please download the latest datasheet of NFM41PC155B1E3# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-gb/products/productdetail?partno=NFM41PC155B1E3%23

"#"at the end indicates the package specification code.



Specifications

Length	4.5±0.3mm
Width	1.6±0.3mm
Thickness	1.0±0.2mm
Capacitance	1.5µF ±20%
Distance between external terminals g	0.7mm min.
DC Resistance(max.)	9mΩ
External terminal size e	0.4±0.3mm
External terminal size i	1.5±0.3mm
External terminal size J	0.3+0.3/-0.2mm
Operating Temperature Range	-55°C to 85°C
Rated Current	6A
Rated Voltage	25Vdc
Size code in inch(mm)	1806 (4516M)

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

- without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of NFM41PC155B1E3# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-gb/products/productdetail?partno=NFM41PC155B1E3%23

NFM41PC155B1E3#

"#"at the end indicates the package specification code.

Characteristic Data

The charts below may show another part number which shares its characteristics.



3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering

