



Data Sheet | Item Number: 789-571

Latching relay module; Nominal input voltage: 24 VDC; 1 make contact; Limiting continuous current: 16 A; Red status indicator; Module width: 18 mm; 2,50 mm²; gray

<https://www.wago.com/789-571>



Color: ■ gray



Technical data			
Control circuit		Load circuit	
Nominal input voltage U_N	24 VDC	Number of make/switch-on contacts	1
Input voltage range	-15 ... +10 %	Contact material (relay)	AgSnO ₂
Nominal input current at U_N	82 mA	Limiting continuous current	16 A
Coil Control	Pulse mode	Inrush current (resistive) max.	(AC) 50 A / 0.02 s
Minimum pulse length (control input)	40 ms	Switching Voltage, Max.	250 VAC
Minimum break time	180 ms	Switching power (resistive) max.	AC 4000 VA
		Recommended minimum load	10 V / 10 mA
		Electrical life (NO; resistive load; 23 °C)	50 x 10 ³ switching operations
		Mechanical life	1 x 10 ⁶ switching operations
		Switching frequency with/without load (max.)	6 min ⁻¹ / 240 min ⁻¹
		Circuit protection	Circuit breaker: 16 A (max.); Tripping characteristic: B



Signaling	
Status indicator	Red LED

Safety and protection	
Rated Voltage	250 V
Rated impulse withstand voltage	4 kV
Pollution degree	2
Dielectric strength (control/load circuit) (AC, 1 min)	4 kVrms
Protection type	IP20

Connection Data	
Connection technology	CAGE CLAMP®
Solid conductor	0.2 ... 2.5 mm² / 24 ... 14 AWG
Fine-stranded conductor	0.2 ... 2.5 mm² / 24 ... 14 AWG
Strip length	9 ... 10 mm / 0.35 ... 0.39 inches

Physical data	
Width	17.5 mm / 0.689 inches
Height	90 mm / 3.543 inches
Depth from upper-edge of DIN-rail	55 mm / 2.165 inches

Mechanical data	
Housing design	DIN-rail-mount enclosure
Mounting type	DIN-35 rail

Material data	
Note (material data)	Information on material specifications can be found here
Color	gray
Fire load	0.666 MJ
Weight	58.8 g

Environmental requirements	
Ambient temperature (operation at U _N)	-25 ... +40 °C
Ambient temperature (storage)	-40 ... +85 °C
Processing temperature	-25 ... +50 °C

Standards and Specifications	
Standards/specifications	EN 60664-1



Commercial data	
Product Group	6 (INTERFACE ELECTRONIC)
PU (SPU)	10 (1) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454572655
Customs tariff number	85364900990

Product Classification	
UNSPSC	39121529
eCl@ss 10.0	27-14-23-09
eCl@ss 9.0	27-14-23-09
ETIM 9.0	EC001437
ETIM 10.0	EC001437
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
CAS-No.	7439-92-1 79-94-7
REACH Candidate List Substance	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	7(a) 7(c)-I
SCIP notification number (Austria)	47a23f63-5d1b-4163-aaaa-17a6ad486e0e
SCIP notification number (Belgium)	15d3a70e-e176-43f3-891b-f071bf91bf2a
SCIP notification number (Bulgaria)	f5f7e129-7373-42ff-a5ad-b6f347fa44d2
SCIP notification number (Czech Republic)	ddfbdc03-d9de-4eb3-8b39-865f36d28bb0
SCIP notification number (Denmark)	db3228ba-af73-4c58-8239-701c1458bf3c
SCIP notification number (Finland)	80e43c22-17db-4045-a4e8-dc706d14da5a
SCIP notification number (France)	fb979714-aa41-41e0-807a-3ed624091a66
SCIP notification number (Germany)	4a18058b-0969-4a85-9c49-247dfa269635
SCIP notification number (Hungary)	5d426e4b-1714-4530-acf5-625acc3d78d0
SCIP notification number (Italy)	ff18a9dc-2c0f-43fe-aec5-e2b12c4e512d
SCIP notification number (Netherlands)	a0be3dd7-9ec6-43f0-a4ce-1d4e2af0a8e2
SCIP notification number (Poland)	b31516bb-3f11-468c-8510-2c0e271245fb
SCIP notification number (Romania)	c9ab27e8-3f63-46cb-8df2-f5f70e4c2a01
SCIP notification number (Sweden)	39675669-d41a-422e-b84b-8f3a9d120ba6

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 789-571

↓



Documentation				
Bid Text				Instruction Leaflet
789-571	19.02.2019	xml 4.84 KB		Operation and Assembly Instructions Interface V 1.0.0 02.04.2025 pdf 1246.19 KB
789-571	20.02.2019	docx 16.53 KB		

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 789-571	EPLAN Data Portal 789-571
	WSCAD Universe 789-571
	ZUKEN Portal 789-571

1 Compatible Products

1.1 Optional Accessories

1.1.1 Ferrule

1.1.1.1 Ferrule

Item No.: 216-241 Ferrule; Sleeve for 0.5 mm² / 20 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; white	Item No.: 216-242 Ferrule; Sleeve for 0.75 mm² / 18 AWG; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; gray	Item No.: 216-243 Ferrule; Sleeve for 1 mm² / AWG 18; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; red	Item No.: 216-244 Ferrule; Sleeve for 1.5 mm² / AWG 16; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; black

1.1.2 Jumper

1.1.2.1 Jumper

Item No.: 789-112 Jumper; 12-way; silver-colored

1.1.3 Marking

1.1.3.1 Marker

Item No.: 2009-145 Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white	Item No.: 248-502 Mini-WSB marking card; as card; MARKED; 1 ... 10 (10x); not stretchable; Horizontal marking; snap-on type; white	Item No.: 248-566 Mini-WSB marking card; as card; MARKED; 1 ... 50 (2x); not stretchable; Horizontal marking; snap-on type; white	Item No.: 248-503 Mini-WSB marking card; as card; MARKED; 11 ... 20 (10x); not stretchable; Horizontal marking; snap-on type; white
Item No.: 248-504 Mini-WSB marking card; as card; MARKED; 21 ... 30 (10x); not stretchable; Horizontal marking; snap-on type; white	Item No.: 248-506 Mini-WSB marking card; as card; MARKED; 41 ... 50 (10x); not stretchable; Horizontal marking; snap-on type; white	Item No.: 248-452 Mini-WSB marking card; as card; MARKED; K (100x); not stretchable; Horizontal marking; snap-on type; white	Item No.: 248-450 Mini-WSB marking card; as card; MARKED; K1 - K10 (10x); not stretchable; Horizontal marking; snap-on type; white



1.1.3.1 Marker



Item No.: 248-451
Mini-WSB marking card; as card; MARKED; K11 - K20 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-455
Mini-WSB marking card; as card; MARKED; U 100 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-453
Mini-WSB marking card; as card; MARKED; U1, ... U10 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-454
Mini-WSB marking card; as card; MARKED; U11 - U20 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 248-501
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white

1.1.3.2 Marking device



Item No.: 210-110
Fiber-tip pen

1.1.4 Tool


1.1.4.1 Operating tool



Item No.: 210-720
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured


Installation Notes

Conductor termination




Inserting a conductor.

Commoning



Easy commoning via adjacent jumpers.

Marking



Marking via Mini-WSB Quick Marking System.