


Part Number : <u>398800512</u> Product Description : 5.08mm Pitch Beau Eurostyle Low Profile, Two Level Terminal Block, Modular, 12 Circuits Series Number : 39880 Status : Active Product Category : Terminal Blocks and Barrier Strip Engineering Number : MX-PSB060D5-0N



### **Documents & Resources**

Drawings 398800512\_sd.pdf

**3D Models and Design Files** 398800512\_stp.zip

## **Product Environment Compliance**

#### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | <b>@</b>  |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                    |
| REACH SVHC         | Contains Lead per D(2024)6225-DC<br>(07 Nov 2024) |
| EU RoHS            | Compliant with Exemption 6(c) per<br>EU 2015/863  |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

# **Part Details**

### General

| Status         | Active  |
|----------------|---|
| Category       | Terminal Blocks and Barrier Strip   |
| Series         | 39880   |
| Description    | 5.08mm Pitch Beau Eurostyle Low<br>Profile, Two Level Terminal Block,<br>Modular, 12 Circuits |
| Application    | Wire-to-Board   |
| Component Type | One Piece   |
| Product Name   | Eurostyle Multi-Level   |
| Туре           | PCB Terminal Blocks and<br>Connectors   |
| UPC            | 800756363172  |

# Agency

|--|

## Electrical

| Current - Maximum per Contact | 13.5A |
|-------------------------------|-------|
| Voltage - Maximum             | 300V  |

# Physical

| Circuits (Loaded)   | 12         |
|---------------------|------------|
| Circuits (maximum)  | 12         |
| Color - Resin       | Black      |
| Entry Angle         | Horizontal |
| Flammability        | 94V-0      |
| Lock to Mating Part | None       |
| Net Weight          | 12.700/g   |
| Number of Rows      | 2          |

| Orientation                   | Vertical                       |
|-------------------------------|--------------------------------|
| Panel Mount                   | No                             |
| PC Tail Length                | 3.50mm                         |
| PCB Retention                 | None                           |
| PCB Thickness - Recommended   | 2.40mm                         |
| Pitch - Mating Interface      | 5.08mm                         |
| Pitch - Termination Interface | 5.08mm                         |
| Polarized to Mating Part      | N/A                            |
| Shrouded                      | Fully                          |
| Stackable                     | Yes                            |
| Temperature Range - Operating | 110°C                          |
| Wire Size (AWG)               | 16, 18, 20, 22, 24, 26, 28, 30 |
| Wire Size mm <sup>2</sup>     | 0.20-1.50                      |

#### Solder Process Data

| Lead-Free Process Capability | WAVE |
|------------------------------|------|

This document was generated on Mar 09, 2025