

Product data sheet

Specifications

Rack ATS, 16A, 230V, (2)IEC 309 in, (1)IEC 309 out



AP7722A

⚠ Discontinued on: Jun 30, 2021

⚠ End-of-service on: Jun 28, 2023

⚠ Discontinued

Overview

Lead time Usually in Stock

Main

Main Input Voltage	200 V 208 V 230 V
Main Output Voltage	230 V
Input Connection Type	IEC 60309 16 A 2P + E
Number of rack unit	1U
Cable length	0.9 m
Number of cables	2
Provided equipment	Rack mounting brackets User manual

Physical

Colour	Black
Height	4.4 cm
Width	43.2 cm
Depth	23.6 cm
Net weight	4.21 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Network frequency	50/60 Hz
Permissible voltage	200...240 V
Max line current	16 A
Input current limits	16 A
Load capacity	3840 VA

Output

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Max current draw	16 A
Number of power socket outlets	1 IEC 60309 16 A 2P + E
Power cable length	0.9 m

Conformance

Product certifications	C-Tick CE GOST TÜV VCCI class A
Standards	EN 55022 class A EN 55024

Environmental

ambient air temperature for operation	-5...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.4 cm
Package 1 Width	34.9 cm
Package 1 Length	60 cm
Package 1 Weight	5.95 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint	
Environmental Disclosure	Product Environmental Profile
Use Better	
Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
Use Again	
Repack and remanufacture	
Circularity Profile	End of Life Information
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins