




SML-E1 Series

1608(0603)
 1.6×0.8mm(t=0.36mm)

Features

- EXCELED™ series
- Compact, Thin size (1.6×0.8mm, t=0.36mm)
- LED die consists of 4 elements
- Original device technology enables high brightness and high reliability


Color Type	V	U	D	Y	
	M	P	E	B	WB

Specifications


Part No.	Chip Structure	Emitting Color	Absolute Maximum Ratings (Ta=25°C)						Electrical and Optical Characteristics (Ta=25°C)									
			Power Dissipation Pd(mW)	Forward Current IF(mA)	Peak Forward Current IFP(mA)	Reverse Voltage VR(V)	Operating Temperature Topr(°C)	Storage Temperature Tstg(°C)	Forward Voltage VF Typ. (V)	IF(mA)	Max. (μA)	VR(V)	Dominant Wavelength λD Min.*3 (nm)	Typ. (nm)	Max.*3 (nm)	Luminous Intensity Iv Min. (mcd)	Typ. (mcd)	Iv(mA)
■ SML-E12V8W	AlGaInP on GaAs	Red	54	20	100*2	5	-40 to +85	-40 to +100	2.2				625	630	635	16	40	
■ SML-E12UW			62	25	60*1	4	-30 to +85	-40 to +85	2.1				619	624	629	36	100	
■ SML-E12U8W			54	20	100*2	5	-40 to +85	-40 to +100	2.2				615	620	625	25	63	
■ SML-E12DW		Orange	62	25	60*1	4	-30 to +85	-40 to +85	1.9	20		4	603.5	606.5	609.5	56	200	20
■ SML-E12D8W		Yellow											602	605	608	40	100	
■ SML-E12Y8W			54				-40 to +85		2.2				587	590	593	25	63	
■ SML-E12M8W		Yellowish Green											569	572	575	10	25	
■ SML-E12P8W	InGaN	Green		20	100*2	5		-40 to +100					557	560	563	2.5	6.3	
■ SMLE12EC6T		Bluish Green	68						3.0				520	527	535	36	85	
■ SMLE12BC7T		Blue	66				-30 to +85		2.9	5		5	464	470	476	9	22	5
□ SMLE12WBC7W		White									100		(x, y) (0.30, 0.30)			22	71	

* 1:Duty1/5, 200Hz / * 2:Duty1/10, 1kHz * 3:Reference


Dimensions



Recommended Solder Pattern




Viewing Angle




* EXCELED™ is ROHM's pending trademark.

Electrical Characteristics Curves


Forward Current-Forward Voltage




Luminous Intensity-Atmosphere Temperature



Luminous Intensity-Forward Current



Derating



SML-E1 Series

Rank Reference of Brightness

Red (V, U)

				(Ta=25°C, If=20mA)															
	Package size(mm)	Height(mm)	Luminous Intensity (mcd)	G	H	J	K	L	M	N	P	Q	R	S	T	U	V	W	X
				1.0 to 1.6	1.6 to 2.5	2.5 to 4.0	4.0 to 6.3	6.3 to 10	10 to 16	16 to 25	25 to 40	40 to 63	63 to 100	100 to 160	160 to 250	250 to 400	400 to 630	630 to 1000	1000 to 1600
Mini-mold Chip LEDs	1608	0.36									SML-E12V8W								
											SML-E12U8W								
											SML-E12UW*								

Orange (D)

				(Ta=25°C, If=20mA)															
	Package size(mm)	Height(mm)	Luminous Intensity (mcd)	G	H	J	K	L	M	N	P	Q	R	S	T	U	V	W	X
				1.0 to 1.6	1.6 to 2.5	2.5 to 4.0	4.0 to 6.3	6.3 to 10	10 to 16	16 to 25	25 to 40	40 to 63	63 to 100	100 to 160	160 to 250	250 to 400	400 to 630	630 to 1000	1000 to 1600
Mini-mold Chip LEDs	1608	0.36												SML-E12DW*					
														SML-E12D8W					

Yellow (Y)

				(Ta=25°C, If=20mA)															
	Package size(mm)	Height(mm)	Luminous Intensity (mcd)	G	H	J	K	L	M	N	P	Q	R	S	T	U	V	W	X
				1.0 to 1.6	1.6 to 2.5	2.5 to 4.0	4.0 to 6.3	6.3 to 10	10 to 16	16 to 25	25 to 40	40 to 63	63 to 100	100 to 160	160 to 250	250 to 400	400 to 630	630 to 1000	1000 to 1600
Mini-mold Chip LEDs	1608	0.36									SML-E12Y8W								

Green (M, P, E)

Green (W, I, L)																			(Ta=25°C, If=20mA)			
	Package size(mm)	Luminous Intensity (mcd)	F	G	H	J	K	L	M	N	P	Q	R	S	T	U	V	W	X			
	Height(mm)		0.63 to 1.0	1.0 to 1.6	1.6 to 2.5	2.5 to 4.0	4.0 to 6.3	6.3 to 10	10 to 16	16 to 25	25 to 40	40 to 63	63 to 100	100 to 160	160 to 250	250 to 400	400 to 630	630 to 1000	1000 to 1800			
Mini-mold Chip LEDs	1608	0.36				SML-E12P8W						SMLE12EC6T [®]										
									SML-E12M8W													

Blue (B)


				(Ta=25°C, If=5mA)															
	Package size(mm)	Height(mm)	Luminous Intensity (mcd)	G	H	J	K	L	M	N	P	Q	R	S	T	U	V	W	
				0.9 to 1.4	1.4 to 2.2	2.2 to 3.6	3.6 to 5.6	5.6 to 9.0	9 to 14	14 to 22	22 to 36	36 to 56	56 to 90	90 to 140	140 to 220	220 to 360	360 to 560	560 to 900	
Mini-mold Chip LEDs	1608	0.36								SMLE12BC7T									

White (WB)

				(Ta=25°C, If=5mA)															
	Package size(mm)	Height(mm)	Luminous Intensity (mcd)	P	Q	R	S	T	U	V	W	X1	X2	Y1	Y2	Z1			
				25 to 36	36 to 56	56 to 90	90 to 140	140 to 220	220 to 360	360 to 560	560 to 900	900 to 1100	1100 to 1400	1400 to 1800	1800 to 2200	2200 to 2800			
Mini-mold Chip LEDs	1608	0.36		SMLE12WBC7W															

※Brightness on specification sheet include tolerance of within ± 10%.

Part No. Explanation



Packing Specification

ROHM LED products are being shipped with desiccant (silica gel) concluded in moisture-proof bags.
Pasting the moisture sensitive label on the outer surface of the moisture-proof bags or enclosing the humidity indication card inside the bag is available upon request.
Please contact the nearest sales office or distributor if necessary.

Notes

No copying or reproduction of this document, in part or in whole, is permitted without the consent of ROHM Co.,Ltd.

The content specified herein is subject to change for improvement without notice.

The content specified herein is for the purpose of introducing ROHM's products (hereinafter "Products"). If you wish to use any such Product, please be sure to refer to the specifications, which can be obtained from ROHM upon request.

Examples of application circuits, circuit constants and any other information contained herein illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.

Great care was taken in ensuring the accuracy of the information specified in this document. However, should you incur any damage arising from any inaccuracy or misprint of such information, ROHM shall bear no responsibility for such damage.

The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM and other parties. ROHM shall bear no responsibility whatsoever for any dispute arising from the use of such technical information.

The Products specified in this document are intended to be used with general-use electronic equipment or devices (such as audio visual equipment, office-automation equipment, communication devices, electronic appliances and amusement devices).

The Products specified in this document are not designed to be radiation tolerant.

While ROHM always makes efforts to enhance the quality and reliability of its Products, a Product may fail or malfunction for a variety of reasons.

Please be sure to implement in your equipment using the Products safety measures to guard against the possibility of physical injury, fire or any other damage caused in the event of the failure of any Product, such as derating, redundancy, fire control and fail-safe designs. ROHM shall bear no responsibility whatsoever for your use of any Product outside of the prescribed scope or not in accordance with the instruction manual.

The Products are not designed or manufactured to be used with any equipment, device or system which requires an extremely high level of reliability the failure or malfunction of which may result in a direct threat to human life or create a risk of human injury (such as a medical instrument, transportation equipment, aerospace machinery, nuclear-reactor controller, fuel-controller or other safety device). ROHM shall bear no responsibility in any way for use of any of the Products for the above special purposes. If a Product is intended to be used for any such special purpose, please contact a ROHM sales representative before purchasing.

If you intend to export or ship overseas any Product or technology specified herein that may be controlled under the Foreign Exchange and the Foreign Trade Law, you will be required to obtain a license or permit under the Law.



Thank you for your accessing to ROHM product informations.
More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

<http://www.rohm.com/contact/>

