

RAFIX 16, lamp socket W2 x 4.6d, quick-connect terminal, for W 2 x 4.6d



Description

Lamp socket for snapping in or onto signal lamps.



technical data

> general

Color	light gray
Operating temperature, min.	-25 °C
Operating temperature, max.	55 °C
Storage temperature, min.	-40 °C
Storage temperature, max.	85 °C
illuminated	Yes
Lamp socket	W 2 x 4.6d
Packaging unit	5 pcs.
Net weight	1.8 g
Environment resistance	IEC 60068-2-14 IEC 60068-2-30 IEC 60068-2-33 IEC 60068-2-78
Shock resistance according to standard IEC 60068-2-27	50 g at 11 ms amplitude semi-sinusoidal
Vibration resistance according to standard IEC 60068-2-6	10 g at 20 - 500 Hz
Minimum order quantity (MOQ)	10 pcs.
RoHS compliant	Yes
REACH compliant	Yes
Country of origin	DE

> mounting diameters

Outside dimension, length	15.9 mm
Outside dimension, width	15.9 mm
Outside dimension, height	23.7 mm
Mounting depth	30.5 mm

> mechanical data

Terminal on the rear	Flat quick-connect terminal 2.8 x 0.8
Fixing	Latching
Solderability	No

direct links

> RAFI eCatalog

Use according to UL:

RAFIX control devices are defined at RAFI as modular elements, consisting of an actuating element, if necessary a coupling and an individual contact or lighting unit.

Actuating elements (such as pushbuttons, emergency stop actuators, etc.) have the intended tactility, reset and function only when assembled with the appropriate switching elements.

drawings

System drawing

