Product Summary

BV_{DSS}	$R_{DS(ON)}$ Max	I_D T_C = +25°C
-60V	250mΩ @ V_{GS} = -10V	-6.1A
	300mΩ @ V_{GS} = -4.5V	-5.6A

Features and Benefits

- 100% Unclamped Inductive Switch (UIS) Test in Production
- Low Gate Drive
- Low Input Capacitance
- Fast Switching Speed
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **The DMP6250SEQ is suitable for automotive applications requiring specific change control; this part is AEC-Q101 qualified, PPAP capable, and manufactured in IATF 16949 certified facilities.**
  https://www.diodes.com/quality/product-definitions/

Description and Applications

This MOSFET is designed to meet the stringent requirements of Automotive applications. It is qualified to AEC-Q101, supported by a PPAP and is ideal for use in:

- Motor Control
- DC-DC Converters
- Power Management Functions
- Uninterrupted Power Supply

Mechanical Data

- Case: SOT223
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals Connections: See Diagram Below
- Terminals: Finish - Matte Tin Annealed over Copper Lead Frame. Solderable per MIL-STD-202, Method 208 e3
- Weight: 0.112 grams (Approximate)

SOT223

Top View



Pin Out - Top View



Equivalent Circuit

Ordering Information (Note 4)

Part Number	Case	Packaging
DMP6250SEQ-13	SOT223	2,500 / Tape & Reel

Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
2. See https://www.diodes.com/quality/lead-free/ for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. For packaging details, go to our website at https://www.diodes.com/design/support/packaging/diodes-packaging/.

Marking Information



= Manufacturer's Marking
P6250 = Marking Code
YWW = Date Code Marking
Y = Year (ex: 0 = 2020)
WW = Week (01 to 53)

© Diodes Incorporated
Downloaded from Arrow.com.

Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

Characteristic		Symbol	Value	Unit
Drain-Source Voltage		V_{DSS}	-60	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current (Note 5) V_{GS} = -10V	T_C = +25°C T_C = +70°C	I_D	-6.1 -4.9	A
Maximum Body Diode Continuous Current		I_S	-6.1	A
Pulsed Drain Current (10µs Pulse, Duty Cycle = 1%)		I_{DM}	-14	A
Single Pulsed Avalanche Current (Note 6) L = 0.1mH		I_{AS}	-12	A
Single Pulsed Avalanche Energy (Note 6) L = 0.1mH		E_{AS}	8	mJ

Thermal Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic		Symbol	Value	Unit
Total Power Dissipation (Note 5)	T_A = +25°C	P_D	1.8	W
Thermal Resistance, Junction to Ambient (Note 5)		$R_{\theta JA}$	69	°C/W
Total Power Dissipation (Note 5)	T_C = +25°C	P_D	14	W
Thermal Resistance, Junction to Case (Note 5)		$R_{\theta JC}$	8.7	°C/W
Operating and Storage Temperature Range		T_J, T_{STG}	-55 to +150	°C

Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 7)						
Drain-Source Breakdown Voltage	BV_{DSS}	-60	—	—	V	I_D = -250µA, V_{GS} = 0V
Zero Gate Voltage Drain Current	I_{DSS}	—	—	-1	µA	V_{DS} = -60V, V_{GS} = 0V
Gate-Source Leakage	I_{GSS}	—	—	±100	nA	V_{GS} = ±20V, V_{DS} = 0V
ON CHARACTERISTICS (Note 7)						
Gate Threshold Voltage	$V_{GS(TH)}$	-1	—	-3	V	V_{DS}= V_{GS}, I_D = -250µA
Static Drain-Source On-Resistance	$R_{DS(ON)}$	—	128	250	mΩ	V_{GS} = -10V, I_D = -1.0A
			156	300		V_{GS} = -4.5V, I_D = -0.5A
Diode Forward Voltage	V_{SD}	—	-0.8	-1.2	V	V_{GS} = 0V, I_S = -2.0A
DYNAMIC CHARACTERISTICS (Note 8)						
Input Capacitance	C_{iss}	—	551	—	pF	V_{DS} = -30V, V_{GS} = 0V f= 1MHz
Output Capacitance	C_{oss}	—	25.7	—	pF	
Reverse Transfer Capacitance	C_{rss}	—	19.1	—	pF	
Gate Resistance	R_g	—	12.1	—	Ω	V_{DS} = 0V, V_{GS} = 0V, f = 1MHz
Total Gate Charge (V_{GS} = -4.5V)	Q_g	—	4.8	—	nC	V_{DS} = -30V, I_D = -2A
Total Gate Charge (V_{GS} = -10V)	Q_g	—	9.7	—	nC	
Gate-Source Charge	Q_{gs}	—	1.5	—	nC	
Gate-Drain Charge	Q_{gd}	—	1.6	—	nC	
Turn-On Delay Time	$t_{D(ON)}$	—	6.3	—	ns	V_{DS} = -30V, V_{GS} = -10V, R_G = 50Ω, I_D = -1A
Turn-On Rise Time	t_R	—	10.3	—	ns	
Turn-Off Delay Time	$t_{D(OFF)}$	—	91.4	—	ns	
Turn-Off Fall Time	t_F	—	39.8	—	ns	
Reverse Recovery Time	t_{RR}	—	9.2	—	ns	I_S = -1A, di/dt= 100A/µs
Reverse Recovery Charge	Q_{RR}	—	3.9	—	nC	

Notes:
5. Device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square copper plate.
6. I_{AS} and E_{AS} ratings are based on low frequency and duty cycles to keep T_J = +25°C.
7. Short duration pulse test used to minimize self-heating effect.
8. For design aid only, not subject to production testing.

© Diodes Incorporated
Downloaded from Arrow.com.



Figure 1 Typical Output Characteristics



Figure 2 Typical Transfer Characteristics



Figure 3. Typical On-Resistance vs. Drain Current and Gate Voltage



Figure 4. Typical Transfer Characteristic



Figure 5. Typical On-Resistance vs. Drain Current and Temperature



Figure 6 On-Resistance Variation with Temperature

© Diodes Incorporated
Downloaded from Arrow.com.



Figure 7. On-Resistance Variation with Temperature



Figure 8 Gate Threshold Variation vs. Ambient Temperature



Figure 9 Diode Forward Voltage vs. Current



Figure 10 Typical Junction Capacitance



Figure 11 Gate-Charge Characteristics



Figure 12. SOA, Safe Operation Area

© Diodes Incorporated
Downloaded from Arrow.com.



Figure 13. Transient Thermal Resistance

© Diodes Incorporated
Downloaded from Arrow.com.

Package Outline Dimensions

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT223



SOT223			
Dim	**Min**	**Max**	**Typ**
A	1.55	1.65	1.60
A1	0.010	0.15	0.05
b	0.60	0.80	0.70
b1	2.90	3.10	3.00
C	0.20	0.30	0.25
D	6.45	6.55	6.50
E	3.45	3.55	3.50
E1	6.90	7.10	7.00
e	-	-	4.60
e1	-	-	2.30
L	0.85	1.05	0.95
Q	0.84	0.94	0.89
All Dimensions in mm			

Suggested Pad Layout

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT223



Dimensions	Value (in mm)
C	2.30
C1	6.40
X	1.20
X1	3.30
Y	1.60
Y1	1.60
Y2	8.00

© Diodes Incorporated
Downloaded from Arrow.com.

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2020, Diodes Incorporated

www.diodes.com

Downloaded from Arrow.com.