

Product Line

DeepTronica >

Single Pair Ethernet >

ZConnect >

Ceres >

X-Lok >

Accessory

Middle Size

Mini Size

Large Size

Standard Size

M Series >

FLOS & FLOS+ >

Power >

RBL >

HS-Lok >

NMEA 2000 >

Heavy Duty Shielded >

RJ >

USB >

SSL >

HDMI >

DVI >

Fiber Optic >

RF >

Cable Joiner >

Cable Gland >

Pressure Relief Vent >

LED Light Guide >

D-Sub >



BD-05BFMA-QL8SP0

Operating Temperature: -40°C ~ +105°C

Transmission Speed: N/A


Shielded: Plastic, Non-shielded

Jacket Material: N/A

Certificate: UL1977

You must login first for view the price

Quantity - 1 +

 Add to Cart

 Inquiry




Can't find? [Customize your part](#)

Mating Pair & Accessories

Connector Type


 Search



X-Lok, Standard...  
AB-BD05FL-BDHL  
-20°C ~ +80°C

- 0 +


☐



X-Lok, Standard...  
AB-BD05FL-BDHL  
-20°C ~ +80°C

- 0 +


☐



X-Lok, Standard...  
AB-BD05FL-BDHL  
-20°C ~ +80°C

- 0 +


☐



X-Lok, Standard...  
AB-BD05FL-BDHL  
-20°C ~ +80°C

- 0 +


☐



X-Lok, Standard...  
AB-BD05FL-BDHL  
-20°C ~ +80°C

- 0 +


☐





X-Lok, Standard...  
AB-BD05FL-BDHL  
-20°C ~ +80°C

- 0 +

☐

 Add to Cart

 Inquiry

Specifications	Download / CAD
Nominal Current <b>5A</b>	Connector Type <b>Field Installable</b>
Shielded <b>Plastic, Non-shielded</b>	No. of Contacts <b>05</b>
Connector Gender <b>Female</b>	Backshell <b>Straight</b>
Mating Style <b>Push Lock</b>	IP Rating <b>IP68</b>
Assembly Style <b>Crimp</b>	
<div> <a href="#">More Options</a></div>	

People Also Bought



BD-05BFMA-QL8SP0



CAP-WADFLC01



CB-05PMMM-LL7A04



MSAS-17BMMM-...



8A-03AFFM-SR7A03