


**SERIES:** TS33 | **DESCRIPTION:** TACTILE SWITCH**FEATURES**

- right angle
- halogen & halogen free

**SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
rated voltage		1		12	Vdc
rated current		0.01		50	mA
withstanding voltage	for 1 minute		250		Vac
contact resistance				100	mΩ
insulation resistance	at 100 Vdc	100			MΩ
operating force	160 gf models 260 gf models	110 190	160 260	210 330	gf gf
return force		30			gf
actuator travel		0.1	0.2	0.3	mm
operating temperature		-20		70	°C
storage temperature		-30		80	°C
life	at 5 Vdc, 5 mA, 2 cycles/second, 1.5 times operating force 160 gf models 260 gf models		100,000 50,000		cycles cycles
vibration	10~55~10 Hz, 1.5 mm amplitude, 2 hours on each XYZ				
flammability rating	see material table				
RoHS	yes				

PART NUMBER KEY**TS33 - 46 - 35 - BK - XXX - X - SMT - TR**



Base Number

Actuator Force (gf):
160 = 160
260 = 260Halogen Free:
'blank' = with halogen
H = halogen free

MECHANICAL DRAWING


units: mm
tolerance:
L≤10: ±0.3
10<L≤100: ±0.5
unless otherwise specified

DESCRIPTION	MATERIAL	PLATING/COLOR
housing	LCP	white
terminal	phosphor bronze	silver
dome	stainless steel	silver
cover	phosphor bronze	silver
stem	LCP	black



SOLDERABILITY

parameter	conditions/description	min	typ	max	units
reflow soldering			260		°C



PACKAGING

units: mm

Reel QTY: 3,000 pcs

REVISION HISTORY

rev.	description	date
1.0	initial release	12/09/2024

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

sameskydevices.com