

StorFly® 2.5-Inch SATA Solid-State Drive

Series 6 (Gen2), SATA-III (6Gb/s), 3D TLC

VSFF25CC960G-V11

Product Brief - Rev. 1.3 See Datasheet for all details



Description

Virtium's StorFly Series 6 2.5" is high-performance SATA-III 6Gb/s embedded solid-state drive (SSD) technology designed for the unique capacity and workload requirements of a broad range of embedded systems, including telco and networking, industrial PC and automation, test and measurement, medical diagnostics and imaging, transportation, defense command and control, self-serve kiosk and POS, security and surveillance, and data recorders.

Features

Capacity

• 960 GB

3D TLC NAND

Sequential Performance

• 128kB Sequential Read: 550 MB/s (QD: 32)

• 128kB Sequential Write: 490 MB/s (QD: 32)

Random Performance

4kB IOPS Read: up to 77,000 (QD: 32)

• 4kB IOPS Write: up to 66,000 (QD: 32)

Power: 5.0V±10%

• 128kB Sequential Read: 2.80 W

• 128kB Sequential Write: 3.33 W

4kB Random Read: 3.00 W

• 4kB Random Write: 3.30 W

• Idle: 0.56 W

Temperature Ranges

• Commercial: 0°C to 70°C

• Non-Operating: -40°C to 85°C

Reliability

Advanced LDPC ECC

• MTBF: >2M hours

Endurance

• JESD219A: 801 TBW

Sequential: 2,972 TBW

Note: (1) Available in parts with -T part number extension



Electrostatic Discharge (ESD) can damage this device. When handling the device, always wear a grounded wrist strap and use a static dissipative surface.

vtGuard® Power Fail Protection

- · Integrated power fail protection
- Preserves static data in the event of power failure
- Cache/buffer contents restored at power-on

SMART Attribute Reporting

- Monitors device health
- Anticipates and predicts failures

Mechanical Dimensions

- 2.5-Inch Form Factor
- Length x Width x Height mm (inches)
 100.5 (3.96) x 69.85 (2.75) x 7.0 (0.275)

Compliance

- SATA Revision 3.1 (SATA-III 6Gb/s)
- ATA/ATAPI-8 (ACS-3)
- FCC, CE, UL, RoHS, WEEE

Environmental (Non-operating)

- Humidity (non-condensing): 5% to 95%
- Shock: 1500G, half-sine wave, 0.5ms duration
- Vibration: 20G, 20 Hz to 2000 Hz

Data Security

- Integrated AES-256 encryption (data-at-rest)
- Crypto Erase
- TCG/Opal 2.0-compliant SED(1)

StorKit® Software - visit virtium.com to learn more.

vtView[®], vtSecure[™], vtTools[™]



Any damage to the unit that occurs after its removal from the shipping package and ESD protective bag is the responsibility of the user.

Tel 949.888.2444 – 30052 Tomas, Rancho Santa Margarita, CA 92688 USA – www.virtium.com