

ix Type A OM Cat.6A Rail 2.0m



Part number	33 48 313 1819 020
Specification	ix Type A OM Cat.6A Rail 2.0m
HARTING eCatalogue	https://harting.com/33483131819020

Image is for illustration purposes only. Please refer to product description.

Identification

Category	System cabling
Series	HARTING ix Industrial [®]
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	HARTING ix Industrial [®] PushPull IP20 Type A Overmoulded IDC termination
Connector 2	HARTING ix Industrial [®] PushPull IP20 Type A Overmoulded IDC termination
Type of cable	Copper cable (round)
Description of the cable	for railway applications
Features	electron beam crosslinked Comp 752

Version

Cable length	2 m
Number of cores	8
Core structure	4x 2x AWG 26/7
Number of contacts	8

Technical characteristics

Transmission characteristics	Cat. 6 _A Class E _A up to 500 MHz	
------------------------------	--	--

Page 1 / 3 | Creation date 2025-04-02 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany

Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com



Technical characteristics

Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s 5 Gbit/s 10 Gbit/s
Limiting temperature	-40 +80 °C unmoved -40 +80 °C moved

Material properties

Material (cable)	Polyolefin copolymer electron beam crosslinked Comp 752
Colour (cable)	Black
RoHS	compliant
ELV status	compliant
China RoHS	е
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

Specifications and approvals

Specifications	EN 45545-2 Fire protection on railway vehicles EN 50264-1 Fire protection on railway vehicles EN 50306-1 Fire protection on railway vehicles NFPA 130 Fire protection on railway vehicles UN/ECE-R 118 fire protection for rolling stock EN 50155 Shock and vibration resistance EN 60811-404 Oil resistance EN 50618 LIV resistant
	EN 60811-404 Oil resistance EN 50618 UV resistant
	IEC 61076-3-124

Commercial data

Packaging size	1
Net weight	125.7 g
Country of origin	Latvia
European customs tariff number	85444290
GTIN	5713140332256
eCl@ss	27060390 Ready-made data cable (unspecified)

Page 2 / 3 | Creation date 2025-04-02 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Customised Solutions GmbH & Co. KG | In der Tütenbeke 22 | 32339 Espelkamp | Germany

Phone +49 5772 47-0 | info@HARTING.com | www.HARTING.com

Product data sheet 33 48 313 1819 020 ix Type A OM Cat.6A Rail 2.0m



Commercial data

UNSPSC 24.0 26121600