
REVISIONS							
REV	ECO	DESCRIPTION	DATE	BY	APPR		
B1	-	RELEASED DRAWING	JAN-18-2014	ARROW	TOMMY		


ECO-MATE, CORD GRIP, SIZE 16

RT0L-16CG-xx

REV: B1 SH: 1







	€ 61Max	1
	15/16-20 UNEF THREAD —	
24.9		 Ø26.5

P/N	SHIELDING RING	CABLE RANGE
RT0L-16CG-C1	WITHOUT	Ø9.0-Ø14.5mm
RT0L-16CG-C2	WITHOUT	Ø13.5-Ø17mm
RT0L-16CG-S1	WITH	Ø9.0-Ø14.5mm
RT0L-16CG-S2	WITH	Ø13.5-Ø17mm

NOTES : (UNLESS OTHERWISE SPECIFIED)

1. MATERIAL :

1.1. NUT: ZINC ALLOY, NICKEL PLATED.

1.2. CLAMP INSERT : THERMOPLASTIC UL94 V-0. 1.3. EMI SHIELDING RING : STAINLESS STEEL.

1.4. BACK SHELL: ZINC ALLOY, NICKEL PLATED.

1.5. O-RING: SILICONE RUBBER.

1.6. GROMMET: RUBBER.

2. ROHS COMPLIANT.

3. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

QUANTITY	PART NUMBER		DESCRIPTION			IT			
			MAT	ERI	٩LS	S LI	ST		
	WISE SPECIFIED	SIGI	NATURES	DATE	Amphenol				
All dimensions a Tolerances are a PL DEC +0.30	as follows:	DRAWN: ARROW JAN-17-2014			Amphenoi				
2 PL DEC ±0.15 3 PL DEC ±0.08	Fractions ±1/64 Angles ±1°	CHECKED:			Sine Systems - www.amphenol-sine.cor				
3) Note reference = X		ENGINEER:			44724 Morley Drive Clinton Township, MI 48036				
MATERIAL SPECIFICA	TIONS:	APPROVAL:							
PROCESS SPECIFICATIONS: NEXT ASSY:		CUSTOMER:			ECO-MATE,CORD GRIP				
			NG IS SUPPLIED				SIZE 16		
		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAI		В	C-	RT0L-160	G-xx	B	
				SCALE: N	ONE		SHEET 1	or 1	