

NOTES:

1. MATERIALS:


BARREL, SHELL, SLEEVE - BRASS ALLOY, NICKEL PLATED
 MICRO CONTACTS - BRASS ALLOY, GOLD PLATED
 BNC CONTACT - BERYLLIUM COPPER, GOLD PLATED
 INSULATORS - TEFLON

2. CHARACTERISTIC IMPEDANCE: 75 Ohms.

3. MEETS SMPTE ST 2082-1 SPEC; BANDWIDTH: 12 GHz.

4. THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

						THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.											
					UNLESS OTHERWISE SPECIFIED 1. ALL DIMENSIONS IN INCHES [mm] - TWO PLACE DECIMALS ±0.02 [0.5] - THREE PLACE DECIMALS ±0.005 [0.13]	SIZE		WIDTH		MULT		LBS/M		TEMPER			
						FINISH SPEC No.						MATERIAL SPEC No.					
						FIRST USED ON				SCALE 3:2							
						DATE DRAWN 8/4/21		BY MS	CHKD MS 8/4/21		APVD * *						
0A	P-20014-1	8/4/21	MS	*		SHEET 1 OF 1											
REV	ECO NUMBER	DATE	BY	APVD													
REVISIONS					DO NOT SCALE DRAWING	NAME ADAPTER, BNC TO MICRO WECO, LONG						PART No. VMMPBNCFL				REV 0A	

DO NOT SCALE DRAWING

SolidWorks CAD File

