

TABLE 1

CLASS	MATERIAL/FINISH
F	ALUMINIUM/NICKEL PLATED
K	STAINLESS STEEL/PASSIVATED
KE	STAINLESS STEEL/PASSIVATED
W	ALUMINIUM/OLIVE DRAB CADMIUM PLATED
Z	ALUMINIUM/ZINK NICKEL PLATED

TABLE 4

CABLE ENTRY SIZE CODE	AA +/-0,1	BB +/-0,1	CC +/-0,3	DD +0,2/-0
A	4,7	7,7	12,2	1,12
B	6,4	9,4	14,0	1,12
C	7,9	11,0	15,5	1,12
D	9,5	12,6	17,1	1,12
E	11,1	14,1	18,7	1,12
F	12,7	15,7	20,3	1,12
G	15,9	18,9	23,5	1,12
H	19,1	22,0	26,7	1,12
J	22,2	25,2	29,8	1,75
K	25,5	28,4	33,0	1,75
L	28,6	31,5	36,2	1,75
M	31,8	34,7	39,4	1,75


TABLE 2

SHELL SIZE	A MAX	B MAX	C THREAD	D +0/-0,25	D2 +0/-0,25	E MAX	G MAX	H MAX	J MAX	I MIN	N	MAXIMUM ENTRY SIZE
08	22,48	15,67	1/2-20 UNF	6,86	6,68 see note 3	15,30	16,10	10,20	31,05	4,95	12	D
10	25,65	18,64	5/8-24 UNEF	9,53	9,35 see note 3	15,30	17,90	13,70	34,21	4,95	15	F
12	28,83	21,79	3/4-20 UNEF	12,98	12,62 see note 3	15,30	19,40	16,80	37,95	4,95	21	H
14	32,00	24,99	7/8-20 UNEF	14,86	14,86	15,30	20,00	17,90	39,65	4,95	24	J
16	35,18	28,24	1-20 UNEF	18,03	17,73 see note 3	15,30	21,60	21,20	41,25	4,95	30	K
18	38,55	30,94	1 1/16-18 UNEF	20,04	20,04	15,30	22,60	23,20	43,75	4,95	33	K
20	41,53	34,16	1 3/16-18 UNEF	23,22	23,22	15,30	24,10	26,20	46,91	4,95	36	L
22	44,70	37,29	1 5/16-18 UNEF	26,39	26,39	15,30	25,70	29,40	50,10	4,95	39	M
24	47,89	40,46	1 7/16-18 UNEF	29,31	29,31	15,30	27,40	32,60	53,29	4,95	42	M
28	54,23	49,45	1 3/4-18 UNS	35,28	35,28	15,30	30,90	39,60	56,46	4,95	54	M

* NOTES:

- 1 - MINIMUM PENETRATION OF ØD OR ØD2 FROM FRONT OF SERRATIONS
- 2 - PLEASE NOTE THERE MAY BE CROSSOVER DEPENDENT ON DIAMETER AND PITCH
- 3 - APPLY TOLERANCE +0,18/-0

EN3660-065W10B



DRAWN W.RUST	DATE 26/04/2018	3RD ANGLE PROJECTION NOT TO SCALE	POLAMCO LTD www.polamco.com	WESTON LOCK LOWER BRISTOL ROAD BATH BA2 1EP	THIS DRAWING IS COPYRIGHT AND THE PROPERTY OF POLAMCO LTD IT MUST NOT BE COPIED, USED FOR MANUFACTURE OR OTHERWISE DISCLOSED WITHOUT PRIOR WRITTEN CONSENT OF THE COMPANY.
SALES APPR H.TAILLANDIER	DATE 26/04/2018				
DESIGN APPR M.PAUL	DATE 04/04/2014	UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN MILLIMETRES GENERAL TOL LINEAR +/-0,25MM ANGULAR +/- 3°	ASSY USED ON: EN2997		
PROD APPR J.STEPHENSON	DATE 04/04/2014		TITLE: 90° ANTI-DECOUPLING BANDING ADAPTOR		
QUAL APPR P.REES	DATE 04/04/2014	MATERIAL SEE ABOVE FINISH SEE ABOVE	PART NUMBER: EN3660-065****		
ISSUE 2	DCR 6780		DRAWING NO: P20030	SHT 1	
NCAGE CODE U5792		WEIGHT			