

PB Busway Tap Off Unit, w/ Metering, 1x2 Pole 3 Wire 30A, L2-L3, 1 Drop cord, 3ft, L6-30, 208V

PBP4A12L630BCM1

Discontinued on: Jul 2, 2025

(!) Discontinued

Overview

Presentation	Factory-assembled and tested, the metered tap off units house a PowerLogic power meter, standard circuit breakers and a pre-terminated cord set. No tools required for installation on 100A, 225A, or 400A busway straight sections.
I ead time	Ligually Shine within 3 Weeks

Main

Main Output Voltage	208 V
Provided Equipment	Installation quido

Physical

Color	Black
Height	14.02 in (35.6 cm)
Width	8.5 in (21.5 cm)
Depth	5.7 in (14.5 cm)
Net Weight	17.99 lb(US) (8.16 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Input Frequency 60 Hz

Output

Maximum Total Current Draw per Phase	30 A
Number of power socket outlets	1 NEMA L6-30R
Cord Length	3 ft (0.9 m)

Conformance

Product Certifications	cUL Listed	
Trouble Continuous	COL LISICU	
	CSA	
	SOA	
	III Listed	

Environmental

Ambient Air Temperature for Operation	14104 °F (-1040 °C)
Relative Humidity	095 %

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Operating altitude	010000 ft
Ambient Air Temperature for Storage	-22158 °F (-3070 °C)
Storage Relative Humidity	095 %
Storage altitude	015000 ft (04572 m)

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Contractual warranty

Warranty 1 year (parts only)



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

EU RoHS Directive

Under investigation

Image of product / Alternate images

Alternative



