




TE Connectivity: Every Connection Counts
© 2016 TE Connectivity Ltd. family of companies. All Rights Reserved

+ RELAYS, CONTACTORS & SWITCHES
TO-5/.100 GRID



✓ Active

TE CONNECTIVITY (TE)

JMGAPD-6L=M39016/18-026L

8-1617542-7

TE Internal Number: 8-1617542-7

Mil-Spec: M39016/18-026L

Alias ID: JMGAPD-6L

Contact Arrangement 2 Form C, DPDT, 2 C/O

Input Voltage (VDC) 3.5

Coil Suppression Diode With

MOSFET Driver Without

Transistor Driver Without

DOCUMENTATION

No documentation available.

FEATURES

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

- MOSFET Driver Without
- Product Type Relay
- Coil Latching Without
- Relay Type Military/Aerospace High Performance
- Enclosure Type Hermetically Sealed

Configuration Features

- Transistor Driver Without

Electrical Characteristics

- Input Voltage (VDC) 3.5
- Coil Suppression Diode With
- Coil Voltage (VDC) 6
- Coil Resistance (Ω) 98
- Coil Power Rating (DC) (mW) 367
- Coil Polarity Protection Diode Without
- Contact Switching Voltage (Max) 28
- Shock 75G's, 6ms
- Vibration 30G's, 10 – 3000Hz
- Actuating System DC
- Coil Power Measurement Milliwatts
- Coil Magnetic System Non-Polarized, Monostable

Contact Features

Contact Arrangement 2 Form C, DPDT, 2 C/O**Contact Current Rating (A)** 1**Contact Current Class** Low Level – 1 A

Termination Features

Termination Type PC Pins

Mechanical Attachment

Mounting Type PC Board

Usage Conditions

Operating Temperature Range (°C) -65 – 125