


HiPerFRED Module

V_{RRM} = 600 V
I_{FAV} = 2x 95 A
t_{rr} = 35 ns

Common Anode


Part number

MPK95-06DA



Backside: isolated

 E72873



Features / Advantages:

- Planar passivated chips
- Very low leakage current
- Very short recovery time
- Improved thermal behaviour
- Very low I_{rm}-values
- Very soft recovery behaviour
- Avalanche voltage rated for reliable operation
- Soft reverse recovery for low EMI/RFI
- Low I_{rm} reduces:
 - Power dissipation within the diode
 - Turn-on loss in the commutating switch

Applications:

- Antiparallel diode for high frequency switching devices
- Antisaturation diode
- Snubber diode
- Free wheeling diode
- Rectifiers in switch mode power supplies (SMPS)
- Uninterruptible power supplies (UPS)

Package: TO-240AA

- Isolation Voltage: 4800 V~
- Industry standard outline
- RoHS compliant
- Height: 30 mm
- Base plate: DCB ceramic
- Reduced weight
- Advanced power cycling

Disclaimer Notice


Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

Fast Diode

Symbol	Definition	Conditions	Ratings			
			min.	typ.	max.	
V_{RSM}	max. non-repetitive reverse blocking voltage	$T_{VJ} = 25^\circ C$			600	V
V_{RRM}	max. repetitive reverse blocking voltage	$T_{VJ} = 25^\circ C$			600	V
I_R	reverse current, drain current	$V_R = 600 V$ $V_R = 600 V$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$		1,3 5	mA
V_F	forward voltage drop	$I_F = 50 A$ $I_F = 100 A$ $I_F = 50 A$ $I_F = 100 A$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 125^\circ C$		1,73 1,89 1,22 1,40	V
I_{FAV}	average forward current	$T_C = 110^\circ C$ rectangular $d = 0.5$	$T_{VJ} = 150^\circ C$		95	A
V_{F0} r_F	threshold voltage slope resistance	for power loss calculation only			0,98 2,3	V mΩ
R_{thJC}	thermal resistance junction to case				0,58	K/W
R_{thCH}	thermal resistance case to heatsink			0,10		K/W
P_{tot}	total power dissipation		$T_C = 25^\circ C$		215	W
I_{FSM}	max. forward surge current	$t = 10 \text{ ms}; (50 \text{ Hz}), \text{sine}; V_R = 0 V$	$T_{VJ} = 45^\circ C$		1,20	kA
C_J	junction capacitance	$V_R = 600 V$ $f = 1 \text{ MHz}$	$T_{VJ} = 25^\circ C$	70		pF
I_{RM}	max. reverse recovery current		$T_{VJ} = 25^\circ C$ $T_{VJ} = 100^\circ C$	4 5,5		A
t_{rr}	reverse recovery time	$I_F = 130 A; V_R = 100 V$ $-di_F/dt = 300 A/\mu s$	$T_{VJ} = 25^\circ C$ $T_{VJ} = 100^\circ C$	35 tbd		ns ns

Package TO-240AA

Symbol	Definition	Conditions	min.	typ.	max.	Unit
I_{RMS}	<i>RMS current</i>	per terminal			200	A
T_{VJ}	<i>virtual junction temperature</i>		-40		150	°C
T_{op}	<i>operation temperature</i>		-40		125	°C
T_{stg}	<i>storage temperature</i>		-40		125	°C
Weight				76		g
M_D	<i>mounting torque</i>		2,5		4	Nm
M_T	<i>terminal torque</i>		2,5		4	Nm
$d_{Spp/App}$	<i>creepage distance on surface striking distance through air</i>		terminal to terminal	13,0	9,7	mm
$d_{Spb/Apb}$			terminal to backside	16,0	16,0	mm
V_{ISOL}	<i>isolation voltage</i>	$t = 1$ second $t = 1$ minute 50/60 Hz, RMS; $I_{ISOL} \leq 1$ mA		4800		V
				4000		V



Ordering	Ordering Number	Marking on Product	Delivery Mode	Quantity	Code No.
Standard	MPK95-06DA	MPK95-06DA	Box	36	501058

Equivalent Circuits for Simulation
^{* on die level}
 $T_{VJ} = 150^\circ\text{C}$


Outlines TO-240AA
