





Connection data			
Clamping units	6	<b>Connection 1</b>	
Total number of potentials	3		
Number of levels	1		
		Connection technology	CAGE CLAMP®
		Actuation type	Operating tool
		Connectable conductor materials	Copper
		Solid conductor	2.5 ... 16 mm² / 14 ... 6 AWG
		Fine-stranded conductor	2.5 ... 16 mm² / 16 ... 6 AWG
		Strip length	12 ... 13 mm / 0.47 ... 0.51 inches
		Pole number	3
		Wiring direction	Side-entry wiring

Physical data		
Width	52.5 mm / 2.067 inches	
Height	105 mm / 4.134 inches	
Depth from upper-edge of DIN-rail	55 mm / 2.165 inches	

Mechanical data		
Mounting type	DIN-35 rail	
Mounting (note)	The fixed foot of the fuse terminal block must face upwards so that the fuse cannot fall out.	

Material data		
Note (material data)	<a href="#">Information on material specifications can be found here</a>	
Color	light gray	
Material group	I	
Insulation material (main housing)	Polyamide (PA66)	
Flammability class per UL94	V0	
Fire load	0 MJ	
Weight	51 g	

Environmental requirements		
Processing temperature	-35 ... +85 °C	
Continuous operating temperature	-35 ... +85 °C	

Commercial data		
Product Group	1 (Rail Mounted Terminal Blocks)	
eCl@ss 10.0	27-14-11-16	
eCl@ss 9.0	27-14-11-16	
ETIM 8.0	EC002705	
ETIM 7.0	EC002705	
PU (SPU)	4 pcs	
Packaging type	Box	
Country of origin	CN	
GTIN	4050821877660	
Customs tariff number	85369095000	



Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Approvals / Certificates

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Confor- mity WAGO GmbH & Co. KG	-	-

Downloads

Environmental Product Compliance

Compliance Search




























Environmental Product  
Compliance 811-330

↓

Documentation				
Additional Information		Bid Text		
Technical Section	pdf 2246.92 KB	811-330	19.02.2019	xml 3.81 KB
			14.03.2017	doc 26.00 KB

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 811-330	EPLAN Data Portal 811-330
	WSCAD Universe 811-330
	ZUKEN Portal 811-330



1 Compatible Products			
1.1 Optional Accessories			
1.1.1 Ferrule			
1.1.1.1 Ferrule			
			
<a href="#">Item No.: 216-209</a> Ferrule; Sleeve for 10 mm² / AWG 8; insulated; electro-tin plated; red	<a href="#">Item No.: 216-109</a> Ferrule; Sleeve for 10 mm² / AWG 8; uninsulated; electro-tin plated	<a href="#">Item No.: 216-208</a> Ferrule; Sleeve for 6 mm² / AWG 10; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; yellow	<a href="#">Item No.: 216-108</a> Ferrule; Sleeve for 6 mm² / AWG 10; uninsulated; electro-tin plated; silver-colored
			
<a href="#">Item No.: 216-545</a> Twin ferrule only for 811 series; Sleeve for 2 x 2.5 mm / AWG 14; insulated; Nominal current 63 A; blue	<a href="#">Item No.: 216-546</a> Twin ferrule only for 811 series; Sleeve for 2 x 4 mm / AWG 12; insulated; Nominal current 63 A; gray	<a href="#">Item No.: 216-547</a> Twin ferrule only for 811 series; Sleeve for 2 x 6 mm / AWG 10; insulated; Nominal current 63 A; yellow	
1.1.2 Installation			
1.1.2.1 Locking system			
			
<a href="#">Item No.: 811-612</a> Coupling kit; for 12 poles; red			
1.1.3 Jumper			
1.1.3.1 Jumper			
			
<a href="#">Item No.: 811-480</a> Jumper; 10-way; insulated; light gray	<a href="#">Item No.: 811-481</a> Jumper; 11-way; insulated; light gray	<a href="#">Item No.: 811-482</a> Jumper; 12-way; insulated; light gray	<a href="#">Item No.: 811-472</a> Jumper; 2-way; insulated; light gray
			
<a href="#">Item No.: 811-473</a> Jumper; 2-way; insulated; light gray	<a href="#">Item No.: 811-474</a> Jumper; 4-way; insulated; light gray	<a href="#">Item No.: 811-475</a> Jumper; 5-way; insulated; light gray	<a href="#">Item No.: 811-476</a> Jumper; 6-way; insulated; light gray
			
<a href="#">Item No.: 811-477</a> Jumper; 7-way; insulated; light gray	<a href="#">Item No.: 811-478</a> Jumper; 8-way; insulated; light gray	<a href="#">Item No.: 811-479</a> Jumper; 9-way; insulated; light gray	
1.1.4 Marking			
1.1.4.1 Label			
			
<a href="#">Item No.: 210-805</a> Labels; for Smart Printer; permanent adhesive; 6 x 15 mm; white	<a href="#">Item No.: 210-805/000-002</a> Labels; for Smart Printer; permanent adhesive; 6 x 15 mm; yellow	<a href="#">Item No.: 210-806</a> Labels; for Smart Printer; permanent adhesive; 9 x 15 mm; white	<a href="#">Item No.: 210-806/000-002</a> Labels; for Smart Printer; permanent adhesive; 9 x 15 mm; yellow
			
<a href="#">Item No.: 210-705</a> Labels; for TP printers; permanent adhesive; 6 x 15 mm; white	<a href="#">Item No.: 210-705/000-002</a> Labels; for TP printers; permanent adhesive; 6 x 15 mm; yellow	<a href="#">Item No.: 210-706</a> Labels; for TP printers; permanent adhesive; 9 x 15 mm; white	<a href="#">Item No.: 210-706/000-002</a> Labels; for TP printers; permanent adhesive; 9 x 15 mm; yellow



1.1.4.2 Marker



**Item No.: 793-5501/000-006**  
WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; blue



**Item No.: 793-5501/000-014**  
WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; brown



**Item No.: 793-5501/000-007**  
WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; gray



**Item No.: 793-5501/000-023**  
WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; green



**Item No.: 793-5501/000-017**  
WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; light green



**Item No.: 793-5501/000-012**  
WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; orange



**Item No.: 793-5501/000-005**  
WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; red



**Item No.: 793-5501/000-024**  
WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; violet



**Item No.: 793-5501**  
WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; white



**Item No.: 793-5501/000-002**  
WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; yellow



**Item No.: 793-501/000-006**  
WMB marking card; as card; not stretchable; plain; snap-on type; blue



**Item No.: 793-501/000-007**  
WMB marking card; as card; not stretchable; plain; snap-on type; gray



**Item No.: 793-501/000-023**  
WMB marking card; as card; not stretchable; plain; snap-on type; green



**Item No.: 793-501/000-017**  
WMB marking card; as card; not stretchable; plain; snap-on type; light green



**Item No.: 793-501/000-012**  
WMB marking card; as card; not stretchable; plain; snap-on type; orange



**Item No.: 793-501/000-005**  
WMB marking card; as card; not stretchable; plain; snap-on type; red



**Item No.: 793-501/000-024**  
WMB marking card; as card; not stretchable; plain; snap-on type; violet



**Item No.: 793-501**  
WMB marking card; as card; not stretchable; plain; snap-on type; white



**Item No.: 793-501/000-002**  
WMB marking card; as card; not stretchable; plain; snap-on type; yellow



**Item No.: 2009-115/000-006**  
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; blue



**Item No.: 2009-115/000-007**  
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; gray



**Item No.: 2009-115/000-023**  
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green



**Item No.: 2009-115/000-017**  
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; light green



**Item No.: 2009-115/000-012**  
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; orange



**Item No.: 2009-115/000-005**  
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; red



**Item No.: 2009-115/000-024**  
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; violet



**Item No.: 2009-115**  
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white



**Item No.: 2009-115/000-002**  
WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; yellow

1.1.4.3 Marker carrier



**Item No.: 285-442**  
Adaptor; gray

1.1.5 Supply module

1.1.5.1 Supply module



**Item No.: 811-471**  
Supply module; 35 mm<sup>2</sup>; for 811 Series Fuse Terminal Blocks; SCREW CLAMP CONNECTION; 35,00 mm<sup>2</sup>; light gray

1.1.6 Test and measurement

1.1.6.1 Testing accessories



Item No.: 206-912  
WAGO Test Probes; 2 mm Ø; 1000 V; CAT IV; 10 A

Installation Notes

Installation



Creating a 2- or 3-pole fuse terminal block via coupling kit.




Removing a terminal block from the DIN-rail.


Conductor termination



Open and close lever via operating tool.



**CAGE CLAMP® connection**  
Inserting a conductor.  
Opening the clamping unit via integrated lever.



Terminating ferruled conductors up to 10 mm² (8 AWG).

Commoning




Jumper bar for quick and convenient commoning



Inserting a fuse.



Marking



WMB marker slot for convenient identification



Marker carriers (285-442) for continuous marking strips