



Part Number : [1202440207](#)

Product Description : Micro-Change (M12) Circular Hybrid Technology (CHT) Double-Ended Cordset, 8 Poles (4 Signal, 4 Power), Y-Coded, Male (Straight) to Male (Straight), 10.0m (32.81') Length, Type 1

Series Number : 120244

Status : Active

Product Category : Circular Industrial Cordsets




Documents and Resources

Drawings

[1202440207_sd.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	 per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2021)10043-DC (17 Jan 2022)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

UKCA - Declaration of Conformity

CE - Declaration of Conformity

Part Details

General

Status	Active
Category	Circular Industrial Cordsets
Series	120244
Description	Micro-Change (M12) Circular Hybrid Technology (CHT) Double-Ended Cordset, 8 Poles (4 Signal, 4 Power), Y-Coded, Male (Straight) to Male (Straight), 10.0m (32.81') Length, Type 1
IP Rating	IP67
Performance Category	5e
Product Name	CHT, Micro-Change (M12)
Type	Double Ended
UPC	884982667662

Agency

UL	E218123
----	---------

Electrical

Current - Maximum per Contact	0.5A, 6.0A
Voltage - Maximum	30V

Physical

Cable Diameter	8.00mm (.315")
Cable Length	10.0m (32.81')
Color - Cable Jacket	Gray
Connector End A	CHT4+4 (M12 Hybrid)

Connector End B	CHT4+4 (M12 Hybrid)
Coupling Style	Threaded
Gender	Male-Male
Keyway	Y-Coded
LED Indicator	None
Material - Cable Jacket	PUR
Material - Connector Body	Brass, PA
Material - Contact	Copper Alloy
Material - Coupling Nut	Brass
Material - Plating Mating	Gold
Net Weight	865.182/g
Orientation	Straight to Straight
Poles	8
Temperature Range - Operating	-25° to +75°C
Wire/Cable Type	Unshielded-Twisted Pair
Wire Size (AWG)	18, 26

Mates With / Use With

Mates with Part(s)

Description	Part Number
Micro-Change (M12) Circular Hybrid Technology (CHT) Female Receptacle, Dual Keyway, M16x1.5mm Back Panel Mount, 8 Pole (4 Signal, 4 Power)	<u>1202440002</u>

This document was generated on Jun 14, 2026