

# MPI2520

## High Current, Low Profile, Miniature Power Inductors

**Applications:**

- Mobile/smart phones
- Handheld/mobile equipment
- Digital cameras
- Media players
- GPS
- MP3 Players
- Tablets/e-readers

**Environmental data:**

- Storage temperature range (Component): -40°C to +125°C
- Operating temperature range: -40°C to +125°C (ambient + self temperature rise)
- Solder reflow temperature: J-STD-020D compliant

**Packaging:**

- Supplied in tape and reel packaging, 3000 parts per 7" diameter reel

**Product description:**

- Halogen free, lead free, RoHS compliant
- 125°C maximum total temperature operation
- 2.7 x 2.2 x 1.0 / 1.2mm maximum surface mount package
- Magnetically shielded, low EMI
- Inductance range from 0.47µH to 10.0µH
- Current range from 1.1 to 4.8 amps



Powering Business Worldwide

## Product specifications


Part Number <sup>5</sup>	OCL1 (μH)±20%	I <sub>rms</sub> <sup>2</sup> (Amps)	I <sub>sat</sub> <sup>3</sup> (Amps)	DCR (mΩ) @ 25°C typical	DCR (mΩ) @ 25°C max	K-Factor <sup>4</sup>
R0 — 1.0mm Height						
MPI2520R0-R47-R	0.47	4.1	4.4	28	34	2887
MPI2520R0-1R0-R	0.9	3.2	3.2	50	60	1925
MPI2520R0-1R5-R	1.5	2.4	2.6	80	96	1444
MPI2520R0-2R2-R	2.2	2.2	2.4	103	124	1283
MPI2520R0-3R3-R	3.3	1.6	1.6	190	228	1050
MPI2520R0-4R7-R	4.7	1.4	1.4	240	288	825
R1 - 1.2mm Height						
MPI2520R1-R47-R	0.47	4.5	4.8	20	24	2310
MPI2520R1-1R0-R	1.0	3.7	4.0	35	42	1925
MPI2520R1-1R5-R	1.5	2.9	3.1	55	66	1444
MPI2520R1-2R2-R	2.2	2.3	2.7	75	90	1255
MPI2520R1-3R3-R	3.3	1.8	2.4	105	126	962
MPI2520R1-4R7-R	4.7	1.6	1.9	150	180	825
MPI2520R1-5R6-R	5.0	1.5	1.5	200	240	679
MPI2520R1-6R8-R	6.8	1.3	1.3	300	360	679
MPI2520R1-100-R	10.0	1.1	1.2	390	460	525

1. Open Circuit inductance (OCL) Test Parameters: 1MHz, 0.1Vrms, 0.0Adc, 25°C
2. I<sub>rms</sub>: DC current for an approximate temperature rise of 40°C without core loss. Derating is necessary for 1°C currents. PCB layout, trace thickness and width, air-flow, and proximity of other heat generating components will affect the temperature rise. It is recommended that the temperature of the part not exceed 125°C under worst case operating conditions verified in the end application.
3. I<sub>sat</sub>: Peak current for approximately 70% rolloff at -25°C

4. K-factor: Used to determine B<sub>pp</sub> for core loss (see graph). B<sub>pp</sub> = K \* L \* ΔI / B<sub>pp</sub> (Gauss), K: (K-factor from table), L: (Inductance in μH), ΔI (Peak to peak ripple current in Amps).
5. Part Number Definition: MPI2520Rx-yyy-R
  - MPI2520Rx = Product code and size
  - yyy = Inductance value in μH, R = decimal point, if no R is present then third character = number of zeros.
  - "R" suffix = RoHS compliant


Discontinued. Effective inventory is depleted. Recommended replacement MPI25-V2

## Dimensions - mm




No marking



## Packaging information - mm







### Temperature rise vs. total loss






### Core loss



### Inductance characteristics



## Inductance characteristics



Discontinued, Effective September 15, 2016 or until inventory is depleted.  
Recommended replacement MPI25-V2

## Solder reflow profile




Table 1 - Standard SnPb Solder ( $T_c$ )

Package	Volume mm <sup>3</sup>	Volume mm <sup>3</sup>
Thickness	<350	≥350
<2.5mm	235°C	220°C
≥2.5mm	220°C	220°C

Table 2 - Lead (Pb) Free Solder ( $T_c$ )

Package	Volume mm <sup>3</sup>	Volume mm <sup>3</sup>	Volume mm <sup>3</sup>
Thickness	<350	350 - 2000	>2000
<1.6mm	260°C	260°C	260°C
1.6 - 2.5mm	260°C	250°C	245°C
>2.5mm	250°C	245°C	245°C

## Reference JDEC J-STD-020D

### Profile Feature

Preheat and Soak

- Temperature min. ( $T_{\text{min}}$ )
- Temperature max. ( $T_{\text{max}}$ )
- Time ( $T_{\text{min}}$  to  $T_{\text{max}}$ ) ( $t_s$ )

Average ramp up rate  $T_{\text{max}}$  to  $T_p$

Liquidus temperature ( $T_L$ )

Time at liquidus ( $t_L$ )

Peak package body temperature ( $T_p$ )\*

Time ( $t_p$ )\*\* within 5°C of the specified classification temperature ( $T_c$ )

Average ramp down rate ( $T_p$  to  $T_{\text{max}}$ )

Time 25°C to Peak Temperature

### Standard SnPb Solder

100°C

50°C

60-120 Seconds

3°C/ Second Max.

183°C

60-150 Seconds

Table 1

20 Seconds\*\*

6°C/ Second Max.

6 Minutes Max.

### Lead (Pb) Free Solder

150°C

200°C

60-120 Seconds

3°C/ Second Max.

217°C

60-150 Seconds

Table 2

30 Seconds\*\*

6°C/ Second Max.

8 Minutes Max.

\* Tolerance for peak profile temperature ( $T_p$ ) is defined as a supplier minimum and a user maximum.

\*\* Tolerance for time at peak profile temperature ( $t_p$ ) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.