

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

4X M3 THREAD
4X M3 螺纹孔

2X M6 NUT
2X M6 螺母

4X Ø6.5

58±0.5

101

103

146.2±0.3

166

0

STE

IP68

CE

118

103

82

48

35

32

4X R7

FOR EMC FEATURES,
CONDUCTIVE SURFACE

Panel Cut Out Dimension,Only for Reference
面板开口尺寸, 仅供参考

24AUG2016
DAVID WANG

24AUG2016
CHRIS WANG

24AUG2016
XIANG XU

108-137191

114-137191

-

CUSTOMER DRAWING

SCALE 1:1

SHEET 1 OF 1

REV B

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	24AUG2016	DW	CW
	B	ECR-20-016312	03JUN2021	BS	CW

NOTES:

I. TECHNICAL CHARACTERISTICS:
HOUSING MATERIAL: DIE CAST ALUMINIUM ALLOY
SURFACE : SEE TABLE
DEGREE OF PROTECTION: IP68 (MATED)

注释

I. 技术参数:
壳体材料: 铝合金
表面处理: 见表格
防护等级: IP68 (配合)

1471-9 (3/13)

printed on 8 Jun 2021 09:32 (China Standard Time) from TE236667

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±-

1 PLC ±-

2 PLC ±-

3 PLC ±-

4 PLC ±-

ANGLES ±-

FINISH -

MATERIAL

-

-

DWN 24AUG2016
DAVID WANG

CHK 24AUG2016
CHRIS WANG

APVD 24AUG2016
XIANG XU

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

TE Connectivity

H16BPR-AG-EMC-C

SIZE A2

CAGE CODE -

DRAWING NO. T193016XXXXX09

RESTRICTED TO

Downloaded from Arrow.com