# molex

Part Number: 464379321

Product Description: EXTreme Ten60Power Right-Angle Plug with Side Guides, 1 DC Power Circuit, 15 Signal Circuits, 1 DC Power Circuit,

Press Fit Tail

Series Number: 46437

**Status:** Active

**Product Category:** Board-to-Board

Connectors



#### **Documents & Resources**

#### **Drawings**

464379321\_sd.pdf 464371001-PK-000.pdf

#### 3D Models and Design Files

464379321\_stp.zip

#### **Specifications**

PS-46436-100-001.pdf 464361000-TS-000.pdf

## **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Compliant with Exemption 44; 34; 33
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant per EU 2015/863

## **Multiple Part Product Compliance Statements**

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

## **Part Details**

#### General

Status	Active
Category	Board-to-Board Connectors
Series	46437
Description	EXTreme Ten60Power Right-Angle Plug with Side Guides, 1 DC Power Circuit, 15 Signal Circuits, 1 DC Power Circuit, Press Fit Tail
Application	Board-to-Board, Power, Signal
Comments	See Product Specification for details
Component Type	PCB Header
Keyword	Ten60
Product Name	EXTreme Ten60Power
UPC	195842667549

## Agency

CSA	LR19980
UL	E29179

### **Electrical**

Current - Maximum per Contact	60.0A
Voltage - Maximum	600V AC / 250V DC

# Physical

Breakaway	No
Circuits (Loaded)	17
Circuits (maximum)	17

Color - Resin	Black
Durability (mating cycles max)	200
First Mate / Last Break	No
Flammability	94V-0
Glow-Wire Capable	No
Guide to Mating Part	Side, Yes
Keying to Mating Part	None
Lock to Mating Part	None
Mated Height	10.00mm
Material - Metal	High Conductivity Copper
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	Liquid Crystal Polymer
Net Weight	11.685/g
Number of Rows	1, 5
Orientation	Right Angle
Packaging Type	Tray
PC Tail Length	2.50mm, 3.28mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.58mm
Pitch - Mating Interface	2.00mm, 5.50mm
Plating min - Mating	0.762μm
Plating min - Termination	2.540µm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
(p)ower-(s)ignal Configuration	1p - 15s - 1p
Stackable	No
Temperature Range - Operating	-40° to +105°C
Termination Interface Style	Through Hole - Compliant Pin

# Mates With / Use With

## Mates with Part(s)

Description	Part Number
Description	I di civalibei

EXTreme Ten60Power Right-Angle Receptacle with Side Guides, 1 DC Power Circuit, 15 Signal Circuits, 1 DC Power Circuit, Press Fit Tail	<u>464369321</u>
EXTreme Ten60Power Vertical Receptacle with Side Guides, 1 DC Power Circuit, 15 Signal Circuits, 1 DC Power Circuit, Press Fit Tail	<u>465629321</u>

This document was generated on Mar 16, 2025