Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of MYPMA01218RCF-CAB from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=MYPMA01218RCF-CAB

MYPMA01218RCF-CAB

36V to 75V input voltage, 12V output voltage up to 10A, Buck Converter with 85degC Ta









Applications

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment,Industrial
	Equipment
	Please refer to Our Website and
	specifications, etc. for information about
Specific	the performance, functions, quality,
Applications	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



Features

Input voltage ranges from 36 to 75V
Fixed outputs voltage, 12V
Up to 10 Aof output current and 120w(216W peak)
Small package, 86.5 x 122.4 x 35.4mm
Light weight,160g
IP56 compliance
Vibration-proof case design
Current limit and short circuit protecton
Thermal protection



Appearance & Shape



1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of MYPMA01218RCF-CAB from the official website of Murata

MYPMA01218RCF-CAB



Specifications

lout(A)Max	10A
Vin(V)	36V to 75V
Vin(V)typ	48V
Vout(V)	12V
Vout(V)typ	12V
LineRegulation (%)	-5% to 5%
LoadRegulation (%)	-5% to 5%
Outputs (#)	1
Efficiency (%)	95%
Switching frequency (kHz)	102kHz
Size(mm)W	122.36mm
Size(mm)L	86.5mm
Size(mm)T	35.3mm
Operatingtemperature(degC)	-20°C to 85°C
Circuit topology	Buck(Step-down)
Package	Enclosed
Туре	Modules (integrated components)
Productseries	МҮРМА
Product Series Features	MYPAM series is non-isolated DC-DC converter for E- Bike/Scooter's auxiliary applications.
Brand	Murata

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

