

PKM22EPPH4001-B0

Note: This datasheet may be out of date.

Please download the latest datasheet of PKM22EPPH4001-B0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=PKM22EPPH4001-B0

In Production








Appearance & Shape





Tol.: ±0.5



Features

Externally driven piezoelectric sounders are used in digital watches, electronic calculators, telephones and other equipment. They are driven by a signal (ex.: 2048Hz or 4096Hz) from an LSI and provide melodious sound.

Features

- 1. Low power consumption
- 2. No noise and high reliability



Applications

Other Usage Consumer/Industrial



Packaging Information

Packaging		Standard Packing Quantity
-B0	Bulk	900

1 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





PKM22EPPH4001-B0

Note: This datasheet may be out of date.

Please download the latest datasheet of PKM22EPPH4001-B0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-sg/products/productdetail?partno=PKM22EPPH4001-B0



Specifications

Oscillation circuits	Not built-in	
Size	φ22.0×8.2 mm	
Frequency	4.0kHz	
Sound Pressure Level	87dB (typ.)	
Sound Pressure Level	75dB (min.)	
Measure Condition of Sound Pressure Level	[±1.5Vo-p,4.0kHz,square wave, 10cm]	
Capacitance	12nF	
Capacitance Tolerance	±30%	
Measurement Condition of Capacitance	[1kHz]	
Maximum input voltage	±15.0Vo-p max.	
Operating Temperature Range	-20°C to 70°C	
Storage Temperature Range	-30°C to 80°C	
Shape	Lead	
Lead Shape	Pin type	
Lead length	Lead length:6.5mm	
Drive Type	External Drive	
EIAJ Part Number	PS-RP2-C22-40	
Mass	2864mg	

2 of 3

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






PKM22EPPH4001-B0

Note: This datasheet may be out of date.

Please download the latest datasheet of PKM22EPPH4001-B0 from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en-sg/products/productdetail?partno=PKM22EPPH4001-B0





The following are examples of externally driven circuits.
(1) Unstable multi-vibrator using Tr.

- (2) Circuits using inverters or NAND gates.



Frequency Response

Recommended Circuit

3 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

