

Part Number: 151360606

Product Description: MicroClasp-to-MicroClasp Off-the-Shelf (OTS) Cable Assembly, Single Row, 600.00mm Length, 6 Circuits, White

Series Number: 15136

Status: Active

**Product Category:** Power and Signal Cable

**Assemblies** 



#### **Documents & Resources**

#### **Drawings**

151360606\_sd.pdf

3D Models and Design Files

151360606\_stp.zip

### **Product Environment Compliance**

### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | <b>©</b>  |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-<br>21            |
| REACH SVHC         | Not Contained per D(2024)6225-DC<br>(07 Nov 2024) |
| EU RoHS            | Compliant per EU 2015/863                         |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

## **Part Details**

## General

| Status                 | Active  |
|------------------------|---|
| Category               | Power and Signal Cable Assemblies   |
| Series                 | 15136   |
| Description            | MicroClasp-to-MicroClasp Off-the-<br>Shelf (OTS) Cable Assembly, Single<br>Row, 600.00mm Length, 6 Circuits,<br>White |
| Application            | Signal, Wire-to-Board   |
| Assembly Configuration | Dual Ended Connectors   |
| Connector to Connector | MicroClasp-to-MicroClasp  |
| Product Name           | MicroClasp  |
| Туре                   | Discrete Wire Assembly  |
| UPC                    | 191128149488  |

## Electrical

| Current - Maximum per Contact | 3.0A             |
|-------------------------------|------------------|
| Voltage - Maximum             | 250V AC (RMS)/DC |

# Physical

| Cable Length                   | 600.00mm        |
|--------------------------------|-----------------|
| Circuits (Loaded)              | 6               |
| Circuits (maximum)             | 6               |
| Color - Resin                  | White           |
| Gender                         | Female-Female   |
| Lock to Mating Part            | Yes             |
| Material - Metal               | Phosphor Bronze |
| Material - Plating Mating      | Tin             |
| Material - Plating Termination | Tin             |
| Material - Resin               | Nylon           |
| Net Weight                     | 16.590/g        |
| Number of Rows                 | 1               |

| Overmolded                  | No                   |
|-----------------------------|----------------------|
| Packaging Type              | Bag                  |
| Pitch - Mating Interface    | 2.00mm               |
| Plating min - Mating        | 0.889µm              |
| Plating min - Termination   | 0.914µm              |
| Single Ended                | No                   |
| Termination Interface Style | Crimp or Compression |
| Wire/Cable Type             | UL 1061              |
| Wire Insulation Diameter    | 1.28mm               |
| Wire Size (AWG)             | 22                   |

## Mates With / Use With

## Mates with Part(s)

| Description                                  | Part Number  |
|--|--------------|
| MicroClasp Vertical Single Row<br>Headers    | <u>55932</u> |
| MicroClasp Right-Angle Single Row<br>Headers | <u>55935</u> |

This document was generated on Mar 03, 2025