

HARD METRIC BACKPLANE CONNECTORS



✓ Active

TE CONNECTIVITY (TE)

2MM H.M. 8 ROW E VERT. RECEPT.

Z-PACK | Z-PACK 2mm HM

5646539-1

TE Internal Number: 5646539-1

EU RoHS Compliant EU ELV Compliant

Data Rate (Gb/s) ≤1

Number of Columns 25

Number of Rows 8

Number of Positions 200

Centerline (Pitch) (mm) 2



PRODUCT DRAWING

English



→ 3D PDF

DOCUMENTATION

Product Drawings

RECEPTACLE ASSEMBLY, VERTICAL, 200 POSN., TYPE E, 8 ROW, Z-PACK 2mm HM

PDF

English

CAD Files

3D PDF

PDF

3D

Customer View Model

2D_DXF.ZIP

English

Customer View Model 3D_IGS.ZIP **English Customer View Model** 3D_STP.ZIP **English Product Specifications Application Specification Z-PACK 2mm HM Interconnection System For Board-To-Board Connections** PDF **English Product Specification** Connector, Z-PACK, 8 Row, 2mm HM PDF **English** Product Environmental Compliance TE Material Declaration 2MM H.M. 8 ROW E VERT. RECEPT. **PDF English FEATURES** Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity. **Product Type Features PCB Mounting Orientation** Vertical Connector & Contact Terminates To Printed Circuit Board Shielded No **Connector Style** Receptacle **Connector Type** Connector Assembly Configuration Features Rows Loaded A, B, C, D, E, F, G, H Number of Columns 25 Number of Rows 8 **Number of Positions 200 Number of Signal Contacts** 200 Signal Characteristics Data Rate (Gb/s) ≤1 Crosstalk Version Standard

Contact Features

Contact Configuration ACTION PIN, Signal **Grounding Contact** Without Contact Mating Area Plating Material Performance Based Feedthrough Post Length (mm) 3.34 **Contact Base Material** Phosphor Bronze **Contact Style** Press-Fit **Contact Type** Socket **Termination Features Interface Type** 2mm HM Termination End Plating Material Tin over Nickel Mechanical Attachment Mating Alignment Type Multi-Purpose Center **Housing Features** Centerline (Pitch) (mm) 2 **Housing Color** Gray Housing Material Polyester - GF **Dimensions** Module Length (mm) 50 **Industry Standards UL Flammability Rating** UL 94V-0 **Packaging Features** Packaging Method Tube Packaging Quantity 10 **PRODUCT COMPLIANCE** Statement of Compliance **Statement of Compliance PDF**