

1133819

<https://www.phoenixcontact.com/us/products/1133819>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Battery module, VRLA-AGM, 48 V DC, 7 Ah

Commercial data

Item number	1133819
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CM30
Product key	CMUEV4
GTIN	4063151064877
Weight per piece (including packing)	14,200 g
Weight per piece (excluding packing)	13,600 g
Customs tariff number	85072080
Country of origin	DE

QUINT-HP-BAT/PB/48DC/7.0AH/PT - Battery module



1133819

<https://www.phoenixcontact.com/us/products/1133819>

Technical data

Notes

General

Note on the battery	For proper operation of the QUINT-HP-UPS/120AC/2.5KVA/PT (1136813) and QUINT-HP-UPS/230AC/2.5KVA/PT (1136815) uninterruptible power supplies, at least 2 QUINT-HP-BAT/PB/48DC/7.0AH/PT (1133819) battery modules are required. For longer buffer times, multiples of 2 battery modules must always be connected to the UPS (2, 4, 6, 8, or 10). A maximum of 10 batteries can be connected to a single UPS of this type. QUINT-HP-UPS/120AC/1.5KVA/PT (1136804) and QUINT-HP-UPS/230AC/1.5KVA/PT (1136811) can be supplied with individual battery modules (1-5 modules).
---------------------	---

Energy storage

Input

Input voltage	48 V DC (SELV)
Nominal capacity	7 Ah
Charging current	2.1 A
End-of-charge voltage	56 V DC (20 °C)

Output

Output current	40 A
Output fuse	max. 40 A

General

Connection in parallel	yes
	max. 5
Battery type	BB Battery BP7-12FR
Battery technology	VRLA-AGM
IQ-Technology	yes
Latest startup date (battery only)	12 Months (0 °C ... 20 °C)
Latest startup (battery only) - range	9 Months ... 12 Months (20 °C ... 30 °C)
	6 Months ... 9 Months (30 °C ... 40 °C)
Accumulator module service life (according to Eurobat)	6 (20 °C)
Size designation	Block
Suitable for fast charging	yes
Temperature sensor	yes

Product properties

Product type	Battery module
Product family	Battery module

Data management status

QUINT-HP-BAT/PB/48DC/7.0AH/PT - Battery module



1133819

<https://www.phoenixcontact.com/us/products/1133819>

Article revision	01
------------------	----

Insulation characteristics

Protection class	III
Degree of pollution	2

Dimensions

Item dimensions

Width	156.5 mm
Height	354 mm
Depth	143 mm

Drill hole

Diameter	5.5 mm
----------	--------

Installation dimensions

Installation distance right/left	0 mm / 0 mm
Installation distance top/bottom	20 mm / 20 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (storage/transport)	-20 °C ... 40 °C
Ambient temperature (charge)	0 °C ... 40 °C
Ambient temperature (discharge)	-20 °C ... 50 °C
Max. permissible relative humidity (operation)	≤ 95 %

Ex data

Suited for EX-applications	no
----------------------------	----

QUINT-HP-BAT/PB/48DC/7.0AH/PT - Battery module




1133819

https://www.phoenixcontact.com/us/products/1133819


Drawings

Graphic



Buffer times for QUINT HP UPS 1.5 kVA

Graphic



Buffer times for QUINT HP UPS 2.5 kVA

QUINT-HP-BAT/PB/48DC/7.0AH/PT - Battery module



1133819

<https://www.phoenixcontact.com/us/products/1133819>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1133819>



IECEE CB Scheme
Approval ID: DK-134725-A1-UL



cULus Listed
Approval ID: E123528-20220920



cULus Listed
Approval ID: E199827-20221028

QUINT-HP-BAT/PB/48DC/7.0AH/PT - Battery module



1133819

<https://www.phoenixcontact.com/us/products/1133819>

Classifications

ECLASS

ECLASS-13.0	27050403
ECLASS-11.0	27050403

ETIM

ETIM 9.0	EC000357
----------	----------

QUINT-HP-BAT/PB/48DC/7.0AH/PT - Battery module



1133819
<https://www.phoenixcontact.com/us/products/1133819>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com