

Part Number: 2032634985

**Product Description :** Sentrality 8.00mm Screw Mount Pin, 66.50mm Engagement Length, Bag

Series Number: 203263

**Status**: Active

**Product Category:** PCB Headers and Receptacles



#### **Documents & Resources**

## **Drawings**

2032634985 sd.pdf

2032630006-PK-000.pdf

**3D Models and Design Files** 

STEP AP242

**SOLIDWORKS** 

Creo

Symbol and Footprint (Multi-Format)

### **Specifications**

2043130001-PS-000.pdf

2043130008-TS-000.pdf

2043131234-TS-000.pdf

# **Product Environment Compliance**

## Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | ⊚<br>per SJ/T 11365-2006                          |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                    |
| REACH SVHC         | Not Contained per D(2023)8585-DC<br>(23 Jan 2024) |
| EU RoHS            | Compliant per EU 2015/863                         |

### **Compliance Statements**

- EU RoHS
- REACH SVHC
- Low-Halogen

## **Industry Documents**

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# <u>Substances of Interest</u>

PFAS

## **EU RoHS Certificate of Compliance**

## Additional Product Compliance Information

### **Part Details**

#### **General**

| Status         | Active  |
|----------------|---|
| Category       | PCB Headers and Receptacles   |
| Series         | 203263  |
| Description    | Sentrality 8.00mm Screw Mount<br>Pin, 66.50mm Engagement Length,<br>Bag |
| Application    | Board-to-Board, Busbar-to-Board,<br>Busbar-to-Busbar, Power             |
| Component Type | PCB Header  |
| Product Name   | Sentrality  |
| UPC            | 191130136384  |

#### **Electrical**

| Current - Maximum per Contact | 200.0A |
|-------------------------------|--------|
| Voltage - Maximum             | 600V   |

# **Physical**

| Breakaway          | No     |
|--------------------|--------|
| Circuits (Loaded)  | 1      |
| Circuits (maximum) | 1      |
| Diameter           | 8.00mm |

| Durability (mating cycles max) | 200            |
|--------------------------------|----------------|
| First Mate / Last Break        | No             |
| Glow-Wire Capable              | No             |
| Guide to Mating Part           | No             |
| Height Above Board             | 66.50mm        |
| Material - Metal               | Copper Alloy   |
| Material - Plating Mating      | Silver         |
| Material - Plating Termination | Silver         |
| Net Weight                     | 11.645/g       |
| Number of Rows                 | 1              |
| Orientation                    | Vertical       |
| Packaging Type                 | Bag            |
| PCB Retention                  | None           |
| Pitch - Mating Interface       | N/A            |
| Polarized to Mating Part       | No             |
| Polarized to PCB               | No             |
| Temperature Range - Operating  | -40° to +125°C |
| Termination Interface Style    | Screw Mount    |

# Mates With / Use With

# Mates with Part(s)

| Description   | Part Number   |
|---|---------------|
| Sentrality Top-entry Surface Mount<br>Socket Assemblies   | <u>204318</u> |
| Sentrality Top-entry Surface Mount<br>Socket Assemblies with Self-<br>alignment Capability      | <u>204365</u> |
| Sentrality Top-entry Knurled Press-<br>Fit Socket Assemblies with Self-<br>alignment Capability | <u>204313</u> |
| Sentrality Top-entry Knurled Press-<br>Fit Socket Assemblies                                    | <u>204316</u> |
| Sentrality 3.40mm Right-Angle<br>Socket Assemblies  | <u>205000</u> |