



LS4M2D



Order Lever Separately

Series HDLS Plug-in: Side Rotary; 2NC 2NO DPDT Center Neutral; 20 mm

Actual product appearance may vary.

Features

- Wide variety of operating heads
- Field adjustable operating modes, for reduced inventory
- Convenience of on-the-spot adjustment instructions
- Complete choice of circuitry and electrical rating options
- Plug-in and non plug-in versions have identical operating characteristics and are dimensionally interchangeable
- Manifold (rear-wire) version
- Explosion-proof versions
- Low temperature versions to -40° C (-40° F)
- Captive head and body screws
- Designed to withstand seismic shock
- Stainless steel (NEMA 4X) versions
- Pre-leaded cable or pre-wired connector types
- Epoxy filled wash down (NEMA 6P) types
- Completely fluorocarbon (FC) sealed versions

Potential Applications

- Machine Tools
- Material Handling
- Packaging
- Presses
- Pulp and Paper
- Welding
- PLC Interface

Description

Sensing and Control offers the world's most advanced line of MICRO SWITCH™ heavy-duty limit switches. These switches include boss -and-socket head design for secure head -to-body retention, unique all-metal drive train for consistent operating characteristics even at high temperature (lasts longer without the need for frequent adjustment than drive trains with plastic parts,) self -lifting pressure plate terminals save wiring time, easily identified grounding terminal (inside) for compliance with OSHA and other regulatory agency standards, one piece flat gasket (seals better than gaskets that go around curves and corners, does not contact terminal pins to reduce chances of fluid migration,) front mounting and interchangeability of single- and double-pole switches, plug-in and non plug-in with one another and with other switch brands, tracking interchangeability of actuator levers for single- and double-pole switches, plug-in and non plug-in, twin shaft seals for an extra measure of protection, inner FC O-ring seal, outer Buna-N seal (all FC available,) FC shaft and diaphragm seals on side rotary switches, rugged corrosion-resistant zinc head and body are phosphate treated and epoxy finished, exclusive teller tab assures proper torque (when it cannot be moved the lever is tight enough to prevent slippage) and domestic and international conduit taps.

Supporting Documentation

- Installation Instructions
- Lever - Required Accessory

| Product Specifications         |                                                                                       |
|--------------------------------|---------------------------------------------------------------------------------------|
| Availability                   | Global                                                                                |
| Operating Force (O.F.)         | 0,45 N m max. [4 in lb max.]                                                          |
| Pretravel (P.T.)               | 18° max.                                                                              |
| Overtravel (O.T.)              | 57° min.                                                                              |
| Differential Travel (D.T.)     | 10° max.                                                                              |
| Product Type                   | MICRO SWITCH™ Heavy - Duty Limit Switches                                             |
| Actuator                       | Side Rotary                                                                           |
| Lever Style                    | Lever Not Included - Reference Lever Required Accessory                               |
| Circuitry                      | 2NC 2NO Double - Pole Double - Throw, Center - Neutral, Snap - Action, Double - Break |
| Ampere Rating                  | 10 A (Thermal)                                                                        |
| Supply Voltage                 | 600 Vac and 250 Vdc max.                                                              |
| Housing Material               | Zinc Die - Cast                                                                       |
| Termination Type               | 20 mm                                                                                 |
| Housing Type                   | HDLS Plug - in                                                                        |
| Series Name                    | HDLS                                                                                  |
| Sealing                        | NEMA 1, 3, 4, 4X, 6, 6P, 12, 13                                                       |
| Approvals                      | UL listed, CSA Certified, CE Certified, CCC Certified                                 |
| CSA File #                     | LR57326/Master Contract 152457                                                        |
| UL File #                      | E37138                                                                                |
| Operating Temperature Range    | -1 °C to 121 ° C [30 °F to 250 °F]                                                    |
| Comment                        | SPDT - DB each direction (Pole 1 operates CCW / Pole 2 operates CW)                   |
| Agency Approvals and Standards | EN60947 -1, EN60947 -5-1                                                              |
| UNSPSC Code                    | 302119                                                                                |
| UNSPSC Commodity               | 302119 Switches and controls and relays                                               |
| Sealed                         | Industrial                                                                            |

My Links

- Login to iCOM
- Login as Rep/AD
- Login as Guest
- Login to Digital University

Keyword Search

Search for product and support information.

All Sensing and Contr▼

Product Search

Part number search:

Use (\*) to expand search

Specification Search