DCM™ DC-DC Converter
DCM4623TB0G31E0M00



Isolated, Regulated DC Converter

Features & Benefits

- Isolated, regulated DC-DC converter
- Up to 500W, 17.90A continuous
- 93.3% peak efficiency
- 1093W/in^3 power density
- Wide input range 110 – 200V_{DC}
- Safety Extra Low Voltage (SELV) 28.0V nominal output
- 4242V_{DC} isolation
- ZVS high-frequency switching
  - Enables low-profile, high-density filtering
- Optimized for array operation
  - Up to 8 units – 4000W
  - No power de-rating needed
  - Sharing strategy permits dissimilar line voltages across an array
- Fully operational current limit
- OV, OC, UV, short circuit and thermal shut down

Typical Applications

- Industrial
- Process Control
- Transportation / Heavy Equipment
- Defense / Aerospace

Product Ratings	
V_{IN} = 110 – 200V	P_{OUT} = 500W
V_{OUT} = 28.0V (16.8 – 30.8V Trim)	I_{OUT} = 17.90A

Product Description

The DCM Isolated, Regulated DC Converter is a DC-DC converter, operating from an unregulated, wide-range input to generate an isolated 28.0V_{DC} output. With its high-frequency zero-voltage switching (ZVS) topology, the DCM converter consistently delivers high efficiency across the input line range. Modular DCM converters and downstream DC-DC products support efficient power distribution, providing superior power system performance and connectivity from a variety of unregulated power sources to the point-of-load.

Leveraging the thermal and density benefits of Vicor ChiP™ packaging technology, the DCM module offers flexible thermal management options with very low top and bottom side thermal impedances. Thermally-adept ChiP-based power components enable customers to achieve cost effective power system solutions with previously unattainable system size, weight and efficiency attributes, quickly and predictably.


Package Information

- Through-hole ChiP package
  - 1.886 x 0.898 x 0.284in [47.91 x 22.80 x 7.21mm]
  - Weight: 29.2g [1.03oz]


Note: Product images may not highlight current product markings and cosmetic features.

Downloaded from Arrow.com.

Typical Applications




Typical application 1: DCM4623TB0G31E0M00 in an array of four units



Typical application 2: single DCM4623TB0G31E0M00, to a non-isolated regulator, and direct to load

Downloaded from Arrow.com.


Typical Applications (Cont.)



Typical application 3: parallel operation of DCMs with common-mode chokes installed on the input side to suppress common-mode noise

Downloaded from Arrow.com.

Pin Configuration



Pin Descriptions

Pin Number	Signal Name	Type	Function
A1	+IN	INPUT POWER	Positive input power terminal
B1	TR	INPUT	Enables and disables trim functionality; adjusts output voltage when trim active
C1	EN	INPUT	Enables and disables power supply
D1	FT	OUTPUT	Fault monitoring
E1	–IN	INPUT POWER RETURN	Negative input power terminal
A'2, C'2	+OUT	OUTPUT POWER	Positive output power terminal
B'2, D'2	–OUT	OUTPUT POWER RETURN	Negative output power terminal

Downloaded from Arrow.com.

Part Ordering Information

Part Number	Temperature Grade	Option	Tray Size
DCM4623TB0G31**M00**	**M** = –55 to 125°C	**00** = Analog Control Interface Version	20 parts per tray

Storage and Handling Information

Note: For compressive loading refer to Application Note AN:036, "Recommendations for Maximum Compressive Force of Heat Sinks."
For handling and assembly processing refer to Application Note AN:031, "Through-Hole ChiP™ Package Soldering Guidelines."

Parameter	Comments	Specification
Storage Temperature Range		–65 to 125°C
Operating Internal Temperature Range (T_{INT})		–55 to 125°C
Peak Temperature Top Case (Soldering) [a]	For further information, please contact factory applications	135°C
Lead Finish	Nickel	0.51 – 2.03µm
	Palladium	0.02 – 0.15µm
	Gold	0.003 – 0.051µm
Weight		29.2g [1.03oz]
MSL Rating	Not applicable to through-hole ChiP products	N/A
ESD Rating	Method per Human Body Model (HBM) Test ESDA / JEDEC JDS-001-2012	Class 1C
	Charged Device Model (CDM) JESD22-C101E	Class 2

[a] Product is not intended for reflow solder attach.

Safety, Reliability and Agency Approvals

Parameter	Comments	Min	Typ	Max	Unit
Dielectric Withstand Test	IN to OUT	**4242**			V_{DC}
	IN to CASE	**2121**			V_{DC}
	OUT to CASE	**2121**			V_{DC}
Insulation Resistance	IN to OUT, IN to CASE, OUT to CASE at 500V_{DC}, 1 minute	10			MΩ
MTBF	MIL-HDBK-217 FN2 Parts Count 25°C Ground Benign, Stationary, Indoors / Computer		1.85		MHrs
	Telcordia Issue 2, Method I Case 3, 25°C, 100% D.C., GB, GC		3.68		
Agency Approvals/Standards					

Downloaded from Arrow.com.

Absolute Maximum Ratings

The absolute maximum ratings below are stress ratings only. Operation at or beyond these maximum ratings can cause permanent damage to the device. Electrical specifications do not apply when operating beyond rated operating conditions.

Parameter	Comments	Min	Max	Unit
Input Voltage (+IN to –IN)		-0.5	224.0	V
Input Voltage Slew Rate		-1	1	V/µs
TR to –IN		-0.3	3.5	V
EN to –IN		-0.3	3.5	V
FT to –IN		-0.3	3.5	V
			5	mA
Output Voltage (+OUT to –OUT)		-0.5	40	V
Dielectric Withstand (Input to Output)	Reinforced insulation	4242		V_{DC}
Average Output Current			25.0	A

Downloaded from Arrow.com.

Electrical Specifications

Specifications apply over all line, trim and load conditions, internal temperature T_{INT} = 25°C, unless otherwise noted. **Boldface** specifications apply over the temperature range of –55°C < T_{INT} < 125°C.

Attribute	Symbol	Conditions / Notes	Min	Typ	Max	Unit
Power Input Specifications						
Input Voltage Range	V_{IN}	Continuous operation	**110**	**135**	**200**	V
Inrush Current (Peak)	I_{INRP}	With maximum $C_{OUT-EXT}$, full resistive load			**5.5**	A
Input Capacitance (Internal)	C_{IN-INT}	Effective value at nominal input voltage		0.8		µF
Input Capacitance (Internal) ESR	$R_{CIN-INT}$	At 1MHz		2.50		mΩ
Input Inductance (External)	L_{IN}	Differential mode, with no further line bypassing			**5**	µH
No-Load Specifications						
Input Power – Disabled	P_Q	Nominal line, see Figure 6		1.0	1.3	W
		Worst case line, see Figure 6			**1.5**	
Input Power – Enabled with No Load	P_{NL}	Nominal line, see Figure 7		6.0	9.0	W
		Worst case line, see Figure 7			**11**	

Downloaded from Arrow.com.

Electrical Specifications (Cont.)

Specifications apply over all line, trim and load conditions, internal temperature T_{INT} = 25°C, unless otherwise noted. **Boldface** specifications apply over the temperature range of –55°C < T_{INT} < 125°C.

Attribute	Symbol	Conditions / Notes	Min	Typ	Max	Unit
Power Output Specifications						
Output Voltage Set Point	$V_{OUT-NOM}$	V_{IN} = 135V, nominal trim, at 100% load, T_{INT} = 25°C	27.9	28.0	28.1	V
Rated Output Voltage Trim Range	$V_{OUT-TRIMMING}$	Trim range over temp at full load. Specifies the low, nominal and high trim conditions.	**16.8**	**28.0**	**30.8**	V
Output Voltage Load Regulation	$\Delta V_{OUT-LOAD}$	Linear load line. Output voltage increase from full rated load current to no load (does not include light-load regulation). See Figure 9 and Design Guidelines section	1.3	1.5	1.6	V
Output Voltage Light Load Regulation	ΔV_{OUT-LL}	0 – 10% load, additional V_{OUT} relative to calculated load-line point. See Figure 9 and Design Guidelines section.	**0.0**		**4.9**	V
Output Voltage Temperature Coefficient	$\Delta V_{OUT-TEMP}$	Nominal, linear temperature coefficient, relative to T_{INT} = 25°C. See Figure 8 and Design Guidelines Section.		**-3.73**		mV / °C
Output Voltage Accuracy	$\%V_{OUT-ACCURACY}$	The total output voltage set-point accuracy from the calculated ideal V_{OUT} based on load, temp and trim. Excludes ΔV_{OUT-LL}	**-5.0**		**5.0**	%
Rated Output Power	P_{OUT}	Continuous, $V_{OUT} \geq$ 28.0V	**500**			W
Rated Output Current	I_{OUT}	Continuous, $V_{OUT} \leq$ 28.0V	**17.9**			A
Output Current Limit	$I_{OUT-LIM}$	% of rated I_{OUT} max. Fully operational current limit, for nominal trim and below.	100	120	140	%
Current Limit Delay	$t_{IOUT-LIM}$	The module will power limit in a fast transient event.		1		ms
Efficiency	η	Full load, nominal line, nominal trim	92.3	93.3		%
		Full load, over line and temperature, nominal trim	**89.0**			
		50% load, over rated line, temperature and trim	**90.0**			
Output Voltage Ripple	V_{OUT-PP}	20MHz bandwidth. At nominal trim, minimum $C_{OUT-EXT}$ and at least 10% rated load		78		mV

Downloaded from Arrow.com.

Electrical Specifications (Cont.)

Specifications apply over all line, trim and load conditions, internal temperature T_{INT} = 25°C, unless otherwise noted. **Boldface** specifications apply over the temperature range of –55°C < T_{INT} < 125°C.

Attribute	Symbol	Conditions / Notes	Min	Typ	Max	Unit
Power Output Specifications (Cont.)						
Output Capacitance (Internal)	$C_{OUT-INT}$	Effective value at nominal output voltage		33		µF
Output Capacitance ESR (Internal)	$R_{COUT-INT}$	At 1MHz		0.069		mΩ
Output Capacitance (External)	$C_{OUT-EXT}$	For load transients that remain >10% rated load; excludes component temperature coefficient	**200**		**2000**	µF
	$C_{OUT-EXT-TRANS}$	For load transients down to 0% rated load, with static trim; excludes component temperature coefficient	**200**		**2000**	µF
	$C_{OUT-EXT-TRANS-TRIM}$	For load transients down to 0% rated load, with dynamic trimming; excludes component temperature coefficient	**470**		**2000**	µF
Output Capacitance ESR (External)	$R_{COUT-EXT}$	At 10kHz, excludes component tolerances	**10**			mΩ
Initialization Delay	t_{INIT}	See state diagram		25	**40**	ms
Output Turn-On Delay	t_{ON}	From rising edge EN, with V_{IN} pre-applied; see timing diagram		200		µs
Output Turn-Off Delay	t_{OFF}	From falling edge EN; see timing diagram			**600**	µs
Soft-Start Ramp Time	t_{SS}	At full rated resistive load. Typical spec is 1-up with minimum $C_{OUT-EXT}$. Max spec is for arrays with max $C_{OUT-EXT}$		32	**200**	ms
Output Voltage Threshold for Max Rated Load Current	$V_{OUT-FL-THRESH}$	During start up, V_{OUT} must achieve this threshold before output can support full rated current			**14.0**	V
Output Current at Start Up	$I_{OUT-START}$	Max load current at start up while V_{OUT} is below V_{OUT-FL_THRESH}	**1.79**			A
Monotonic Soft-Start Threshold Voltage	$V_{OUT-MONOTONIC}$	Output voltage rise becomes monotonic with 10% of preload once it crosses $V_{OUT-MONOTONIC}$			**14.0**	V
Minimum Required Disabled Duration	$t_{OFF-MIN}$	This refers to the minimum time a module needs to be in the disabled state before it will attempt to start via EN			**2**	ms
Minimum Required Disabled Duration for Predictable Restart	$t_{OFF-MONOTONIC}$	This refers to the minimum time a module needs to be in the disabled state before it is guaranteed to exhibit monotonic soft-start and have predictable start-up timing			**100**	ms
Voltage Deviation (Transient)	$\%V_{OUT-TRANS}$	Minimum C_{OUT_EXT} (10 ↔ 90% load step), excluding load line		<10		%
Settling Time	t_{SETTLE}			10.0		ms

Downloaded from Arrow.com.

Electrical Specifications (Cont.)

Specifications apply over all line, trim and load conditions, internal temperature T_{INT} = 25°C, unless otherwise noted. **Boldface** specifications apply over the temperature range of –55°C < T_{INT} < 125°C.

Attribute	Symbol	Conditions / Notes	Min	Typ	Max	Unit
Powertrain Protections						
Input Voltage Initialization Threshold	$V_{IN-INIT}$	Threshold to start t_{INIT} delay			**75**	V
Input Voltage Reset Threshold	$V_{IN-RESET}$	Latching faults will clear once V_{IN} falls below $V_{IN-RESET}$	**50**			V
Input Undervoltage Lockout Threshold	$V_{IN-UVLO-}$		**66.00**		**100.00**	V
Input Undervoltage Recovery Threshold	$V_{IN-UVLO+}$	See timing diagram			**110.00**	V
Input Overvoltage Lockout Threshold	$V_{IN-OVLO+}$				**220**	V
Input Overvoltage Recovery Threshold	$V_{IN-OVLO-}$	See timing diagram	**200**			V
Output Overvoltage Threshold	$V_{OUT-OVP}$	From 25 to 100% load; latched shut down	**35.42**			V
	$V_{OUT-OVP-LL}$	From 0 to 25% load; latched shut down	**36.96**			V
Minimum Current Limited V_{OUT}	$V_{OUT-UVP}$	Over all operating steady-state line and trim conditions			**12.60**	V
Overtemperature Threshold (Internal)	$T_{INT-OTP}$		**125**			°C
Power Limit	P_{LIM}				**620**	W
Input Voltage Overvoltage to Cessation of Powertrain Switching	$t_{OVLO-SW}$	Independent of fault logic		1.0		µs
Input Voltage Overvoltage Response Time	t_{OVLO}	For fault logic only			**200**	µs
Input Voltage Undervoltage Response Time	t_{UVLO}				**100**	ms
Short Circuit Response Time	t_{SC}	Powertrain on, operational state			**200**	µs
Short Circuit, or Temperature Fault Recovery Time	t_{FAULT}	See timing diagram		1		s

Downloaded from Arrow.com.

Electrical Specifications (Cont.)

Specifications apply over all line, trim and load conditions, internal temperature T_{INT} = 25°C, unless otherwise noted. **Boldface** specifications apply over the temperature range of –55°C < T_{INT} < 125°C.

Attribute	Symbol	Conditions / Notes	Min	Typ	Max	Unit
Trim: TR						
TR Trim Disable Threshold	$V_{TRIM-DIS-TH}$	Trim disabled when TR above this threshold at power up			**3.20**	V
TR Trim Enable Threshold	$V_{TRIM-EN-TH}$	Trim enabled when TR below this threshold at power up	**3.15**			V
Internally Generated V_{CC}	V_{CC}		**3.21**	3.30	**3.39**	V
TR Pin Functional Range	$V_{TRIM-EN}$		0.00	2.44	3.16	V
V_{OUT} Referred TR Pin Resolution	$V_{OUT-RES}$	With V_{CC} = 3.3V		40		mV
TR Internal Pull-Up Resistance to V_{CC}	$R_{TRIM-INT}$		**9.9**	10.0	**10.1**	kΩ
Enable: EN						
EN Enable Threshold	$V_{ENABLE-EN-TH}$				**2.31**	V
EN Disable Threshold	$V_{ENABLE-DIS-TH}$		**0.99**			V
Internally Generated V_{CC}	V_{CC}		**3.21**	3.30	**3.39**	V
EN internal Pull-Up Resistance to V_{CC}	$R_{ENABLE-INT}$		**9.9**	10.0	**10.1**	kΩ
Fault: FT						
FT Internal Pull-Up Resistance to V_{CC}	$R_{FAULT-INT}$		**494**	499	**504**	kΩ
FT Voltage	$V_{FAULT-ACTIVE}$	At rated current drive capability	**3.0**			V
FT Current Drive Capability	$I_{FAULT-ACTIVE}$	Overload beyond the ABSOLUTE MAXIMUM ratings may cause module damage	**4**			mA
FT Response Time	$t_{FT-ACTIVE}$	Delay from cessation of switching to FT Pin Active			**200**	µs




Figure 1 — *Electrical specified operating area (does not include light-load boosting)*

Downloaded from Arrow.com.

Thermal Specified Operating Area




Figure 2 — *Thermal specified operating area; max output power vs. case temp, single unit at minimum full-load efficiency; bottom and leads at temperature*




Figure 3 — *Thermal specified operating area; max output power vs. case temp, single unit at minimum full-load efficiency; top, bottom and leads at temperature*




Figure 4 — *Thermal specified operating area; max output power vs. case temp, single unit at minimum full-load efficiency; top and leads at temperature*





Figure 5 — *Thermal specified operating area; max output power vs. case temp, single unit at minimum full-load efficiency; top only at temperature*

Downloaded from Arrow.com.

High-Level Functional State Diagram


Conditions that cause state transitions are shown along arrows. Sub-sequence activities listed inside the state bubbles.



Downloaded from Arrow.com.

Timing Diagrams


Module inputs are shown in blue; module outputs are shown in brown.



Downloaded from Arrow.com.

Timing Diagrams (Cont.)

Module inputs are shown in blue; module outputs are shown in brown.



Downloaded from Arrow.com.

Typical Performance Characteristics

The following figures present typical performance at T_C = 25°C, unless otherwise noted. See associated figures for general trend data.




Figure 6 — *Disabled power dissipation vs. V_{IN}*




Figure 7 — *No-load power dissipation vs. V_{IN}, at nominal trim*




Figure 8 — *Ideal V_{OUT} vs. case temperature, at full load*




Figure 9 — *Ideal V_{OUT} vs. load current, at 25°C case*




Figure 10 — *Effective internal input capacitance vs. applied voltage*

Downloaded from Arrow.com.

Typical Performance Characteristics (Cont.)

The following figures present typical performance at T_C = 25°C, unless otherwise noted. See associated figures for general trend data.




Figure 11 — *Full-load efficiency vs. V_{IN}, at low trim*




Figure 12 — *Full-load efficiency vs. V_{IN}, at nominal trim*




Figure 13 — *Full-load efficiency vs. V_{IN}, at high trim*

Downloaded from Arrow.com.

Typical Performance Characteristics (Cont.)

The following figures present typical performance at T_C = 25°C, unless otherwise noted. See associated figures for general trend data.




Figure 14 — *Efficiency vs. load at T_{CASE} = -55°C, nominal trim*




Figure 15 — *Power dissipation vs. load at T_{CASE} = -55°C, nominal trim*




Figure 16 — *Efficiency vs. load at T_{CASE} = 25°C, nominal trim*




Figure 17 — *Power dissipation vs. load at T_{CASE} = 25°C, nominal trim*




Figure 18 — *Efficiency vs. load at T_{CASE} = 100°C, nominal trim*




Figure 19 — *Power dissipation vs. load at T_{CASE} = 100°C, nominal trim*

Downloaded from Arrow.com.

Pin Functions

+IN, –IN

Input power pins. –IN is the reference for all control pins, and therefore a Kelvin connection for the control signals is recommended as close as possible to the pin on the package, to reduce effects of voltage drop due to –IN currents.

+OUT, –OUT

Output power pins.

EN (Enable)

This pin enables and disables the DCM converter; when held low the unit will be disabled. It is referenced to the –IN pin of the converter. The EN pin has an internal pull-up to V_{CC} through a 10kΩ resistor.

- Output enable: When EN is allowed to pull up above the enable threshold, $V_{ENABLE-EN-TH}$, the module will be enabled. If leaving EN floating, it is pulled up to V_{CC} and the module will be enabled.
- Output disable: EN may be pulled down externally below $V_{ENABLE-DIS-TH}$ in order to disable the module.
- EN is an input only, it does not pull low in the event of a fault.
- The EN pins of multiple units should be driven high concurrently to permit the array to start in to maximum rated load. However, the direct interconnection of multiple EN pins requires additional considerations, as discussed in the section on Array Operation.

TR (Trim)

The TR pin is used to select the trim mode and to trim the output voltage of the DCM converter. The TR pin has an internal pull-up to V_{CC} through a 10.0kΩ resistor.

The DCM will latch trim behavior at application of V_{IN} (once V_{IN} exceeds $V_{IN-UVLO+}$), and persist in that same behavior until loss of input voltage

- At application of V_{IN}, if TR is sampled at above $V_{TRIM-DIS-TH}$, the module will latch in a non-trim mode, and will ignore the TR input for as long as V_{IN} is present.
- At application of V_{IN}, if TR is sampled at below $V_{TRIM-EN-TH}$, the TR will serve as an input to control the real-time output voltage, relative to full load, 25°C. It will persist in this behavior until V_{IN} is no longer present.

If trim is active when the DCM is operating, the TR pin provides dynamic trim control at a typical 30Hz of –3dB bandwidth over the output voltage. TR also decreases the current limit threshold when trimming above $V_{OUT-NOM}$.

FT (Fault)

The FT pin provides a Fault signal.

Any time the module is enabled and has not recognized a fault, the FT pin is inactive. FT has an internal 499kΩ pull-up to V_{CC}, therefore a shunt resistor, R_{SHUNT}, of approximately 50kΩ can be used to ensure the LED is completely off when there is no fault, per the diagram below.


Whenever the powertrain stops (due to a fault protection or disabling the module by pulling EN low), the FT pin becomes active and provides current to drive an external circuit.

When active, FT pin drives to V_{CC}, with up to 4mA of external loading. Module may be damaged from an overcurrent FT drive, thus a resistor in series for current limiting is recommended.

The FT pin becomes active momentarily when the module starts up.

During the output voltage soft-start ramp, the FT pin output toggles.

Typical External Circuits for Signal Pins (TR, EN, FT)



Downloaded from Arrow.com.

Design Guidelines

Building Blocks and System Design

The DCM converter input accepts the full 110 – 200V range, and it generates an isolated trimmable 28.0V_{DC} output. Multiple DCMs may be paralleled for higher power capacity via wireless load sharing, even when they are operating off of different input voltage supplies.

The DCM converter provides a regulated output voltage around defined nominal load line and temperature coefficients. The load line and temperature coefficients enable configuration of an array of DCM converters which manage the output load with no share bus among modules. Downstream regulators may be used to provide tighter voltage regulation, if required.

The DCM4623TB0G31E0M00 may be used in standalone applications where the output power requirements are up to 500W. However, it is easily deployed as arrays of modules to increase power handling capacity. Arrays of up to eight units have been qualified for 4000W capacity. Application of DCM converters in an array requires no de-rating of the maximum available power versus what is specified for a single module.

Note: For more information on operation of single DCM, refer to "Single DCM as an Isolated, Regulated DC-DC Converter" application note AN:029. For more information on designing a power system using the DCMs, refer to the DCM Design Guide.

Soft Start

When the DCM starts, it will go through a soft start. The soft-start routine ramps the output voltage by modulating the internal error amplifier reference. This causes the output voltage to approximate a piecewise linear ramp. The output ramp finishes when the voltage reaches either the nominal output voltage, or the trimmed output voltage in cases where trim mode is active.

During soft start, the maximum load current capability is reduced. Until V_{OUT} achieves at least $V_{OUT\text{-}FL\text{-}THRESH}$, the output current must be less than $I_{OUT\text{-}START}$ in order to guarantee start up. Note that this is current available to the load, above that which is required to charge the output capacitor.

Nominal Output Voltage Load Line

Throughout this document, the programmed output voltage, (either the specified nominal output voltage if trim is inactive or the trimmed output voltage if trim is active), is specified at full load and at room temperature. The actual output voltage of the DCM is given by the programmed trimmed output voltage, with modification based on load and temperature. The nominal output voltage is 28.0V, and the actual output voltage will match this at full load and room temperature with trim inactive.

The largest modification to the actual output voltage compared to the programmed output is due to the 5.263% $V_{OUT\text{-}NOM}$ load line, which for this model corresponds to $\Delta V_{OUT\text{-}LOAD}$ of 1.4736V. As the load is reduced, the internal error amplifier reference, and by extension the output voltage, rises in response. This load line is the primary enabler of the wireless current sharing among an array of DCMs.

The load line impact on the output voltage is absolute, and does not scale with programmed trim voltage.

For a given programmed output voltage, the actual output voltage versus load current at nominal trim and room temperature is given by the following equation:

$$V_{OUT}\ at\ 25ºC = 28.0 + 1.4736 \bullet (1 - I_{OUT} / 17.90) \qquad (1)$$

Nominal Output Voltage Temperature Coefficient

A second additive term to the programmed output voltage is based on the temperature of the module. This term permits improved thermal balancing among modules in an array, especially when the factory nominal trim point is utilized (trim mode inactive). This term is much smaller than the load line described above, representing only a -3.73mV / °C change. Regulation coefficient is relative to 25°C.

For nominal trim and full load, the output voltage relates to the temperature according to the following equation:

$$V_{OUT\text{-}FL} = 28.0 - 3.733 \bullet 0.001 \bullet (T_{INT} - 25) \qquad (2)$$

Where T_{INT} is in °C

The impact of temperature coefficient on the output voltage is absolute, and does not scale with trim or load.

Trim Mode and Output Trim Control

When the input voltage is initially applied to a DCM, and after t_{INIT} elapses, the trim pin voltage V_{TR} is sampled. The TR pin has an internal pull-up resistor to V_{CC}, so unless external circuitry pulls the pin voltage lower, it will pull up to V_{CC}. If the initially sampled trim pin voltage is higher than $V_{TRIM\text{-}DIS\text{-}TH}$, then the DCM will disable trimming as long as the V_{IN} remains applied. In this case, for all subsequent operation the output voltage will be programmed to the nominal. This minimizes the support components required for applications that only require the nominal rated V_{OUT}, and also provides the best output setpoint accuracy, as there are no additional errors from external trim components.

If at initial application of V_{IN}, the TR pin voltage is prevented from exceeding $V_{TRIM\text{-}EN\text{-}TH}$, then the DCM will activate trim mode, and it will remain active for as long as V_{IN} is applied.

V_{OUT} set point under full load and room temperature can be calculated using the equation below:

$$V_{OUT\text{-}FL}\ @\ 25ºC = 12.25 + (21.274 \bullet V_{TR} / V_{CC}) \qquad (3)$$

Note that the trim mode is not changed when a DCM recovers from any fault condition or being disabled.

Module performance is guaranteed through output voltage trim range $V_{OUT\text{-}TRIMMING}$. If V_{OUT} is trimmed above this range, then certain combinations of line and load transient conditions may trigger the output OVP.

Downloaded from Arrow.com.

Overall Output Voltage Transfer Function

Taking load line (Equation 1), temperature coefficient (Equation 2) and trim (Equation 3) into account, the general equation relating the DC V_{OUT} to programmed trim (when active), load and temperature is given by:

$$V_{OUT} = 12.25 + (21.274 \bullet V_{TR} / V_{CC}) + 1.4736 \bullet (1 - I_{OUT} / 17.90) -3.733 \bullet 0.001 \bullet (T_{INT} - 25) + \Delta V_{OUT\text{-}LL} \quad (4)$$

Finally, note that when the load current is below 10% of the rated capacity, there is an additional ΔV which may add to the output voltage, depending on the line voltage which is related to light-load boosting. Please see the section on light-load boosting below for details.

Use 0V for $\Delta V_{OUT\text{-}LL}$ when load is above 10% of rated load. See section on light-load boosting operation for light-load effects on output voltage.

Output Current Limit

The DCM features a fully operational current limit which effectively keeps the module operating inside the Safe Operating Area (SOA) for all valid trim and load profiles. The current limit approximates a "brick wall" limit, where the output current is prevented from exceeding the current limit threshold by reducing the output voltage via the internal error amplifier reference. The current limit threshold at nominal trim and below is typically 120% of rated output current, but it can vary between 100% to 140%. In order to preserve the SOA, when the converter is trimmed above the nominal output voltage, the current limit threshold is automatically reduced to limit the available output power.

When the output current exceeds the current limit threshold, current limit action is held off by 1ms, which permits the DCM to momentarily deliver higher peak output currents to the load. Peak output power during this time is still constrained by the internal Power Limit of the module. The fast Power Limit and relatively slow Current Limit work together to keep the module inside the SOA. Delaying entry into current limit also permits the DCM to minimize droop voltage for load steps.

Sustained operation in current limit is permitted, and no de-rating of output power is required, even in an array configuration.

Some applications may benefit from well matched current distribution, in which case fine tuning sharing via the trim pins permits control over sharing. The DCM does not require this for proper operation, due to the power limit and current limit behaviors described here.

Current limit can reduce the output voltage to as little as the UVP threshold ($V_{OUT\text{-}UVP}$). Below this minimum output voltage compliance level, further loading will cause the module to shut down due to the output undervoltage fault protection.

Line Impedance, Input Slew Rate and Input Stability Requirements

Connect a high-quality, low-noise power supply to the +IN and –IN terminals. Additional capacitance may have to be added between +IN and –IN to make up for impedances in the interconnect cables as well as deficiencies in the source.

Excessive source impedance can bring about system stability issues for a regulated DC-DC converter, and must either be avoided or compensated by filtering components. A 1µF input capacitor is the minimum recommended in case the source impedance is insufficient to satisfy stability requirements.

For selecting optimum value of decoupling capacitor, refer to section 2 of the DCM Design Guide.

Ensure that the input voltage slew rate is less than 1V/µs, otherwise a pre-charge circuit is required for the DCM input to control the input voltage slew rate and prevent overstress to input stage components.

Input Fuse Selection

The DCM is not internally fused in order to provide flexibility in configuring power systems. Input line fusing is recommended at the system level, in order to provide thermal protection in case of catastrophic failure. The fuse shall be selected by closely matching system requirements with the following characteristics:

- Current rating
  (usually greater than the DCM converter's maximum current)
- Maximum voltage rating
  (usually greater than the maximum possible input voltage)
- Ambient temperature
- Breaking capacity per application requirements
- Nominal melting I^2t
- Recommended fuse:
  See Safety Approvals for recommended fuse

Downloaded from Arrow.com.

Fault Handling

Input Undervoltage Fault Protection (UVLO)

The converter's input voltage is monitored to detect an input undervoltage condition. If the converter is not already running, then it will ignore enable commands until the input voltage is greater than $V_{IN-UVLO+}$. If the converter is running and the input voltage falls below $V_{IN-UVLO-}$, the converter recognizes a fault condition, the powertrain stops switching, and the output voltage of the unit falls.

Input voltage transients which fall below UVLO for less than t_{UVLO} may not be detected by the fault protection logic, in which case the converter will continue regular operation. No protection is required in this case.

Once the UVLO fault is detected by the fault protection logic, the converter shuts down and waits for the input voltage to rise above $V_{IN-UVLO+}$. Provided the converter is still enabled, it will then restart.

Input Overvoltage Fault Protection (OVLO)

The converter's input voltage is monitored to detect an input overvoltage condition. When the input voltage is more than the $V_{IN-OVLO+}$, a fault is detected, the powertrain stops switching, and the output voltage of the converter falls.

After an OVLO fault occurs, the converter will wait for the input voltage to fall below $V_{IN-OVLO-}$. Provided the converter is still enabled, the powertrain will restart.

The powertrain controller itself also monitors the input voltage. Transient OVLO events which have not yet been detected by the fault sequence logic may first be detected by the controller if the input slew rate is sufficiently large. In this case, powertrain switching will immediately stop. If the input voltage falls back in range before the fault sequence logic detects the out of range condition, the powertrain will resume switching and the fault logic will not interrupt operation. Regardless of whether the powertrain is running at the time or not, if the input voltage does not recover from OVLO before t_{OVLO}, the converter fault logic will detect the fault.

Output Undervoltage Fault Protection (UVP)

The converter determines that an output overload or short circuit condition exists by measuring its primary sensed output voltage and the output of the internal error amplifier. In general, whenever the powertrain is switching and the primary-sensed output voltage falls below $V_{OUT-UVP}$ threshold, a short circuit fault will be registered. Once an output undervoltage condition is detected, the powertrain immediately stops switching, and the output voltage of the converter falls. The converter remains disabled for a time t_{FAULT}. Once recovered and provided the converter is still enabled, the powertrain will again enter the soft-start sequence after t_{INIT} and t_{ON}.

Temperature Fault Protections (OTP)

The fault logic monitors the internal temperature of the converter. If the measured temperature exceeds $T_{INT-OTP}$, a temperature fault is registered. As with the undervoltage fault protection, once a temperature fault is registered, the powertrain immediately stops switching, the output voltage of the converter falls, and the converter remains disabled for at least time t_{FAULT}. Then, the converter waits for the internal temperature to return to below $T_{INT-OTP}$ before recovering. Provided the converter is still enabled, the DCM will restart after t_{INIT} and t_{ON}.

Output Overvoltage Fault Protection (OVP)

The converter monitors the output voltage during each switching cycle by a corresponding voltage reflected to the primary side control circuitry. If the primary sensed output voltage exceeds $V_{OUT-OVP}$, the OVP fault protection is triggered. The control logic disables the powertrain, and the output voltage of the converter falls.

This type of fault is latched, and the converter will not start again until the latch is cleared. Clearing the fault latch is achieved by either disabling the converter via the EN pin, or else by removing the input power such that the input voltage falls below $V_{IN-INIT}$.

External Output Capacitance

The DCM converter internal compensation requires a minimum external output capacitor. An external capacitor in the range of 200 – 2000µF with ESR of 10mΩ is required, per DCM for control loop compensation purposes.

However some DCM models require an increase in the minimum external output capacitor value in certain loading and trim conditions. In applications where the load can go below 10% of rated load but the output trim is held constant, the range of output capacitor required is given by $C_{OUT-EXT-TRANS}$ in the Electrical Specifications table. If the load can go below 10% of rated load and the DCM output trim is also dynamically varied, the range of output capacitor required is given by $C_{OUT-EXT-TRANS-TRIM}$ in the Electrical Specifications table.

Light-Load Boosting

Under light-load conditions, the DCM converter may operate in light-load boosting depending on the line voltage. Light-load boosting occurs whenever the internal power consumption of the converter combined with the external output load is less than the minimum power transfer per switching cycle. In order to maintain regulation, the error amplifier will switch the powertrain off and on repeatedly, to effectively lower the average switching frequency, and permit operation with no external load. During the time when the powertrain is off, the module internal consumption is significantly reduced, and so there is a notable reduction in no-load input power in light-load boosting. When the load is less than 10% of rated I_{OUT}, the output voltage may rise by a maximum of 4.93V, above the output voltage calculated from trim, temperature and load line conditions.

Downloaded from Arrow.com.

Thermal Considerations

Based on the specified thermal operating area shown on page 12, the full rated power of the DCM4623TB0G31E0M00 can be processed provided that the top, bottom and leads are all held below 87°C. These curves highlight the benefits of dual-sided thermal management, but also demonstrate the flexibility of the Vicor ChiP™ platform for customers who are limited to cooling only the top or the bottom surface.

The OTP sensor is located on the top side of the internal PCB structure. Therefore in order to ensure effective overtemperature fault protection, the case bottom temperature must be constrained by the thermal solution such that it does not exceed the temperature of the case top.

The ChiP package provides a high degree of flexibility in that it presents three pathways to remove heat from internal power dissipating components. Heat may be removed from the top surface, the bottom surface and the leads. The extent to which these three surfaces are cooled is a key component for determining the maximum power that is available from a ChiP, as can be seen from Figure 20.

Since the ChiP has a maximum internal temperature rating, it is necessary to estimate this internal temperature based on a real thermal solution. Given that there are three pathways to remove heat from the ChiP, it is helpful to simplify the thermal solution into a roughly equivalent circuit where power dissipation is modeled as a current source, isothermal surface temperatures are represented as voltage sources and the thermal resistances are represented as resistors. Figure 20 shows the "thermal circuit" for a DCM4623 ChiP, in an application where both case top and case bottom and leads are cooled. In this case, the DCM power dissipation is PD_{TOTAL} and the three surface temperatures are represented as T_{CASE_TOP}, T_{CASE_BOTTOM} and T_{LEADS}. This thermal system can now be very easily analyzed with simple resistors, voltage sources, and a current source.

This analysis provides an estimate of heat flow through the various pathways as well as internal temperature.




Figure 20 — *Double-side cooling and leads thermal model*

Alternatiely, equations can be written around this circuit and analyzed algebraically:

$$T_{INT} - PD_1 \bullet \theta_{INT\text{-}TOP} = T_{CASE_TOP}$$
$$T_{INT} - PD_2 \bullet \theta_{INT\text{-}BOTTOM} = T_{CASE_BOTTOM}$$
$$T_{INT} - PD_3 \bullet \theta_{INT\text{-}LEADS} = T_{LEADS}$$
$$PD_{TOTAL} = PD_1 + PD_2 + PD_3$$

Where T_{INT} represents the internal temperature and PD_1, PD_2 and PD_3 represent the heat flow through the top side, bottom side and leads respectively.




Figure 21 — *One-side cooling and leads thermal model*

Figure 21 shows a scenario where there is no bottom-side cooling. In this case, the heat flow path to the bottom is left open and the equations now simplify to:

$$T_{INT} - PD_1 \bullet \theta_{INT\text{-}TOP} = T_{CASE_TOP}$$
$$T_{INT} - PD_3 \bullet \theta_{INT\text{-}LEADS} = T_{LEADS}$$
$$PD_{TOTAL} = PD_1 + PD_3$$




Figure 22 — *One-side cooling thermal model*

Figure 22 shows a scenario where there is no bottom-side and leads cooling. In this case, the heat flow path to the bottom is left open and the equations now simplify to:

$$T_{INT} - PD_1 \bullet \theta_{INT\text{-}TOP} = T_{CASE_TOP}$$
$$PD_{TOTAL} = PD_1$$

Vicor provides a suite of online tools, including a simulator and thermal estimator which greatly simplify the task of determining whether or not a DCM thermal configuration is sufficient for a given condition. These tools can be found at: www.vicorpower.com/powerbench.

Symbol	Thermal Impedance (°C/W)	Definition of Estimated Thermal Resistance
$\theta_{INT\text{-}TOP}$	1.7	to maximum-temperature internal component from isothermal top
$\theta_{INT\text{-}LEADS}$	5.6	to maximum-temperature internal component from isothermal leads
$\theta_{INT\text{-}BOTTOM}$	1.8	to maximum-temperature internal component from isothermal bottom
Thermal Capacity		
21.5Ws/°C		

Table 1 — *Thermal data*

Downloaded from Arrow.com.

Array Operation

A decoupling network is needed to facilitate paralleling:

- An output inductor should be added to each DCM, before the outputs are bussed together to provide decoupling.
- Each DCM needs a separate input filter, even if the multiple DCMs share the same input voltage source. These filters limit the ripple current reflected from each DCM, and also help suppress generation of beat frequency currents that can result when multiple powertrains input stages are permitted to directly interact.

If signal pins (TR, EN, FT) are not used, they can be left floating, and DCM will work in the nominal output condition.

When common-mode noise in the input side is not a concern, TR and EN can be driven and FT received using a single Kelvin connection to the shared –IN as a reference.

Note: For more information on parallel operation of DCMs, refer to "Parallel DCMs" application note AN:030.

An example of DCM paralleling circuit is shown in Figure 23.

Filter components

Input filter: The choice of the input filter components varies up on the low line and maximum output power of the DCM. Refer to the Filtering Guidelines Introduction section in the DCM Design Guide to design an input filter.

Output filter:

Reference Designator	Value	Mfg. Part Number & Count/DCM
C_{2_1}	80µF	GRM32EC72A106KE05L, #8
L_{2_1}, L_{2_2}	0.33µH	744309033, #1
R_{d_1}, R_{d_2}	0.05Ω	RL2512FK-070R05L, #1
L_{b_1}, L_{b_2}	72nH	IFLR2727EZER72NM01, #1

$C_{OUT-EXT-x}$: electrolytic or tantalum capacitor with at least 10mΩ ESR, 200µF ≤ **$C_{OUT-EXT}$** ≤ 2000µF;

C_3, C_4: additional ceramic /electrolytic capacitors, if needed for output ripple filtering;

In order to help sensitive signal circuits reject potential noise, additional components are recommended:

R_{2_x}: 301Ω, facilitate noise attenuation for TR pin;

FB_{1_x}, C_{2_x}: **FB_1** is a ferrite bead with an impedance of at least 10Ω at 100MHz. **C_{2_x}** can be a ceramic capacitor of 0.1µF. Facilitate noise attenuation for EN pin.

Note: Use an RCR filter network as suggested in the application note AN:030 to reduce the noise on the signal pins.

Note: In case of the excessive line inductance, a properly sized decoupling capacitor $C_{DECOUPLE}$ is required as shown in Figure 23 and Figure 24.

When common-mode noise rejection in the input side is needed, common-mode chokes can be added in the input side of each DCM. An example of DCM paralleling circuit is shown in Figure 24.

Notice that each group of control pins need to be individually driven and isolated from the other groups control pins. This is because –IN of each DCM can be at a different voltage due to the common mode chokes. Attempting to share control pin circuitry could lead to incorrect behavior of the DCMs.




Figure 23 — *DCM paralleling configuration circuit 1*

Downloaded from Arrow.com.




Figure 24 — *DCM paralleling configuration circuit 2*


An array of DCMs used at the full array rated power may generally have one or more DCMs operating at current limit, due to sharing errors. Load sharing is functionally managed by the load line. Thermal balancing is improved by the nominal effective temperature coefficient of the output voltage set point.

DCMs in current limit will operate with higher output current or power than the rated levels. Therefore the following Thermal Specified Operating Area plot should be used for arrays or loads that drive the DCM in to current limit for sustained operation.


Downloaded from Arrow.com.


DCM Module Product Outline Drawing Recommended PCB Footprint and Pinout

4623 THRU HOLE
(Reference DWG # 40257 Rev 4)




TOP VIEW (COMPONENT SIDE)





BOTTOM VIEW



RECOMMENDED HOLE PATTERN
(COMPONENT SIDE)

NOTES:
1- UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE MM [INCH]
2- TOLERANCES ARE:
DECIMALS
X.XX [X.XX] = ±0.25 [0.01]
X.XXX [X.XXX] = ±0.127 [0.005]
ANGLES = ±1°

Downloaded from Arrow.com.

Revision History

Revision	Date	Description	Page Number(s)
1.0	06/02/23	Initial release	N/A
1.1	06/12/23	Spec correction	8

Downloaded from Arrow.com.

Vicor's comprehensive line of power solutions includes high density AC-DC and DC-DC modules and accessory components, fully configurable AC-DC and DC-DC power supplies, and complete custom power systems.

Information furnished by Vicor is believed to be accurate and reliable. However, no responsibility is assumed by Vicor for its use. Vicor makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication. Vicor reserves the right to make changes to any products, specifications, and product descriptions at any time without notice. Information published by Vicor has been checked and is believed to be accurate at the time it was printed; however, Vicor assumes no responsibility for inaccuracies. Testing and other quality controls are used to the extent Vicor deems necessary to support Vicor's product warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Specifications are subject to change without notice.

Visit https://www.vicorpower.com/dc-dc/isolated-regulated/dcm for the latest product information.

Vicor's Standard Terms and Conditions and Product Warranty

All sales are subject to Vicor's Standard Terms and Conditions of Sale, and Product Warranty which are available on Vicor's webpage (https://www.vicorpower.com/termsconditionswarranty) or upon request.

Life Support Policy

VICOR'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS PRIOR WRITTEN APPROVAL OF THE CHIEF EXECUTIVE OFFICER AND GENERAL COUNSEL OF VICOR CORPORATION. As used herein, life support devices or systems are devices which (a) are intended for surgical implant into the body, or (b) support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in a significant injury to the user. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system or to affect its safety or effectiveness. Per Vicor Terms and Conditions of Sale, the user of Vicor products and components in life support applications assumes all risks of such use and indemnifies Vicor against all liability and damages.

Intellectual Property Notice

Vicor and its subsidiaries own Intellectual Property (including issued U.S. and Foreign Patents and pending patent applications) relating to the products described in this data sheet. No license, whether express, implied, or arising by estoppel or otherwise, to any intellectual property rights is granted by this document. Interested parties should contact Vicor's Intellectual Property Department.

The products described on this data sheet are protected by the following U.S. Patents Numbers:
RE40,072; 7,561,446; 7,920,391; 7,782,639; 8,427,269; 6,421,262; 9,516,761 and other patents pending.

Contact Us: https://www.vicorpower.com/contact-us

Vicor Corporation
25 Frontage Road
Andover, MA, USA 01810
Tel: 800-735-6200
Fax: 978-475-6715
www.vicorpower.com

email
Customer Service: custserv@vicorpower.com
Technical Support: apps@vicorpower.com

©2023 Vicor Corporation. All rights reserved. The Vicor name is a registered trademark of Vicor Corporation.
All other trademarks, product names, logos and brands are property of their respective owners.

Downloaded from Arrow.com.