# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# Power Cord, Locking C19 to IEC309-16A, 3.0m



AP8758

### **Overview**

Presentation	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
Lead time	Usually in Stock

### Main

Product or component type	Power cord	
Input Connection Type	IEC 60309 16 A 2P + E	
Cable length	3.00 m	

### **Physical**

Height	43.2 cm
Width	15.2 cm
Depth	10.2 cm
Net weight	0.49 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

### Input

Max line current	16 A
Input current limits	16 A

### **Output**

Max current draw	16 A
Number of power socket outlets	1 IEC 60320 C19
Power cable length	3.05 m

### **Conformance**

Product certifications	VDF		

### **Environmental**

Relative humidity	2080 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2570 °C
Storage Relative Humidity	2080 %
Storage altitude	015240 m

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43.2 cm
Package 1 Width	15.2 cm
Package 1 Length	10.2 cm
Package 1 Weight	0.49 kg

# **Contractual warranty**

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Total lifecycle Carbon footprint	154
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
SCIP Number	1cdb2fed-a06f-4574-913d-8df8e70936b2
REACh Regulation	REACh Declaration
Halogen-free status	Product contains halogen above thresholds

### **Use Again**

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	Yes