


## *Best Selection*

### Fiber Sensors

Best Selection Catalog



OMRON's Fiber Sensors continue to support  
an increasing range of applications.

This catalog brings you the latest information on our Fiber Units.



E32-series Fiber Units

Amplifier Units



E3X-DA-S/-MDA Series

E3X-NA Series

realizing

# Fiber Unit

## Standard Models

## First, Our Standard Lineup

...▶ P6

These Fibers Units can be used in a variety of applications, such as detecting the presence of workpieces and positioning.

### A Wide Variety of Shapes for Adapting to Different Installation Locations

Choose the model that suits the installation space from a wide variety of shapes and sizes.



### Space Savings and Simple Mounting

#### Flat Models


Flat models that allow simple screw mounting and straightforward wiring have been added to the lineup. Using these models eliminates the problem of fibers getting caught on surrounding objects.



### Detect Workpieces in Tight Spaces


#### Custom-produced Sleeves

Models with sleeves allow detection in tight spaces. We will perform the time-consuming task of fashioning the sleeve, with a length and bends to suit the space (except for ultrafine sleeves).



### Flexible, Pliable Fiber That Can Be Handled Like Wire

We have developed a broad range of fibers to meet a wide variety of needs. Multicore (flexible) fiber is a new type of standard fiber that can be used like wire without worrying about the bending radius. We have also produced fiber that will not break when used in moving parts and fiber that is not degraded by contact with oil.



You will certainly appreciate the ease of use that flexible fiber ensures.

### Length Can Be Specified in 1-m Units

#### Saving Energy and Work

We will produce fiber of the required length (in meter units). For large-scale installations, specifications of up to 20 m can be handled. (Specifications of 0.3 m and 0.5 m are also possible.)




## Special-beam Models

## Detection with Increased Reliability ...▶ P10

A variety of heads incorporating the latest optical technology makes it possible to solve common problems related to detection and to increase reliability.


- Resistant to dust and dirt
  - Capable of detecting small workpieces
  - Resistant to workpiece vibration
- Use these models to handle unstable detection conditions.



## Environment-resistive Models

## High Resistance to External Conditions with Fiber ...▶ P14

We have developed model variations for adapting to a variety of environmental conditions. These models enable detection in high-temperature environments and vacuums.



- High-temperature environments
  - Environments subject to the splattering of chemicals
  - Vacuums
- Use these models to handle applications in special environments.

## Application-corresponding Models

## Fiber Units for the Food-packaging, Semiconductor, and FPD Industries ...▶ P16

These models, which were developed for specific applications, offer top-quality detection performance.


- Label detection
  - Liquid-level detection
  - Alignment and mapping of glass substrates
  - Wafer mapping
- Use these models for specific applications.



### ■ Page Reference

Type	Feature/applications	Variations	Type	Ratings and performance	Dimensions
Standard models	→ Page 6	→ Page 8	Through-beam → Page 19 Reflective → Page 26	→ Page 37	Through-beam → Page 40 Reflective → Page 48
Special-beam models	→ Page 10	---	Through-beam → Page 22 Reflective → Page 29	→ Page 38	Through-beam → Page 43 Reflective → Page 51
Environment resistant models	→ Page 14	---	Through-beam → Page 24 Reflective → Page 32	→ Page 39	Through-beam → Page 46 Reflective → Page 56
Application-corresponding models	→ Page 16	---	→ Page 33	→ Page 39	→ Page 57
Accessories	---	---	→ Page 25 (Vacuum-resistant) → Page 35	---	→ Page 47 (Vacuum-resistant) → Page 60

## Selection Guide



### Fiber Units

Detection conditions \ Environmental conditions	Standard environments	Special environments
<b>Standard detection</b> <ul style="list-style-type: none"> <li>Workpiece presence</li> <li>Positioning</li> <li>Level differences and marks</li> </ul>	<b>Standard Models</b> ●●●▶ P.6 <div>  Workpiece presence              Positioning              Level differences              Marks           </div>	<b>Environment-resistive Models</b> ●●●▶ P.14 <div>  Workpiece presence              Positioning              Level difference           </div>
<b>Special-beam</b> <ul style="list-style-type: none"> <li>Long-distance sensing, resistance to dust and dirt</li> <li>Small beam, resistance to rattling</li> <li>Detection of transparent objects</li> </ul>	<b>Special-beam Models</b> ●●●▶ P.10 <div>  High power              Small spot              Area sensing              Retroreflective sensing           </div>	
<b>Application-corresponding</b> <ul style="list-style-type: none"> <li>Labels</li> <li>Liquid level</li> <li>Alignment and mapping of glass substrates</li> <li>Water mapping</li> </ul>	<b>Application-corresponding Models</b> ●●●▶ P.16 <div>  Labels              Liquid level              Alignment              Mapping           </div>	

### Amplifier Units

Type	Digital		Manual
Appearance		2-channel models	
Response time	48 $\mu$ s, 1 ms, or 4 ms (2-output models: 80 $\mu$ s, 1 ms, or 4 ms)	100 $\mu$ s, 1 ms, or 4 ms	200 $\mu$ s (high-speed models: 20 $\mu$ s)
Light source	Red, green, blue, or infrared LED		Red or green LED
Function	Dual display (including digital, bar, percent, and hold display functions) Threshold adjustment performed manually or by teaching OFF-delay, ON-delay, one-shot timer (adjustable from 1 ms to 5 s)		LED bar display (5 levels) 8-turn sensitivity adjuster OFF delay timer (fixed at 40 ms)
	Advanced-function models are available (2-output/input models).		Water-resistant models are available.
Models	E3X-DA□-S E3X-DA□TW-S (2-output model) E3X-DA□RM-S (input model)	E3X-MDA□	E3X-NA□ E3X-NA□F (high-speed model) E3X-NA□V (water-resistant model)



■ Selection Guide .....	P4
-------------------------	----

---

## ■ Overview of Features, Applications, and Variations

Standard Models	Flexible (New Standard) .....	P6
	Standard .....	P6
	Break-resistant .....	P6
	Fluorine Coating .....	P7
Special-beam Models	Long Distance, High Power .....	P10
	Ultracompact, Ultrafine Sleeve .....	P10
	Coaxial, Small Spot .....	P11
	Fine Beam (Narrow Vision Field) .....	P12
	Area Sensing .....	P12
	Retroreflective .....	P13
	Limited-reflective .....	P13
Environment-resistive Models	Heat-resistant .....	P14
	Chemical-resistant .....	P14
	Vacuum-resistant .....	P15
Application-corresponding Models	Label Detection .....	P16
	Liquid-level Detection .....	P16
	Glass-substrate Alignment .....	P17
	Glass-substrate Mapping .....	P17
	Water Mapping .....	P18

---

## ■ Ordering Information

Through-beam Fiber Units .....	P19
Fiber Units with Reflective Sensors .....	P26
Application-corresponding Fiber Units .....	P33

---

## ■ Ratings/Characteristics..... P37

---

## ■ Dimensions

Through-beam Fiber Units .....	P40
Fiber Units with Reflective Sensors .....	P48
Application-corresponding Fiber Units .....	P57

---

## ■ Precautions..... P63

## Features/Applications


### Standard Models

#### Flexible (New Standard)


R

- Perform wiring without worrying about the bending radius.
- Choose the model to suit the installation space from a variety of shapes.

Flexible fiber



Conventional fiber



Fewer problems

Light intensity affected by bends in fiber  
Fiber broken by getting caught on surrounding objects

#### ■ Feature: Multicore (Flexible) Fibers



A large number of ultrafine cores are all surrounded by cladding. As a result, the fiber is flexible and can be bent without significantly reducing the light intensity. This helps solve problems, such as fiber being broken by getting caught on other objects.

#### ■ Ratings/Characteristics

Min. sensing object	0.005-mm dia.
Min. bending radius	1 mm
Ambient temperature range	-40°C to 70°C (no icing or condensation)
Fiber material	Plastic (Free-cut)

#### Standard

- Choose the model to suit the installation space from a variety of shapes.
- New flat models allow space savings and simple installation.



Screw-shaped

Cylindrical

Flat

Equipped with sleeve

#### ■ Feature: Flat Models

Flat models, which allow simple attachment and wiring, have been added to the lineup. Choose the model to suit the installation space from 3 sensing directions and 2 sizes, standard and small.



#### ■ Ratings/Characteristics

Min. sensing object	0.005-mm dia.
Min. bending radius	10 or 25 mm*
Ambient temperature range	-40°C to 70°C (no icing or condensation)
Fiber material	Plastic (Free-cut)

\*Depends on the fiber diameter.

#### Break-resistant

B

- Bundle-fiber models can be used for moving parts.
- Capable of withstanding at least one million repeated bends (in typical applications).



#### ■ Feature: Bundle Fibers

The Fiber Units contain a large number of independent fine fibers, ensuring a high degree of flexibility.



#### ■ Ratings/Characteristics

Min. sensing object	0.005-mm dia.
Min. bending radius	4 mm (withstands repeated bending)
Ambient temperature range	-40°C to 70°C (no icing or condensation)
Fiber material	Plastic (Free-cut)


## Standard Models

### Fluorine Coating




- Fiber degradation due to oil is prevented using a fluoro-resin coating.
- Free cutting is possible with cutter provided.

Oil is blocked!



#### Feature: Fluorine Coating



Fluoro-resin is used as the sheath material to prevent fiber degradation resulting from oil adhesion.

Note: The tip of the head is not chemical-resistant.

#### Ratings/Characteristics

Min. sensing object	0.005-mm dia.
Min. bending radius	4 mm
Ambient temperature range	-40°C to 70°C (with no icing or condensation)
Fiber material	Plastic <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">Free-cut</span>

Fiber Customization Service (Fiber Length, Sleeve Length, and Bends)

#### Fiber Length



- Applicable Models
  - Standard models
  - Flexible Break-resistant Models

- Model Number Used for Ordering
  - Standard model number + Fiber length
  - Fiber length: 0.3 m, 0.5 m, or any length from 1 to 20 m (in 1-m units)


#### Sleeve Length and Bends

- Applicable Models
  - E32-TC200B/E32-TC200F
  - E32-DC200B/E32-DC200F
  - The E32-DC200B cannot be bent.


This customization/delivery service applies to standard models. It is aimed at reducing industrial waste and simplifying the installation procedure.

#### Fiber Length vs. Sensing Distance

Through-beam Fiber Units  
(Fiber length of 2 m corresponds to 100%.)



Fiber Units with Reflective Sensors  
(Fiber length of 2 m corresponds to 100%.)




#### Model Number Used When Changing Only the Sleeve Length



Model: E32-\*1C200\*2-S\*3

#### Model Number Used When Changing the Sleeve Length and Bends



Model Numbers Incorporating the Bending Radius, R, and Dimensions L1 and L2  
Specifying L1 Only (Units: mm) Specifying L2 Only (Units: mm)

Bending radius	L1 (±1)	Model number	Bending radius	L2 (±1)	Model number
R5	10	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> A1	R5	5	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> A3
	15	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> A2		10	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> A4
R7.5	12.5	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> B1	R7.5	7.5	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> B3
	17.5	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> B2		17.5	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> B4
R10	15	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> C1	R10	10	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> C3
	20	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> C2		20	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> C4
R12.5	17.5	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> D1	R12.5	12.5	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> D3
	22.5	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> D2		22.5	E32- <span style="border: 1px solid black; padding: 0 2px;">*1</span> C200 <span style="border: 1px solid black; padding: 0 2px;">*2</span> -S <span style="border: 1px solid black; padding: 0 2px;">*3</span> D4

\*1: Insert "T" for Through-beam Fiber Units and "D" for Fiber Units with Reflective Sensors.

\*2: Insert the "B" or "F" that appears at the end of the original model number.

\*3: Insert "50" if the total length is 50 mm. The total length must not exceed 120 mm.

## Features/Applications
















### Standard Models

Overview of Model Variations




### Through-beam Fiber Units

Sensing distance (mm)  
(See note 1.)

Model

Type (See note 2.)	Flexible (New Standard)   Flexible and pliable	Standard 	Break-resistant   Withstands repeated bending	Fluorine coating  (Cross section)  Cable protected against oil
 Screw-shaped (top-view)	M4 	530 E32-T11N		
	M4	530 E32-T11R	760 E32-TC200	680 E32-T11 E32-T11U
(with sleeve) 	M3	130 E32-T21R	220 E32-TC200E	200 E32-T21
	M4 (1.2-dia. sleeve) M3 (0.9-dia. sleeve)	530 E32-TC200BR 130 E32-TC200FR	760 E32-TC200B 220 E32-TC200F	
Cylindrical (top-view) 	3 dia.	530 E32-T12R	760 E32-T12	680 E32-T12B
	1.5 dia.	130 E32-T222R	220 E32-T222	200 E32-T22B
(side-view) 	3 dia.	210 E32-T14LR	460 E32-T14L	
	1 dia.	50 E32-T24R	130 E32-T24	
Flat (top-view) 	15 × 8 × 3	530 E32-T15XR	760 E32-T15X	680 E32-T15XB
	12 × 7 × 2	130 E32-T25XR	220 E32-T25X	150 E32-T25XB
(side-view) 	15 × 8 × 3	210 E32-T15YR	460 E32-T15Y	
	12 × 7 × 2	50 E32-T25YR	130 E32-T25Y	
(flat-view) 	15 × 8 × 3	210 E32-T15ZR	460 E32-T15Z	
	12 × 7 × 2	50 E32-T25ZR	130 E32-T25Z	

Note 1. The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).

2. These symbols are defined as follows.  : Flexible fiber,  : Bendable fiber,  : Fluorine-coated fiber.























































# Standard Models




## Overview of Model Variations

### Fiber Units with Reflective Sensors

Sensing distance (mm) (See note 1)
Model

Type (See note 2.)		Flexible (New Standard) <div></div> <div></div> <div>Flexible and pliable</div>	Standard <div></div>	Break-resistant <div></div> <div></div> <div>Withstands repeated bending</div>	Fluorine coating <div></div> <div></div> <div>Cable protected against oil</div>
<div>Shape of head</div> <div>[For dimensions, refer to page 40.]</div> <div></div>	M6	<div></div> 170			
		E32-D11N			
	M6	<div></div> 170			
		E32-C11N			
<div>Screw-shaped (top-view)</div> <div></div>	M6	<div></div> 170	<div></div> 300	<div></div> 170	<div></div> 170
		E32-D11R	E32-DC200	E32-D11	E32-D11U
	M3	<div></div> 30	<div></div> 80	<div></div> 30	
		E32-D21R	E32-DC200E	E32-D21	
<div>(with sleeve)</div> <div></div>	M6 (2.5-dia. sleeve)	<div></div> 170	<div></div> 300		
		E32-DC200BR	E32-DC200B		
	M3 (1.2-dia. sleeve)	<div></div> 30	<div></div> 80		
		E32-DC200FR	E32-DC200F		
<div>Cylindrical (top-view)</div> <div></div>	3 dia.	<div></div> 170	<div></div> 230	<div></div> 70	
		E32-D12R	E32-D12	E32-D221B	
	3 dia. (1.5 dia.)	<div></div> 30	<div></div> 80	<div></div> 30	
		E32-D22R	E32-D22	E32-D22B	
<div>(side-view)</div> <div></div>	6 dia.	<div></div> 45	<div></div> 110		
		E32-D14LR	E32-D14L		
	2 dia.	<div></div> 15	<div></div> 30		
		E32-D24R	E32-D24		
<div>Flat (top-view)</div> <div></div>	15 × 10 × 3	<div></div> 170	<div></div> 300	<div></div> 170	
		E32-D15XR	E32-D15X	E32-D15XB	
	12 × 7 × 2	<div></div> 30	<div></div> 80	<div></div> 50	
		E32-D25X	E32-D25X	E32-D25XB	
<div>(side-view)</div> <div></div>	15 × 10 × 3	<div></div> 40	<div></div> 100		
		E32-D15YR	E32-D15Y		
	12 × 8 × 2	<div></div> 8	<div></div> 20		
		E32-D25YR	E32-D25Y		
<div>(flat-view)</div> <div></div>	15 × 10 × 3	<div></div> 40	<div></div> 100		
		E32-D15ZR	E32-D15Z		
	12 × 8 × 2	<div></div> 8	<div></div> 20		
		E32-D25ZR	E32-D25Z		

Note 1. The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).


2. These symbols are defined as follows.  : Flexible fiber,  : Bendable fiber,  : Fluorine-coated fiber.

## Features/Applications

## Special-beam Models

## Long Distance, High Power

- Powerful beam reduces influence of dust and dirt.
- Long sensing distance enables use in large-scale installations.



## ■ Applications

Detecting parts inside (translucent) containers



Detecting workpieces in coating processes



## ■ Ratings/Characteristics

Ambient temperature range	-40°C to 70°C (no icing or condensation)
Fiber material	Plastic (Free-cut)

## ■ Overview of Model Variations

Type	Features	Shape, sensing distance (mm)*	Model number
Through-beam	Equipped with large lens	20,000	E32-T17L
	Side-view, screw mounting	3,400	E32-T14
	M4 screw	1,330	E32-T11L
Reflective	Equipped with large lens	700	E32-D16
	M6 screw	400	E32-D11L


## Ultracompact, Ultrafine Sleeve

- Ultracompact head can be installed in tight spaces.
- Ultrafine sleeve ensures reliable detection of small objects, such as electronic components.



## ■ Applications

Alignment inspections



Detection of terminals



## ■ Ratings/Characteristics

Min. sensing object	0.005-mm dia.
Ambient temperature range	-40°C to 70°C (no icing or condensation)
Material	Plastic

## ■ Overview of Model Variations


Type	Features	Shape, sensing distance (mm)*	Model number
Through-beam	1-dia. cylinder	130	E32-T223R
	0.5-dia. sleeve (0.25-dia. opening)	44	E32-T33-S5
	0.22-dia. sleeve (0.1-dia. opening)	5	E32-T334-S5
Reflective	0.8-dia. sleeve	16	E32-D33
	0.5-dia. sleeve	3	E32-D331

\*The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).

## Special-beam Models

### Coaxial, Small Spot


- Small spot diameter (0.1 mm min. in diameter) enables the reliable detection of small workpieces.
- Use of red light ensures easy visual recognition and simple positioning.



E32-C42+  
E39-F3A

### Applications

#### Detecting of CDs





E32-C31+  
E39-F3C


### Ratings/Characteristics

Min. sensing object	0.005-mm dia.
Ambient temperature range	–40°C to 70°C (no icing or condensation)
Fiber material	Plastic

### Overview of Model Variations

Type	Features	Shape, sensing distance (mm)*	Model number
Coaxial, reflective	Coaxial, M6 screw	 300	E32-CC200
	Coaxial, 3-dia. cylinder	 150	E32-D32L
	Small spot	0.1-dia. spot at a distance of 7 mm	E32-C41+ E39-F3A-5
	Small variable spot	Spot diameter variable in the range 0.1 to 0.6 mm at distances in the range 6 to 15 mm	E32-C42+ E39-F3A
	Long distance, small spot	0.5-dia. spot at 17 mm	E32-C31+ E39-F3B
	Long distance, parallel light	Spot diameter of 4 mm max. at distances in the range 0 to 20 mm	E32-C31+ E39-F3C

\*The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).




## Features/Applications

### Special-beam Models


#### Fine Beam (Narrow Vision Field)

- Fine beam reduces unwanted light in surrounding area.
- Powerful beam allows use in applications requiring a long sensing distance.



#### Applications



Alignment inspection  
of orientation flats



#### Ratings/Characteristics

Min. bending radius	10 mm
Ambient temperature range	-40°C to 70°C (no icing or condensation)
Fiber material	Plastic (Free-cut)


#### Overview of Model Variations

Type	Features	Shape, sensing distance (mm)*	Model number
Through-beam	Top view	 1,900	E32-T22S
	Side view	 1,300	E32-T24S

\*The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).


#### Area Sensing

- These Fiber Units ensure greater reliability with the detection of position inconsistencies in passing workpieces and the presence of workpieces with holes.
- Wide sensing bands of 11 and 30 mm (through-beam models) enable the detection of large position inconsistencies.




#### Applications

Detecting passage of  
candies



E32-T16WR

Detecting chips on film







E32-T16PR

#### Ratings/Characteristics

Ambient temperature range	-40°C to 70°C (no icing or condensation) E32-T16W□ only: -25°C to 55°C
Fiber material	Plastic (Free-cut)

#### Overview of Model Variations

Type	Features	Shape, sensing distance (mm)*	Model number
Through-beam	Sensing width: 11 mm	 840	E32-T16PR
	Sensing width: 11 mm Flat-view	 750	E32-T16JR
	Sensing width: 30 mm	 1,300	E32-T16WR
Refle- ctive	Beam width: 11 mm	 150	E32-D36P1


\*The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).



# Special-beam Models

## Retroreflective


- The return optical path ensures that more light is interrupted by transparent workpieces than with through-beam models.
- Equipped with MSR function to eliminate light reflected directly from the workpiece.



E32-R16

## Applications

Detecting translucent medicine



E32-R21

## Ratings/Characteristics

Ambient temperature range	E32-R21: -40°C to 70°C E32-R16: -25°C to 55°C (with no icing or condensation)
Fiber material	Plastic <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">Free-cut</span>


## Overview of Model Variations

Type	Features	Shape, sensing distance (mm)*	Model number
Retro-reflective	MSR function, M6 screw	250	E32-R21
	MSR function, screw mounting, long distance	1,500	E32-R16

\*The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).

## Limited-reflective

- Limited-reflective models eliminate light reflected from distant objects.
- Small level differences can be reliably detected.
- The optical-axis direction can be selected according to the installation space.



E32-L24L


## Applications

Detecting connector pins

Detecting wafers (glass substrates)



E32-L25L



E32-L24L

## Ratings/Characteristics

Min. sensing object	0.005-mm dia.
Fiber material	Plastic <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">Free-cut</span> 200°C models only: Glass

## Overview of Model Variations

Type	Features	Shape, sensing distance (mm)*	Model number
Limited-reflective	Ultracompact, flat-view Ideal for checking stocks of glass substrates	0 to 4	E32-L24S
	Heat-resistant up to 105°C, top-view	5.4 to 9 (center: 7.2)	E32-L25L
	Wide sensing range, flat-view	0 to 15	E32-A10
	Heat-resistant up to 200°C, flat-view	4 to 10	E32-L86


\*The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).

# Features/Applications

## Environment-resistant Models

### Heat-resistant


- These Fiber Units can be used for various applications in temperatures up to 400°C.



E32-T84S-S

### Applications

Detecting wafers in high-temperature environments








E32-T61-S

### Ratings/Characteristics

	150°C models	200°C and higher models	
		E32-T81R E32-D81R	All other models
Min. bending radius	35 mm	10 mm	25 mm
Fiber material	Plastic (fluororesin coating)	Glass (fluororesin coating)	Glass (SUS spiral coating)

### Overview of Model Variations


Type	Ambient temperature range	Features	Shape, sensing distance (mm)*1	Model number
Through-beam	-40°C to 150°C	M4 screw	 760	E32-T51
	-40°C to 200°C	L-shaped, long distance	 1,300	E32-T84S-S
	-60°C to 350°C	M4 screw	 450	E32-T61-S
Reflective <sup>2</sup>	-60°C to 350°C	M6 screw	 90	E32-D61-S
	-40°C to 400°C	M6 screw, with sleeve	 60	E32-D73-S

\*1 The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).

\*2 Order the Fiber Unit based on the Amplifier Unit. Use the E32-D□-S if the E3X-DA□-S, E3X-MDA□, or E3X-DAC□-S is used. Use the E32-D□ if any other Amplifier is used.

### Chemical-resistant


- Built-in lens and high-power beam reduce the influence of dirt and drops of water.
- Round design prevents drops of water sticking to the head (E32-T11F).



E32-T14F

### Applications

Detecting workpieces in cleaning processes







E32-T12F

### Ratings/Characteristics

	All other models	E32-T51F	E32-T81F-S
Ambient temperature range	-40°C to 70°C	-40°C to 150°C	-40°C to 200°C
Fiber material	Plastic (fluororesin coating)		Glass (fluororesin coating)

### Overview of Model Variations

Type	Features	Shape, sensing distance (mm)*	Model number
Through-beam	Water-resistant round head	 2,000	E32-T11F
	Built-in lens, high power	 3,000	E32-T12F
	Heat-resistant up to 200°C	 700	E32-T81F-S
Reflective <sup>2</sup>	Built-in lens, high power	 95	E32-D12F

\*The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).


## Environment-resistant Models

### Vacuum-resistant

- These models can be used in high-vacuum environments at pressures from  $10^{-5}$  to 0.1 Pa.
- The 4-channel multi-flange, which has a maximum leakage rate of  $1 \times 10^{-10}$  Pa·m<sup>3</sup>/s, contributes to space savings.



### Applications (Configuration Example)



### Ratings/Characteristics

	120°C models	200°C models	Atmospheric-pressure side
Min. bending radius	30 mm	25 mm	
Fiber material	Glass (fluororesin coating)	Glass (SUS spiral coating)	Plastic <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">Free-cut</span>

### Overview of Model Variations

Type	Features	Shape, sensing distance (mm)*	Model number
Through-beam	M4 screw, top-view, heat-resistant up to 120°C, long distance	1,000	E32-T51V+ E39-F1V
	L-shaped, heat-resistant up to 120°C	130	E32-T54V 1M
	L-shaped, long distance, heat-resistant up to 200°C	480	E32-T84SV 1M

\*The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).

### Fiber Units on Atmospheric-pressure Side

Appearance	Type	Model number
	Common	E32-T10V 2M

### Flanges

Appearance	Type	Model number
	4-channel flange	E32-VF4
	1-channel flange	E32-VF1

### Ratings/Characteristics

Item	Number of channels	
	Model	
	4 channels	1 channels
	E32-VF4	E32-VF1
Leakage rate	$1 \times 10^{-10}$ Pa·m <sup>3</sup> /s max.	
Ambient temperature range	Operating: -25°C to 55°C Storage: -25°C to 55°C	
Material	Aluminum (A5056)	Stainless steel (SUS304) Aluminum (A5056)
Flange-seal material	Fluorocarbon rubber (Viton)	
Weight (packed state)	Approx. 280 g	Approx. 240 g

# Features/Application

## Application-corresponding Models


### Label Detection

- Built-in lens and high-power beam enable the reliable detection of labels through a mounting board.
- These Fiber Units can be washed with hydrogen peroxide, making them ideal for the food industry.



### Applications

#### Detecting labels





E32-G14

### Ratings/Characteristics

Ambient temperature range	-40°C to 70°C (no icing or condensation)
Fiber material	Plastic <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">Free-cut</span>
Degree of protection	IP67

### Overview of Model Variations

Type	Features	Shape, sensing distance (mm)*	Model number
Through-beam	Slot sensor, no adjustment of optical axis required	 10	E32-G14
	Screw mounting, side-view	 3,400	E32-T14

\*The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).

### Liquid-level Detection


- Area sensing is possible with minimal influence from bubbles and drops of water (E32-A01/A02/D36T).
- For safety when disconnections occur, two models have been developed, a light ON model for liquid presence and a light ON model for liquid absence (E32-A01/A02).

#### Tube-mounting model



E32-D36T


#### Liquid-contact model




E32-D82F1

### Operating Principle

#### Tube-mounting



#### Liquid-contact model



The presence/absence of liquid is detected using the refractive properties of light. More specifically, it utilizes the fact that the difference in refractive index between the air and the tip/tube is larger than the difference between the liquid and the tip/tube.

### Overview of Model Variations

Type	Features	Shape, sensing distance (mm)*	Model number
Tube-mounting	Light ON when liquid is present (ideal for checking lower limits)	Applicable tube: Transparent tube with a diameter of 3.2, 6.4, or 9.5 mm and a recommended wall thickness of 1 mm	E32-A01
	Light ON when liquid is absent (ideal for checking for overflow)	Applicable tube: Transparent tube with a diameter in the range 6 to 13 mm and a recommended wall thickness of 1 mm	E32-A02
	No restriction on tube diameter, resistant to bubbles and drops of water	Applicable tube: Transparent tube (no restriction on diameter)	E32-D36T
Liquid-contact	Heat-resistant up to 200°C, shape prevents liquid buildup	Liquid-contact model	E32-D82F1

\*The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).



## Application-corresponding Models

### Glass-substrate Alignment


- There is little variation of detection position within the detection range ( $\pm 0.1$  mm max.)
- The different model variations can handle a variety of sensing distances and temperature conditions.







E32-L16-N

### Engineering Data (E32-A07/A08/L16-N)

Detection-Position Characteristic (Typical Examples)




### Overview of Model Variations

Type	Features	Shape, sensing distance (mm)*	Model number
Limited-reflective	0 to 15 mm, wide-range sensing	 0 to 15	E32-L16-N
	Long-distance sensing	 10 to 20	E32-A08
		 15 to 25	E32-A07E1 E32-A07E2
	Heat-resistant up to 300°C	 5 to 18	E32-L66

\*The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).


### Glass-substrate Mapping

- These models can reliably detect thin glass-substrate end faces ( $t = 0.5$  mm, beveled edge).
- Using a large-diameter lens makes it possible to cope with tilting of the glass substrates.





E32-A09

### Engineering Data (E32-A09)



### Overview of Model Variations

Type	Features	Shape, sensing distance (mm)*	Model number
Limited-reflective	Large-diameter lens ensures resistance to tilting	 15 to 38 (center: 25)	E32-A09
	Heat-resistant up to 150°C		E32-A09H
	Heat-resistant up to 300°C	 20 to 30 (center: 25)	E32-A09H2


\*The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).

Features/Applications

Application-corresponding Models


Wafer Mapping

- Wafers are reliably detected with an ultrafine beam.
- The optical axis is adjusted before delivery to allow easy installation.




■ Features



Optical axis adjusted before delivery so that displacement is typically within 0.1°.



■ Engineering Data



■ Overview of Model Variations

















Type	Features	Shape, sensing distance (mm)*	Model number
Through-beam	Opening angle: 1.5°	 890	E32-A03
	With mounting flange		E32-A03-1
	Opening angle: 3° ultraslim	 340	E32-A04
	With mounting flange		E32-A04-1

\*The sensing distances apply for use in combination with the E3X-DA-S Amplifier Unit (general-purpose, standard mode).

# Ordering Information

## Through-beam Fiber Units Standard models

High-resolution mode Standard mode High-speed mode Super-high-speed mode \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).

Type	Appearance (mm) *2	Dimensions page	Sensing distance (mm)	Standard object (min. sensing object) (mm) *1	Min. bending radius (mm)	Features	Model number
Flexible (new standard)	Standard size	 M4	40	1 dia. (0.005 dia.)		M4 right angle	E32-T11N
		 M4	40			M4 screw	E32-T11R
		 3 dia.	40			3-dia. cylinder	E32-T12R
		 15 x 8 x 3	40			Flat shape	E32-T15XR
		 90 (40) (E32-TC200B4R) M4 1.2 dia. Min. bending radius of sleeve: 5	40			M4 screw, with sleeve	E32-TC200BR E32-TC200B4R
		 3 dia.	40			3-dia. cylinder, side-view	E32-T14LR
		 15 x 8 x 3	41			Flat shape, side-view	E32-T15YR
		 15 x 8 x 3	41			Flat shape, flat-view	E32-T15ZR
		 M3	40			M3 screw (small)	E32-T21R
		 2 dia.	40			2-dia. cylinder (small)	E32-T22R
	Small size	 1.5 dia.	40	0.5 dia. (0.005 dia.)		1.5-dia. cylinder (small)	E32-T222R
		 12 x 7 x 2	40			Flat shape (small)	E32-T25XR
		 90 (40) (E32-TC200F4R) M3 0.9 dia. Min. bending radius of sleeve: 5	40			M3 screw (small), with sleeve	E32-TC200FR E32-TC200F4R
		 1 dia.	41			1-dia. cylinder (small), side-view	E32-T24R
		 12 x 7 x 2	41			Flat shape (small), side-view	E32-T25YR
		 12 x 7 x 2	41			Flat shape (small), flat-view	E32-T25ZR

















\*1. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.

\*2.  Indicates models that allow free cutting.

 Flexible  Break-resistant  Fluoresces

# Through-beam Fiber Units Standard models

High-resolution mode   Standard mode   High-speed mode   \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).  
 Super-high-speed mode

Type	Appearance (mm) *2	Dimensions page	Sensing distance (mm)	Standard object (min. sensing object) (mm) *1	Min. bending radius (mm)	Features	Model number
Standard	Standard size	 (Free-cut) M4	40			M4 screw	E32-TC200
		 (Free-cut) M4	40			3-dia. cylinder	E32-T12
		 (Free-cut) 15 × 8 × 3	40	1,000 760 500 (200)		Flat shape	E32-T15X
		 (Free-cut) 90 (40) ( ): E32-TC200B4R M4 1.2 dia. Min. bending radius of sleeve: 5	40			M4 screw, with sleeve	E32-TC200B E32-TC200B4
		 (Free-cut) 3 dia.	40			3-dia. cylinder, side-view	E32-T14L
		 (Free-cut) 15 × 8 × 3	41	600 460 300 (120)		Flat shape, side-view	E32-T15Y
		 (Free-cut) 15 × 8 × 3	41			Flat shape, flat-view	E32-T15Z
	Small size	 (Free-cut) M3	40	900 680 450 (180)		M3 screw (small)	E32-TC200A E32-TC200E
		 (Free-cut) M3	40			2-dia. cylinder (small)	E32-T22
		 (Free-cut) 2 dia.	40			1.5-dia. cylinder (small)	E32-T222
		 (Free-cut) 1.5 dia.	40	270 220 125 (50)		Flat shape (small)	E32-T25X
		 (Free-cut) 12 × 7 × 2	40			M3 screw (small), with sleeve	E32-TC200F E32-TC200F4
		 (Free-cut) 90 (40) ( ): E32-TC200F4R M3 0.9 dia. Min. bending radius of sleeve: 5	40			1-dia. cylinder (small), side-view	E32-T24
		 (Free-cut) 1 dia.	41			Flat shape (small), side-view	E32-T25Y
		 (Free-cut) 12 × 7 × 2	41	160 130 75 (30)		Flat shape (small), flat-view	E32-T25Z
		 (Free-cut) 12 × 7 × 2	41				

\*1. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.




\*2. (Free-cut) Indicates models that allow free cutting.

**R** Flexible **B** Break-resistant **U** Fluororesin coating



# Standard models

  High-resolution mode 
   Standard mode 
   High-speed mode 
   Super-high-speed mode 
 \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).

Type	Appearance (mm) *2	Dimensions page	Sensing distance (mm)	Standard object (min. sensing object) (mm) *1	Min. bending radius (mm)	Features	Model number
Break-resistant	Standard size 	42				M4 screw	E32-T11
		42	<div style="background-color: #ff00ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffccff; width: 100%; height: 10px;"></div>	1 dia (0.005 dia.)		3-dia. cylinder	E32-T12B
		42				Flat shape	E32-T15XB
	Small size 	42				M3 screw (small)	E32-T21
		42	<div style="background-color: #ff00ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffccff; width: 100%; height: 10px;"></div>	0.5 dia (0.005 dia.)		2-dia. cylinder (small)	E32-T221B
		42				1.5-dia. cylinder (small)	E32-T22B
		42	<div style="background-color: #ff00ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffccff; width: 100%; height: 10px;"></div>			Flat shape (small)	E32-T25XB
	Coating 	42	<div style="background-color: #ff00ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffccff; width: 100%; height: 10px;"></div>	1 dia. (0.005 dia.)		M4 screw, fluorine coating	E32-T11U










\*1. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.

\*2. Free-cut Indicates models that allow free cutting.

R Flexible 
 B Break-resistant 
 U Fluororesin coating

# Through-beam Fiber Units Special-beam models

High-resolution mode Standard mode High-speed mode Super-high-speed mode \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).

Type	Appearance (mm) *2	Dimensions page	Sensing distance (mm)	Standard object (min. sensing object) (mm) *1	Min. bending radius (mm)	Features	Model number
Long-distance, high-power		43	<div>High-resolution mode: 20,000*3</div> <div>Standard mode: 20,000*3</div> <div>High-speed mode: 10,000 (4,000)</div>	10 dia.	R25	Large built-in lens, M14 screw	E32-T17L
		40 60	<div>High-resolution mode: 4,000</div> <div>Standard mode: 3,700</div> <div>High-speed mode: 2,400 (970)</div>	4 dia. (0.1 dia.)	R1	M4 right angle	E32-T11N+ E39-F1
		40 60	<div>High-resolution mode: 4,000*4</div> <div>Standard mode: 4,000*4</div> <div>High-speed mode: 2,600 (1,500)</div>		R25	M4 screw	E32-TC200+ E39-F1
		40 60	<div>High-resolution mode: 4,000*4</div> <div>Standard mode: 3,700</div> <div>High-speed mode: 2,400 (970)</div>		R1	M4 screw, flexible fiber	E32-T11R+ E39-F1
		42 60	<div>High-resolution mode: 4,000*4</div> <div>Standard mode: 3,600</div> <div>High-speed mode: 2,300 (930)</div>		R4	M4 screw, break-resistant	E32-T11+ E39-F1
		43	<div>High-resolution mode: 4,000*4</div> <div>Standard mode: 3,400</div> <div>High-speed mode: 2,250 (900)</div>			Screw mounting, side-view	E32-T14
		43	<div>High-resolution mode: 1,700</div> <div>Standard mode: 1,330</div> <div>High-speed mode: 870 (350)</div>	1.4 dia. (0.01 dia.)	R25	M4 screw	E32-T11L
		43				3-dia. cylinder	E32-T12L
		43 60	<div>High-resolution mode: 910</div> <div>Standard mode: 800</div> <div>High-speed mode: 500 (180)</div>	3 dia. (0.1 dia.)	R25	M4 screw, side-view	E32-T11L+ E39-F2
		40 60	<div>High-resolution mode: 520</div> <div>Standard mode: 400</div> <div>High-speed mode: 250 (100)</div>			M4 screw, side-view, flexible fiber	E32-T11R+ E39-F2
		42 60	<div>High-resolution mode: 820</div> <div>Standard mode: 660</div> <div>High-speed mode: 430 (160)</div>		R4	M4 screw, side-view, break-resistant	E32-T11+ E39-F2
		43	<div>High-resolution mode: 540</div> <div>Standard mode: 440</div> <div>High-speed mode: 250 (100)</div>	0.9 dia. (0.005 dia.)	R10	M3 screw (small)	E32-T21L
		43				2-dia. cylinder (small)	E32-T22L

\*1. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.

\*2.  Indicates models that allow free cutting.
































































\*3. The optical fiber is 10 m long on each side, so the sensing distance is 20,000 mm.

\*4. The optical fiber is 2 m long on each side, so the sensing distance is 4,000 mm.

 Flexible  Break-resistant  Fluororesin coating

# Special-beam models

  High-resolution mode 
   Standard mode 
   High-speed mode 
   Super-high-speed mode 
 \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).

Type	Appearance (mm) *2	Dimensions page	Sensing distance (mm)			Standard object (min. sensing object) (mm)*1	Min. bending radius (mm)	Features	Model number
Ultracompact, thin-sleeve		44	 160  130  75 (30)			0.5 dia. (0.005 dia.)	 R1	1-dia. cylinder, flexible fiber	E32-T223R
		44	 53  44  25 (10)			0.25 dia. (0.005 dia.)	 R10	0.5-dia. sleeve; 0.25-dia. opening	E32-T33-S5
		44	 12  10  6 (4)			0.125 dia. (0.005 dia.)		0.25-dia. sleeve; 0.125-dia. opening	E32-T333-S5
		44	 6  5  3 (2)			0.1 dia. (0.005 dia.)		0.22-dia. sleeve; 0.1-dia. opening	E32-T334-S5
Fine-beam		44	 2,500  1,900  1,250 (500)			1.7 dia. (0.1 dia.)	 R10	3-dia. cylinder	E32-T22S
		44	 1,750  1,300  870 (350)			2 dia. (0.1 dia.)		3.5-dia. cylinder, side-view	E32-T24S
Area-sensing		45	 1,100  840  560 (220)			(0.2 dia.) *3	 R1	Area width: 11 mm	E32-T16PR
		45	 1,500  1,100  750 (300)				 R10		E32-T16P
		45	 980  750  480 (190)			(0.3 dia.) *3	 R1	Area width: 11 mm; side-view	E32-T16JR
		45	 1,300  1,000  650 (260)				 R10		E32-T16J
		44	 1,700  1,300  850 (340)			(0.6 dia.) *4	 R1	Area width: 30 mm	E32-T16WR
		44	 2,300  1,800  1,150 (450)				 R10		E32-T16W
	45	 3,700  2,800  1,850 (740)			2 dia. (0.1 dia.)	 R25	Area width: 10 mm; long distance	E32-T16	
	44	 750  610  350 (140)					Multi-point detection (4-head)	E32-M21	

\*1. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.

























\*2.  Indicates models that allow free cutting.

\*3. This is the value for which detection is possible within the sensing area, with the sensing distance set to 300 mm. (The sensing object is stationary.)


\*4. This is the value for which detection is possible within the sensing area, with the sensing distance set to give a digital value of 1,000. (The sensing object is stationary.)

# Through-beam Fiber Units Environment-resistant models

High-resolution mode Standard mode High-speed mode \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).  
( Super-high-speed mode)

Type	Appearance (mm) *2	Dimensions page	Sensing distance (mm)	Standard object (min. sensing object) (mm)*1	Min. bending radius (mm)	Features	Model number
Heat-resistant	150°C *5	 M4	46	 1,000 760 500 (200)	1.5 dia. (0.1 dia.)	Heat-resistant up to 150°C	E32-T51
		 2 dia.	46	 300 230 150 (60)		Heat-resistant up to 150°C; side-view	E32-T54
	200°C *6	 M4	46	 360 280 180 (70)	1 dia. (0.005 dia.)	Heat-resistant up to 200°C	E32-T81R-S
		 M4	46 60	 600 450 300 (120)	3 dia. (0.1 dia.)	Heat-resistant up to 200°C; side-view	E32-T61-S+ E39-F2
		 M4	46 60	 4,000*7 3,400 2,200 (900)	4 dia. (0.1 dia.)	Heat-resistant up to 200°C, long distance	E32-T61-S+ E39-F1
		 3 dia.	46	 1,750 1,300 870 (350)	1.7 dia. (0.1 dia.)	Heat-resistant up to 200°C; L-shaped; long distance	E32-T84S-S
	350°C *6	 M4	46	 600 450 300 (120)	1 dia. (0.005 dia.)	Heat-resistant up to 350°C	E32-T61-S
Chemical-resistant	 7.2 dia.	46	 2,500 2,000 1,300 (520)	4 dia. (0.1 dia.)	R4	Fluororesin cover, round head	E32-T11F
	 5 dia.	46	 4,000*7 3,000 2,000 (800)		R40	Fluororesin cover, long distance	E32-T12F
	 5 dia.	46	 500 400 250 (100)	3 dia. (0.1 dia.)		Fluororesin cover, side-view	E32-T14F
	 5 dia.	46	 1,800 1,400 900 (350)	4 dia. (0.1 dia.)		Fluororesin cover, heat-resistant up to 150°C *5	E32-T51F
	 6 dia.	46	 920 700 460 (190)	1 dia. (0.005 dia.)	R10	Fluororesin cover, heat-resistant up to 200°C *6	E32-T81F-S

\*1. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.

\*2.  Indicates models that allow free cutting.

\*3. This is the value for which detection is possible within the sensing area, with the sensing distance set to 300 mm. (The sensing object is stationary.)

\*4. This is the value for which detection is possible within the sensing area, with the sensing distance set to give a digital value of 1,000. (The sensing object is stationary.)




\*5. For continuous operation, use the products within a temperature range of -40°C to 130°C.

\*6. The maximum temperature that can be withstood varies with the location. Refer to dimensions diagrams for details.

\*7. The optical fiber is 2 m long on each side, so the sensing distance is 4,000 mm.



## Environment-resistant models

  High-resolution mode 
   Standard mode 
   High-speed mode 
   Super-high-speed mode 
 \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).


Type	Appearance (mm)	Dimensions page	Sensing distance (mm)	Standard object (min. sensing object) (mm) *	Min. bending radius (mm)	Features	Model number
Vacuum-resistant		47	<div style="background-color: #ff00ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100px; height: 10px; margin-bottom: 2px;"></div>	1.2 dia. (0.01 dia.)	R30	M4 screw, heat-resistant up to 120°C	E32-T51V 1M
		47	<div style="background-color: #ff00ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100px; height: 10px; margin-bottom: 2px;"></div>	4 dia. (0.1 dia.)		M4 screw, heat-resistant up to 120°C, long distance	E32-T51V 1M+ E39-F1V
		47	<div style="background-color: #ff00ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100px; height: 10px; margin-bottom: 2px;"></div>	1.2 dia. (0.01 dia.)		L-shaped, heat-resistant up to 120°C	E32-T54V 1M
		47	<div style="background-color: #ff00ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100px; height: 10px; margin-bottom: 2px;"></div>	4 dia. (0.1 dia.)		L-shaped, heat-resistant up to 120°C, long distance	E32-T54V 1M+ E39-F1V
		47	<div style="background-color: #ff00ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100px; height: 10px; margin-bottom: 2px;"></div>	2 dia. (0.1 dia.)	R25	L-shaped, heat-resistant up to 200°C, long distance	E32-T84SV 1M
		47	<div style="background-color: #ff00ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100px; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100px; height: 10px; margin-bottom: 2px;"></div>				

\* The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.


### Flanges

Appearance (mm)	Dimensions page	Type	Model number
	47	4-channel flange	E32-VF4
	47	1-channel flange	E32-VF1

### Lens Units


Appearance (mm)	Dimensions page	Type	Quantity	Remarks
	47	E39-F1V	2	Long-distance Lens Unit Can be used for the E32-T51V and the E32-T54V.

### Fiber Units for Atmospheric-pressure Side

Appearance (mm)	Dimensions page	Type	Model number
	47	Amplifier-Flange Connection Fiber	E32-T10V 2M

\* Free-cut Indicates models that allow free cutting.




















### Mounting Brackets

Appearance (mm)	Dimensions page	Type	Quantity	Remarks
	47	E39-L54V	2	Can be used for the E32-T54V.

# Fiber Units with Reflective Sensors

## Standard models

  High-resolution mode 
   Standard mode 
   High-speed mode 
   Super-high-speed mode 
 \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).

Type	Appearance (mm) *3	Dimen- sions page	Sensing distance (mm) *1				(Min. sensing object) (mm) *2	Min. bending radius (mm)	Features	Model number
Flexible (new standard)	Standard size		48						M6 right angle	E32-D11N
			48						M6 screw	E32-D11R
			48						3-dia. cylinder	E32-D12R
			48						Flat shape	E32-D15XR
			48						M6 screw, with sleeve	E32-DC200BR E32-DC200B4R
			49						6-dia. cylinder, side-view	E32-D14LR
			49						Flat shape, side-view	E32-D15YR
			49						Flat shape, flat-view	E32-D15ZR
	Small size		48						M4 screw (small)	E32-D211R
			48						M3 screw (small)	E32-D21R
			48						3-dia. cylinder (small)	E32-D22R
			48						Flat panel (small)	E32-D25XR
			48						M3 screw (small), with sleeve	E32-DC200FR E32-DC200F4R
			49						2-dia. cylinder (small), side-view	E32-D24R
			49						Flat shape (small), side-view	E32-D25YR
			49						Flat shape (small), flat-view	E32-D25ZR

\*1. The sensing distances are for white paper.

\*2. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.
















\*3. Free-cut Indicates models that allow free cutting.

R Flexible 
 B Break-resistant 
 U Fluororesin coating



# Standard models

  High-resolution mode 
   Standard mode 
   High-speed mode 
   Super-high-speed mode 
 \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).

Type	Appearance (mm) *3	Dimen- sions page	Sensing distance (mm) *1		(Min. sens- ing object) (mm) *2	Min. bending radius (mm)	Features	Model number	
Standard	Standard size	 Free-cut M6	48	<div><div></div><div></div><div></div></div> 500 300 200 (90)		(0.005 dia.)	M6 screw	E32-DC200	
		 Free-cut 3 dia.	48	<div><div></div><div></div><div></div></div> 400 230 160 (70)			3-dia. cylinder	E32-D12	
		 Free-cut 15 x 10 x 3	48				Flat shape	E32-D15X	
		 Free-cut ( ): E32-DC200B4 Sleeve cannot be bent. M6 2.5 dia.	48	<div><div></div><div></div><div></div></div> 500 300 200 (90)			M6 screw, with sleeve	E32-DC200B E32-DC200B4	
		 Free-cut 6 dia.	49	<div><div></div><div></div><div></div></div> 200 110 80 (36)			6-dia. cylinder, side-view	E32-D14L	
		 Free-cut 15 x 10 x 3	49	<div><div></div><div></div><div></div></div> 170 100			Flat shape, side-view	E32-D15Y	
		 Free-cut 15 x 10 x 3	49	<div><div></div><div></div><div></div></div> 65 (30)			Flat shape, flat-view	E32-D15Z	
	Small size	 Free-cut M4	48				(0.005 dia.)	M4 screw (small)	E32-D211
		 Free-cut M3	48					M3 screw (small)	E32-DC200E
		 Free-cut 3 dia.	48	<div><div></div><div></div><div></div></div> 130 80 50 (22)				3-dia. cylinder (small)	E32-D22
		 Free-cut 12 x 8 x 2	48					Flat shape (small)	E32-D25X
		 Free-cut ( ): E32-DC200F4 Min. bending radius of sleeve: 5 M3 1.2 dia.	48					M3 screw (small), with sleeve	E32-DC200F E32-DC200F4
		 Free-cut 2 dia.	49	<div><div></div><div></div><div></div></div> 50 30 20 (8)				2-dia. cylinder (small), side-view	E32-D24
		 Free-cut 12 x 8 x 2	49	<div><div></div><div></div><div></div></div> 35 20				Flat shape (small), side-view	E32-D25Y
		 Free-cut 12 x 8 x 2	49	<div><div></div><div></div><div></div></div> 12 (6)				Flat shape (small), flat-view	E32-D25Z

\*1. The sensing distances are for white paper.

\*2. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.









\*3.  Indicates models that allow free cutting.

R Flexible 
 B Break-resistant 
 U Fluororesin coating

# Fiber Units with Reflective Sensors

## Standard models

  High-resolution mode 
   Standard mode 
   High-speed mode 
   Super-high-speed mode 
 \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).

Type	Appearance (mm) *3	Dimensions page	Sensing distance (mm) *1			(Min. sensing object) (mm) *2	Min. bending radius (mm)	Features	Model number
Break-resistant	<div>Free-cut</div> 	50	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;"> </span> 300	<span style="background-color: #ff66ff; border: 1px solid black; padding: 2px;"> </span> 170	<span style="background-color: #ff99ff; border: 1px solid black; padding: 2px;"> </span> 120 (50)	(0.005 dia.)	<b>B</b> R4	M6 screw	E32-D11
	<div>Free-cut</div> 	50						Flat shape	E32-D15XB
	<div>Free-cut</div> 	50	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;"> </span> 110	<span style="background-color: #ff66ff; border: 1px solid black; padding: 2px;"> </span> 70	<span style="background-color: #ff99ff; border: 1px solid black; padding: 2px;"> </span> 45 (20)			M4 screw (small)	E32-D21B
	<div>Free-cut</div> 	50						3-dia. cylinder (small)	E32-D221B
	<div>Free-cut</div> 	50	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;"> </span> 50	<span style="background-color: #ff66ff; border: 1px solid black; padding: 2px;"> </span> 30	<span style="background-color: #ff99ff; border: 1px solid black; padding: 2px;"> </span> 20 (8)			M3 screw (small)	E32-D21
	<div>Free-cut</div> 	50						1.5-dia. cylinder (small)	E32-D22B
	<div>Free-cut</div> 	50	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;"> </span> 85	<span style="background-color: #ff66ff; border: 1px solid black; padding: 2px;"> </span> 50	<span style="background-color: #ff99ff; border: 1px solid black; padding: 2px;"> </span> 30 (15)			Flat shape (small)	E32-D25XB
	<div>Free-cut</div> 	50	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;"> </span> 300	<span style="background-color: #ff66ff; border: 1px solid black; padding: 2px;"> </span> 170	<span style="background-color: #ff99ff; border: 1px solid black; padding: 2px;"> </span> 120 (50)			M6 screw, fluorine coating	E32-D11U
Coating							<b>U</b> R4		

\*1. The sensing distances are for white paper.







\*2. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.

\*3. Free-cut Indicates models that allow free cutting.

R Flexible 
 B Break-resistant 
 U Fluororesin coating

## Special-beam models

High-resolution mode 
  Standard mode 
  High-speed mode 
  Super-high-speed mode 
 \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).

Type	Appearance (mm) *3	Dimensions page	Sensing distance (mm) *1	(Min. sensing object) (mm) *2	Min. bending radius (mm)	Features	Model number
Long-distance, high-power		51	<div style="background-color: #ff00ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> 40 to 1,000 <div style="background-color: #ff66ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> 40 to 700 <div style="background-color: #ff99ff; width: 100px; height: 10px;"></div> 40 to 450 (40 to 240)	---	<div style="border: 1px solid black; border-radius: 50%; width: 20px; height: 20px; display: flex; align-items: center; justify-content: center;"> <div style="background-color: yellow; border-radius: 50%; width: 10px; height: 10px; display: flex; align-items: center; justify-content: center;">B</div> </div> R4	Large built-in lens, screw mounting	E32-D16
		51	<div style="background-color: #ff00ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> 650 <div style="background-color: #ff66ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> 400 <div style="background-color: #ff99ff; width: 100px; height: 10px;"></div> 260 (110)	(0.005 dia.)	R25	M6 screw	E32-D11L
		51	<div style="background-color: #ff00ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> 210 <div style="background-color: #ff66ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> 130 <div style="background-color: #ff99ff; width: 100px; height: 10px;"></div> 80 (35)		R10	M4 screw	E32-D21L
		51	<div style="background-color: #ff00ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> 80 (35)			3-dia. cylinder	E32-D22L
Ultracompact, thin-sleeve		51	<div style="background-color: #ff00ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> 25 <div style="background-color: #ff66ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> 16 <div style="background-color: #ff99ff; width: 100px; height: 10px;"></div> 10 (4)	(0.005 dia.)	R4	0.8-dia. sleeve	E32-D33
		51	<div style="background-color: #ff00ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> 5 <div style="background-color: #ff66ff; width: 100px; height: 10px; margin-bottom: 2px;"></div> 3 <div style="background-color: #ff99ff; width: 100px; height: 10px;"></div> 2 (0.8)			0.5-dia. sleeve	E32-D331


















\*1. The sensing distances are for white paper.

\*2. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.

\*3. Free-cut Indicates models that allow free cutting.

# Fiber Units with Reflective Sensors Special-beam models

High-resolution mode Standard mode High-speed mode Super-high-speed mode \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).

Type	Appearance (mm) *3	Dimensions page	Sensing distance (mm) *1	(Min. sensing object) (mm) *2	Min. bending radius (mm)	Features	Model number
Coaxial, small-spot		52	280 170 160 (50)				M6 right angle E32-C11N
		52	40 25 23 (7)				M3 right angle E32-C31N
		52	250 150 100 (45)				M6 screw E32-CC200R
		52	500 300 200 (90)				E32-CC200
		52	250 150 100 (45)				3-dia. cylinder E32-D32L
		52	120 75 50 (22)				M3 screw (small) E32-C31
		52					2-dia. cylinder (small) E32-D32
		52 60	6 to 15 mm; spot diameter: 0.1 to 0.6 mm				Small spot (variable) E32-C42+ E39-F3A
		52 60	Spot diameter of 0.5 to 1 mm at distances in the range 6 to 15 mm				E32-D32+ E39-F3A
		52 60	Spot diameter of 0.1 mm at 7 mm				Small spot E32-C41+ E39-F3A-5
		52 60	Spot diameter of 0.5 mm at 7 mm				E32-C31+ E39-F3A-5
		52 60	Spot diameter of 0.2 mm at 17 mm				Long distance, small spot E32-C41+ E39-F3B
		52 60	Spot diameter of 0.5 mm at 17 mm				E32-C31+ E39-F3B
		52 60	Spot diameter of 4 mm max. at distances in the range 0 to 20 mm				Long-distance sensing, parallel light E32-C31+ E39-F3C
Area-sensing		53	250 150 100 (45)				Beam width: 11 mm E32-D36P1
Retroreflective		53	10 to 250 10 to 250 10 to 250 (10 to 250)				M6 screw E32-R21+ E39-R3 (Attached)
		53	150 to 1,500 150 to 1,500 150 to 1,500 (150 to 1,500)				Screw mounting, long distance E32-R16+ E39-R1 (Attached)

\*1. The sensing distances are for white paper.









\*2. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.

\*3. Free-cut Indicates models that allow free cutting.

R Flexible B Break-resistant U Fluororesin coating

## Special-beam models

  High-resolution mode 
   Standard mode 
   High-speed mode 
   Super-high-speed mode 
 \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).

Type	Appearance (mm) *3	Dimensions page	Sensing distance (mm) *1				(Min. sensing object) (mm) *2	Min. bending radius (mm)	Features	Model number
Convergent-reflective		54	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">3.3</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">3.3</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">3.3</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">3.3</span>	(0.005 dia.)	R25	Small level differences, high power, side-view	E32-L25
		54	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">3.3</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">3.3</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">3.3</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">3.3</span>			Small level differences, top-view	E32-L25A
		54	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">0 to 4</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">0 to 4</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">0 to 4</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">0 to 4</span>		R10	Ultracompact, flat-view	E32-L24S
		54	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">2 to 6 (center: 4)</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">2 to 6 (center: 4)</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">2 to 6 (center: 4)</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">2 to 6 (center: 4)</span>			Heat resistant up to 105°C *4, top-view	E32-L24L
		54	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">5.4 to 9 (center: 7.2)</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">5.4 to 9 (center: 7.2)</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">5.4 to 9 (center: 7.2)</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">5.4 to 9 (center: 7.2)</span>			Heat resistant up to 105°C *4, top-view	E32-L25L
		55	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">4 to 10</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">4 to 10</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">4 to 10</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">4 to 10</span>	Soda glass with reflection factor of 7%	R25	Heat resistant up to 200°C, flat-view	E32-L86
		55	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">1 to 5</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">1 to 5</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">1 to 5</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">1 to 5</span>			Heat resistant up to 300°C	E32-L64
		55	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">0 to 8</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">0 to 8</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">0 to 6</span>	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;">0 to 4</span>			Ideal for detecting glass stock.	E32-A10

\*1. The sensing distances are for white paper.







\*2. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.

\*3. Free-cut Indicates models that allow free cutting.

\*4. For continuous operation, use the products within a temperature range of -40°C to 90°C.

# Fiber Units with Reflective Sensors Environment-resistant models

  High-resolution mode 
   Standard mode 
   High-speed mode 
   Super-high-speed mode 
 \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).

Type	Appearance (mm) *3	Dimensions page	Sensing distance (mm) *1	(Min. sensing object) (mm) *2	Min. bending radius (mm)	Features	Model number
Heat-resistant	150°C *4 	56	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;"> </span> 400 <span style="background-color: #ff66ff; border: 1px solid black; padding: 2px;"> </span> 230 <span style="background-color: #ff99ff; border: 1px solid black; padding: 2px;"> </span> 160 (72)	(0.005 dia.)	R35	Heat resistant up to 150°C	E32-D51
	200°C *5 	56	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;"> </span> 150 <span style="background-color: #ff66ff; border: 1px solid black; padding: 2px;"> </span> 90 <span style="background-color: #ff99ff; border: 1px solid black; padding: 2px;"> </span> 60 (27)		R10	Heat resistant up to 200°C	E32-D81R-S E32-D81R*6
	350°C *5 	56			R25	Heat resistant up to 350°C	E32-D61-S E32-D61*6
	400°C *5 	56	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;"> </span> 100 <span style="background-color: #ff66ff; border: 1px solid black; padding: 2px;"> </span> 60 <span style="background-color: #ff99ff; border: 1px solid black; padding: 2px;"> </span> 40 (18)			Heat resistant up to 400°C, with sleeve	E32-D73-S E32-D73*6
Chemical-resistant		56	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;"> </span> 160 <span style="background-color: #ff66ff; border: 1px solid black; padding: 2px;"> </span> 95 <span style="background-color: #ff99ff; border: 1px solid black; padding: 2px;"> </span> 65 (30)	(0.005 dia.)	R40	Fluororesin cover, long distance	E32-D12F
		56	<span style="background-color: #ff00ff; border: 1px solid black; padding: 2px;"> </span> 70 <span style="background-color: #ff66ff; border: 1px solid black; padding: 2px;"> </span> 40 <span style="background-color: #ff99ff; border: 1px solid black; padding: 2px;"> </span> 30 (10)			Fluororesin cover, side-view	E32-D14F

- \*1. The sensing distances are for white paper.
- \*2. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.
- \*3. Free-cut Indicates models that allow free cutting.
- \*4. For continuous operation, use the products within a temperature range of -40°C to 90°C.
- \*5. The maximum temperature that can be withstood varies with the location. Refer to dimensions diagrams for details.
- \*6. Order the Fiber Unit based on the Amplifier Unit. Use the E32-D□-S if the E3X-DA□-S, E3X-MDA□, or E3X-DAC□-S is used. Use the E32-D□ if any other Amplifier is used.












R Flexible 
 B Break-resistant 
 U Fluororesin coating



# Ordering Information

## Application-corresponding Fiber Units

■ High-resolution mode 
 ■ Standard mode 
 ■ High-speed mode 
 ■ Super-high-speed mode 
 \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).

Type	Appearance (mm) *2	Dimensions page	Sensing distance (mm)			Standard object (min. sensing object) (mm)*1	Min. bending radius (mm)	Features	Model number
Label-detection		57	10 10 10 (10)			4 dia. (0.1 dia.)	R25	Slot sensor (no adjustment of optical axis required)	E32-G14
		43							Screw mounting, side-view
Liquid-level detection		57	Applicable tube: Transparent tube with a diameter in the range 8 to 10 mm and a recommended wall thickness of 1 mm				R10	Compact	E32-L25T
		57	Applicable tube: Transparent tube (no restriction on diameter)				R4	No restriction on tube diameter, resistant to bubbles and drops of water	E32-D36T
		58	Applicable tube: Transparent tube with a diameter of 3.2, 6.4, or 9.5 mm and a recommended wall thickness of 1 mm					Light ON when fluid is present, resistant to bubbles and drops of water	E32-A01
		58	Applicable tube: Transparent tube with a diameter in the range 6 to 13 mm and a recommended wall thickness of 1 mm					Light ON when fluid is not present, resistant to bubbles and drops of water	E32-A02
		58	Liquid-contact models				R40	Heat resistant up to 200°C, fluororesin cover	E32-D82F1 E32-D82F2
Glass-substrate-alignment		54	0 to 15 0 to 15 0 to 15 (0 to 12)			Soda glass with reflection factor of 7%	R25	Variation of detection position within the detection range: 0.1 mm	E32-L16-N
		58	10 to 20 10 to 20 10 to 20 (-)						E32-A08
		58	15 to 25 15 to 25 10 to 20 (-)						E32-A07E1*5 E32-A07E2*5
		58	5 to 18 5 to 18 5 to 16 (-)					Heat resistant up to 300°C *3, *4	E32-L66
		54	10 to 20 10 to 20 10 to 20					Heat resistant up to 300°C	E32-A08H2

\*1. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.

\*2. Free-cut Indicates models that allow free cutting.









\*3. The maximum temperature that can be withstood varies with the location. Refer to dimensions diagrams for details.

\*4. These values are based on the assumption that there are no repeated sudden changes in temperature.

\*5. The characteristics for sensing object incline are different between the Attachments with model numbers ending in "E1" and "E2." Refer to page 52 for installation precautions.

# Application-corresponding Fiber Units

  High-resolution mode  
   Standard mode  
   High-speed mode  
   Super-high-speed mode  
 \*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).

Type	Appearance (mm) *2	Dimensions page	Sensing distance (mm)	Standard object (min. sensing object) (mm)*1	Min. bending radius (mm)	Features	Model number
Glass-substrate-mapping		59	<div style="background-color: #ff00ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff99ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100%; height: 10px;"></div>	Edge of soda glass with reflection factor of 7% (t = 0.5 mm, rounded edge)	R25	Resistant to tilting	E32-A09
		59	<div style="background-color: #ff00ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff99ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100%; height: 10px;"></div>		R35	Heat resistant up to 150°C *3	E32-A09H
		59	<div style="background-color: #ff00ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff99ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100%; height: 10px;"></div>		R25	Heat resistant up to 300°C *4, *5	E32-A09H2
Wafer-mapping		59		2 dia. (0.1 dia.)	R1	Opening angle: 1.5°; optical axis adjusted before delivery	E32-A03
		59	<div style="background-color: #ff00ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff99ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100%; height: 10px;"></div>			Opening angle: 1.5°; with mounting flange; optical axis adjusted before delivery	E32-A03-1
		44	<div style="background-color: #ff00ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff99ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100%; height: 10px;"></div>			Long distance; opening angle: 4°	E32-T24S
		59		1.2 dia. (0.1 dia.)	R10	Ultraslim (t = 2 mm); opening angle: 3°; optical axis adjusted before delivery	E32-A04
		59	<div style="background-color: #ff00ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff66ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ff99ff; width: 100%; height: 10px; margin-bottom: 2px;"></div> <div style="background-color: #ffcccc; width: 100%; height: 10px;"></div>			Ultraslim (t = 2 mm); opening angle: 3°; with mounting flange; optical axis adjusted before delivery	E32-A04-1

\*1. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.

\*2. Free-cut Indicates models that allow free cutting.

\*3. For continuous operation, use the products within a temperature range of -40°C to 130°C.

\*4. The maximum temperature that can be withstood varies with the location. Refer to dimensions diagrams for details.








\*5. These values are based on the assumption that there are no repeated sudden changes in temperature.

R Flexible  
 B Break-resistant  
 U Fluororesin coating

Accessories

Lens Units

\*When used in combination with the E3X-DA-S Amplifier Unit (general-purpose).




Type		Appearance	Dimensions page	Applicable Fiber Units	Sensing distance (mm)				Standard object (min. sensing object) (mm) *1	Features	Model number
					High-resolution mode	Standard mode	High-speed mode	Super-high-speed mode			
Through-beam Lens Units	Long-distance Lens Units		60	E32-T11L	4,000*2	3,200	2,100	840	4 dia. (0.1 dia.)	Long-distance sensing; opening angle: 5° to 40° (heat resistant up to 200°C)	E39-F1
				E32-TC200	4,000*2	4,000*2	2,600	1,500			
				E32-T11R	4,000*2	3,700	2,400	970			
				E32-T11	4,000*2	3,600	2,300	930			
				E32-T11U	4,000*2	3,600	2,300	930			
				E32-T81R-S	2,650	2,100	1,300	520			
				E32-T61-S	4,000*2	3,400	2,200	900			
	Side-view Units		60	E32-T11L	910	800	500	180	3 dia. (0.1 dia.)	Side-view, space-saving (heat resistant up to 200°C)	E39-F2
				E32-TC200	840	700	450	160			
				E32-T11R	520	400	250	100			
				E32-T11	820	660	430	160			
				E32-T11U	820	660	430	160			
				E32-T81R-S	360	280	180	70			
				E32-T61-S	600	450	300	120			
	Reflection Units		60	E32-T11L E32-TC200 E32-T11R E32-T11 E32-T11U E32-T81R-S E32-T61-S	---				---	Long distance reflection (heat resistant up to 200°C)	E39-F3
Reflective Lens Units	Small-spot Lens Units		60	E32-C42	Spot diameter variable in the range 0.1 to 0.6 mm at distances in the range 6 to 15 mm				Small spot (variable)	E39-F3A	
				E32-D32	Spot diameter variable in the range 0.5 to 1 mm at distances in the range 6 to 15 mm						
		60	E32-C41	0.1-dia. spot at a distance of 7 mm				Small spot	E39-F3A-5		
			E32-C31	0.5-dia. spot at a distance of 7 mm							
		60	E32-C41	0.2-dia. spot at a distance of 17 mm				Long distance, small spot	E39-F3B		
			E32-C31	0.5-dia. spot at a distance of 17 mm							
		60	E32-C31 E32-C41	Spot diameter of 4 mm max. at distances in the range 0 to 20 mm				Long-distance sensing, parallel light	E39-F3C		

\*1. The values for the minimum sensing object are representative values that indicate values obtained in standard mode with the sensing distance and sensitivity set to optimum values.

\*2. The optical fiber is 2 m long on each side, so the sensing distance is 4,000 mm.







## Accessories

### Protective Spiral Tube

Appearance	Dimen- sions page	Application	Applicable Fiber Units	Tube length	Model number
	61	Fiber protection	M3-screw models E32-D21/E32-D21R E32-DC200E E32-DC200F□ E32-C31	500 mm	E39-F32A5
				1 m	E39-F32A
			M3-screw models E32-T21□ (Except the E32-T21R.) E32-TC200E E32-TC200F□	500 mm	E39-F32B5
				1 m	E39-F32B
	61		M4-screw models E32-T11□ (except the E32-T11N Right-angle Model) E32-TC200 E32-TC200B□ E32-T51 E32-D21L/E32-D21B	500 mm	E39-F32C5
				1 m	E39-F32C
	61		M6-screw models E32-D11□ (except the E32-D11N Right-angle Model) E32-DC200 E32-DC200B E32-CC200□ E32-D51	500 mm	E39-F32D5
				1 m	E39-F32D

Note: Before using a Protective Spiral Tube, remove the protective tube that protects the area between the head and the optical fiber provided with some models. The Lens Unit and Spiral Tube cannot be used at the same time.

### Other Accessories

Appearance	Dimensions page	Application	Name	Applicable Fiber Units	Remarks	Model number
	62	Used to cut the fiber.	Cutter	Fiber Units that allow free cutting	Provided with applicable Fiber Units.	E39-F4
	62	Attachments for inserting thin fibers into Amplifier Units	Thin-fiber Attachments	Fiber Units that allow free cutting and have a 1.0-dia. sheath	<ul style="list-style-type: none"> <li>• 2 per set</li> <li>• Provided with applicable Fiber Units.</li> </ul>	E39-F9
	62	Used to extend fibers.		Fiber Units that allow free cutting and have a 2.2-dia. sheath	---	E39-F10
	62	Easy-to-use, one-touch relay connectors	Fiber Connectors	Fiber Units that allow free cutting	E39-F13: Used for Fiber Units with a 2.2-dia. sheath. E39-F14: Used for Fiber Units with a 1.0-dia. sheath. E39-F15: Used to connect Fiber Units with different sheath diameters, 1.0 mm and 2.2 mm.	E39-F13 E39-F14 E39-F15
	62	Used to bends in sleeves.	Sleeve Bender	E32-TC200B(4) E32-TC200F(4) E32-DC200F(4)	---	E39-F11
	62	Used to secure the 3.5-dia. Fiber Head	Mounting Bracket	E32-T24S E32-A03	Provided with applicable Fiber Units.	E39-L83

## Ratings/Characteristics

## Standard models

Models	Ambient operating temperature range	Ambient humidity range	Fiber core material (sheath material)	Permissible bending radius	Tightening force (N·m)	Pulling force (N)	IEC standard degree of protection
E32-D11	-40 to +70°C	35% to 85%	Plastic (PVC coating)	R4	0.98	29.4	IP67
E32-D11N			Plastic (PVC coating)	R1	0.98	29.4	IP67
E32-D11R			Plastic (PVC coating)	R1	0.98	29.4	IP67
E32-D11U			Plastic (fluororesin coating)	R4	0.98	29.4	IP67
E32-D12			Plastic (polyethylene coating)	R25	0.29	29.4	IP67
E32-D12R			Plastic (PVC coating)	R1	0.29	29.4	IP67
E32-D14L			Plastic (polyethylene coating)	R25	0.98	29.4	IP67
E32-D14LR			Plastic (PVC coating)	R1	0.98	29.4	IP67
E32-D15X			Plastic (polyethylene coating)	R25	0.15	29.4	IP67
E32-D15XB			Plastic (PVC coating)	R4	0.15	29.4	IP67
E32-D15XR			Plastic (PVC coating)	R1	0.15	29.4	IP67
E32-D15Y			Plastic (polyethylene coating)	R25	0.15	29.4	IP40
E32-D15YR			Plastic (PVC coating)	R1	0.15	29.4	IP40
E32-D15Z			Plastic (polyethylene coating)	R25	0.15	29.4	IP40
E32-D15ZR			Plastic (PVC coating)	R1	0.15	29.4	IP40
E32-D21			Plastic (PVC coating)	R4	0.78	9.8	IP67
E32-D211			Plastic (polyethylene coating)	R10	0.78	9.8	IP67
E32-D211R			Plastic (polyethylene coating)	R1	0.78	9.8	IP67
E32-D21B			Plastic (PVC coating)	R4	0.78	9.8	IP67
E32-D21R			Plastic (polyethylene coating)	R1	0.78	9.8	IP67
E32-D22			Plastic (polyethylene coating)	R10	0.29	9.8	IP67
E32-D221B			Plastic (PVC coating)	R4	0.29	9.8	IP67
E32-D22B			Plastic (PVC coating)	R4	0.20	9.8	IP67
E32-D22R			Plastic (polyethylene coating)	R1	0.29	9.8	IP67
E32-D24			Plastic (polyethylene coating)	R10	0.29	9.8	IP67
E32-D24R			Plastic (polyethylene coating)	R1	0.29	9.8	IP67
E32-D25X			Plastic (polyethylene coating)	R10	0.15	9.8	IP67
E32-D25XB			Plastic (PVC coating)	R4	0.15	9.8	IP67
E32-D25XR			Plastic (polyethylene coating)	R1	0.15	9.8	IP67
E32-D25Y			Plastic (polyethylene coating)	R10	0.15	9.8	IP40
E32-D25YR			Plastic (polyethylene coating)	R1	0.15	9.8	IP40
E32-D25Z			Plastic (polyethylene coating)	R10	0.15	9.8	IP40
E32-D25ZR			Plastic (polyethylene coating)	R1	0.15	9.8	IP40
E32-DC200			Plastic (polyethylene coating)	R25	0.98	29.4	IP67
E32-DC200B(B4)			Plastic (polyethylene coating)	R25	0.98	29.4	IP67
E32-DC200BR(B4R)			Plastic (PVC coating)	R1	0.98	29.4	IP67
E32-DC200E			Plastic (polyethylene coating)	R10	0.78	9.8	IP67
E32-DC200F(F4)			Plastic (polyethylene coating)	R10	0.78	9.8	IP67
E32-DC200FR(F4R)			Plastic (polyethylene coating)	R1	0.78	9.8	IP67
E32-T11			Plastic (PVC coating)	R4	0.78	29.4	IP67
E32-T11N			Plastic (PVC coating)	R1	0.78	29.4	IP67
E32-T11R			Plastic (PVC coating)	R1	0.78	29.4	IP67
E32-T11U			Plastic (fluororesin coating)	R4	0.78	29.4	IP67
E32-T12			Plastic (polyethylene coating)	R25	0.29	29.4	IP67
E32-T12B			Plastic (PVC coating)	R4	0.29	29.4	IP67
E32-T12R			Plastic (PVC coating)	R1	0.29	29.4	IP67
E32-T14L			Plastic (polyethylene coating)	R25	0.29	29.4	IP67
E32-T14LR			Plastic (PVC coating)	R1	0.29	29.4	IP67
E32-T15X			Plastic (polyethylene coating)	R25	0.15	29.4	IP67
E32-T15XB			Plastic (PVC coating)	R4	0.15	29.4	IP67
E32-T15XR			Plastic (PVC coating)	R1	0.15	29.4	IP67
E32-T15Y			Plastic (polyethylene coating)	R25	0.15	29.4	IP40
E32-T15YR			Plastic (PVC coating)	R1	0.15	29.4	IP40
E32-T15Z			Plastic (polyethylene coating)	R25	0.15	29.4	IP40
E32-T15ZR			Plastic (PVC coating)	R1	0.15	29.4	IP40
E32-T21			Plastic (PVC coating)	R4	0.78	9.8	IP67
E32-T21R			Plastic (polyethylene coating)	R1	0.78	29.4	IP67
E32-T22			Plastic (polyethylene coating)	R10	0.29	9.8	IP67
E32-T221B			Plastic (PVC coating)	R4	0.29	9.8	IP67
E32-T222			Plastic (polyethylene coating)	R10	0.20	9.8	IP67
E32-T222R			Plastic (polyethylene coating)	R1	0.20	9.8	IP67
E32-T22B			Plastic (PVC coating)	R4	0.20	9.8	IP67
E32-T22R			Plastic (polyethylene coating)	R1	0.29	9.8	IP67

## Standard models (continued)

Models	Ambient operating temperature range	Ambient humidity range	Fiber core material (sheath material)	Permissible bending radius	Tightening force (N·m)	Pulling force (N)	IEC standard degree of protection
E32-T24	-40 to +70°C	35% to 85%	Plastic (polyethylene coating)	R10	0.29	9.8	IP67
E32-T24R			Plastic (polyethylene coating)	R1	0.29	9.8	IP67
E32-T25X			Plastic (polyethylene coating)	R10	0.15	9.8	IP67
E32-T25XB			Plastic (PVC coating)	R4	0.15	9.8	IP67
E32-T25XR			Plastic (polyethylene coating)	R1	0.15	9.8	IP67
E32-T25Y			Plastic (polyethylene coating)	R10	0.15	9.8	IP40
E32-T25YR			Plastic (polyethylene coating)	R1	0.15	9.8	IP40
E32-T25Z			Plastic (polyethylene coating)	R10	0.15	9.8	IP40
E32-T25ZR			Plastic (polyethylene coating)	R1	0.15	9.8	IP40
E32-TC200			Plastic (polyethylene coating)	R25	0.78	29.4	IP67
E32-TC200A			Plastic (polyethylene coating)	R25	0.78	29.4	IP67
E32-TC200B(B4)			Plastic (polyethylene coating)	R25	0.78	29.4	IP67
E32-TC200BR(B4R)			Plastic (PVC coating)	R1	0.78	29.4	IP67
E32-TC200E			Plastic (polyethylene coating)	R10	0.78	9.8	IP67
E32-TC200F(F4)			Plastic (polyethylene coating)	R10	0.78	9.8	IP67
E32-TC200FR(F4R)			Plastic (polyethylene coating)	R1	0.78	9.8	IP67

## Special-beam models

Models	Ambient operating temperature range	Ambient humidity range	Fiber core material (sheath material)	Permissible bending radius	Tightening force (N·m)	Pulling force (N)	IEC standard degree of protection
E32-A10	-40 to +70°C	35% to 85%	Plastic (polyethylene coating)	R25	0.53	29.4	IP30
E32-C11N	-40 to +70°C		Plastic (combination of PVC and polyethylene)	R4	0.98	29.4	IP67
E32-C31	-40 to +70°C		Plastic (polyethylene coating)	R25	0.78	9.8	IP67
E32-C31N	-40 to +70°C		Plastic (combination of PVC and polyethylene)	R4	0.29	9.8	IP67
E32-C41	-40 to +70°C		Plastic (polyethylene coating)	R25	0.78	9.8	IP67
E32-C42	-40 to +70°C		Plastic (polyethylene coating)	R25	0.29	9.8	IP67
E32-CC200	-40 to +70°C		Plastic (polyethylene coating)	R25	0.98	29.4	IP67
E32-CC200R	-40 to +70°C		Plastic (polyethylene coating)	R4	0.98	29.4	IP67
E32-D11L	-40 to +70°C		Plastic (polyethylene coating)	R25	0.98	29.4	IP67
E32-D16	-40 to +70°C		Plastic (PVC coating)	R4	0.53	29.4	IP40
E32-D21L	-40 to +70°C		Plastic (polyethylene coating)	R10	0.78	9.8	IP67
E32-D22L	-40 to +70°C		Plastic (polyethylene coating)	R10	0.29	9.8	IP67
E32-D32	-40 to +70°C		Plastic (polyethylene coating)	R25	0.29	9.8	IP67
E32-D32L	-40 to +70°C		Plastic (polyethylene coating)	R25	0.29	29.4	IP67
E32-D33	-40 to +70°C		Plastic (polyethylene coating)	R4	0.29	9.8	IP67
E32-D331	-40 to +70°C		Plastic (polyethylene coating)	R4	0.29	9.8	IP67
E32-D36P1	-40 to +70°C		Plastic (polyethylene coating)	R4	0.78	29.4	IP67
E32-L24L	-40 to +105°C		Plastic (polyethylene coating)	R10	0.29	9.8	IP50
E32-L24S	-40 to +70°C		Plastic (polyethylene coating)	R10	0.29	9.8	IP40
E32-L25	-40 to +70°C		Plastic (polyethylene coating)	R25	0.29	19.6	IP50
E32-L25A	-40 to +70°C		Plastic (polyethylene coating)	R25	0.29	19.6	IP50
E32-L25L	-40 to +105°C		Plastic (polyethylene coating)	R10	0.29	9.8	IP50
E32-L64	-40 to +300°C		Glass (SUS spiral coating)	R25	0.54	9.8	IP50
E32-L86	-40 to +200°C		Glass (SUS spiral coating)	R25	0.54	9.8	IP40
E32-M21	-40 to +70°C		Plastic (PVC coating)	R25	0.49. 0.78*	9.8	IP50
E32-R16	-25 to +55°C		Plastic (polyethylene coating)	R25	0.54	29.4	IP66
E32-R21	-40 to +70°C		Plastic (polyethylene coating)	R10	0.39	9.8	IP67
E32-T11L	-40 to +70°C		Plastic (polyethylene coating)	R25	0.78	29.4	IP67
E32-T12L	-40 to +70°C		Plastic (polyethylene coating)	R25	0.29	29.4	IP67
E32-T14	-40 to +70°C		Plastic (polyethylene coating)	R25	0.49	29.4	IP67
E32-T16	-40 to +70°C		Plastic (polyethylene coating)	R25	0.49	29.4	IP67
E32-T16J	-40 to +70°C		Plastic (PVC coating)	R10	0.29	29.4	IP50
E32-T16JR	-40 to +70°C		Plastic (PVC coating)	R1	0.29	29.4	IP50
E32-T16P	-40 to +70°C		Plastic (PVC coating)	R10	0.29	29.4	IP50
E32-T16PR	-40 to +70°C		Plastic (PVC coating)	R1	0.29	29.4	IP50
E32-T16W	-25 to +55°C		Plastic (PVC coating)	R10	0.29	9.8	IP50
E32-T16WR	-25 to +55°C		Plastic (PVC coating)	R1	0.29	9.8	IP50
E32-T17L	-40 to +70°C		Plastic (polyethylene coating)	R25	0.78	29.4	IP67
E32-T21L	-40 to +70°C		Plastic (polyethylene coating)	R10	0.78	9.8	IP67
E32-T223R	-40 to +70°C		Plastic (polyethylene coating)	R1	0.20	9.8	IP67
E32-T22L	-40 to +70°C		Plastic (polyethylene coating)	R10	0.29	9.8	IP67
E32-T22S	-40 to +70°C		Plastic (PVC coating)	R10	0.29	29.4	IP50
E32-T24S	-40 to +70°C		Plastic (PVC coating)	R10	0.29	29.4	IP50
E32-T333-S5	-40 to +70°C		Plastic (polyethylene coating)	R10	0.29	9.8	IP67
E32-T334-S5	-40 to +70°C		Plastic (polyethylene coating)	R10	0.29	9.8	IP67
E32-T33-S5	-40 to +70°C		Plastic (PVC coating)	R10	0.29	9.8	IP67

\*The strength depends on the section. Use 0.49 N·m max. to 5 mm from the tip and 0.78 N·m max. at a distance of more than 5 mm from the tip.



## Environment-resistant models

Models	Ambient operating temperature range	Ambient humidity range	Fiber core material (sheath material)	Permissible bending radius	Tightening force (N·m)	Pulling force (N)	IEC standard degree of protection
E32-D12F	-40 to +70°C	35% to 85%	Plastic (fluororesin coating)	R40	0.78	29.4	IP67
E32-D14F	-40 to +70°C		Plastic (fluororesin coating)	R40	0.78	29.4	IP67
E32-D51	-40 to +150°C		Plastic (fluororesin coating)	R35	0.98	29.4	IP67
E32-D61	-60 to +350°C		Glass (SUS spiral coating)	R25	0.98	29.4	IP67
E32-D61-S	-60 to +350°C		Glass (SUS spiral coating)	R25	0.98	29.4	IP67
E32-D73	-40 to +400°C		Glass (SUS spiral coating)	R25	0.78	29.4	IP67
E32-D73-S	-40 to +400°C		Glass (SUS spiral coating)	R25	0.78	29.4	IP67
E32-D81R	-40 to +200°C		Glass (fluororesin coating)	R10	0.78	9.8	IP67
E32-D81R-S	-40 to +200°C		Glass (fluororesin coating)	R10	0.78	9.8	IP67
E32-T11F	-40 to +70°C		Plastic (fluororesin coating)	R4	0.29	29.4	IP67
E32-T12F	-40 to +70°C		Plastic (fluororesin coating)	R40	0.78	29.4	IP67
E32-T14F	-40 to +70°C		Plastic (fluororesin coating)	R40	0.78	29.4	IP67
E32-T51	-40 to +150°C		Plastic (fluororesin coating)	R35	0.78	29.4	IP67
E32-T51F	-40 to +150°C		Plastic (fluororesin coating)	R40	0.78	29.4	IP67
E32-T51V	-25 to +120°C		Glass (fluororesin coating)	R30	0.29	29.4	---
E32-T54	-40 to +150°C		Plastic (fluororesin coating)	R35	0.29	29.4	IP67
E32-T54V	-25 to +120°C		Glass (fluororesin coating)	R30	0.29	29.4	---
E32-T61-S	-60 to +350°C		Glass (SUS spiral coating)	R25	0.78	29.4	IP67
E32-T81F-S	-40 to +200°C		Glass (fluororesin coating)	R10	0.78	9.8	IP67
E32-T81R-S	-40 to +200°C		Glass (fluororesin coating)	R10	0.78	9.8	IP67
E32-T84S-S	-40 to +200°C		Glass (fluororesin coating)	R25	0.29	9.8	IP67
E32-T84SV	-25 to +200°C		Glass (SUS spiral coating)	R25	0.29	29.4	---

## Application-corresponding models

Models	Ambient operating temperature range	Ambient humidity range	Fiber core material (sheath material)	Permissible bending radius	Tightening force (N·m)	Pulling force (N)	IEC standard degree of protection
E32-A01	-40 to +70°C	35% to 85%	Plastic (fluororesin coating)	R4	---	9.8	IP50
E32-A02	-40 to +70°C		Plastic (fluororesin coating)	R4	---	9.8	IP50
E32-A03	-40 to +70°C		Plastic (polyethylene coating)	R1	0.29	9.8	IP50
E32-A03-1	-40 to +70°C		Plastic (polyethylene coating)	R10	0.29	9.8	IP50
E32-A04	-40 to +70°C		Plastic (polyethylene coating)	R10	0.29	9.8	IP50
E32-A04-1	-40 to +70°C		Plastic (polyethylene coating)	R10	0.29	9.8	IP50
E32-A07E1(E2)	-40 to +70°C		Plastic (polyethylene coating)	R25	0.53	9.8	IP40
E32-A08	-40 to +70°C		Plastic (polyethylene coating)	R25	0.53	9.8	IP40
E32-A08H2	-40 to +300°C		Glass (SUS spiral coating)	R25	0.53	29.4	IP30
E32-A09	-40 to +70°C		Plastic (polyethylene coating)	R25	0.53	9.8	IP40
E32-A09H	-40 to +150°C		Plastic (fluororesin coating)	R35	0.53	9.8	IP40
E32-A09H2	-40 to +300°C		Glass (SUS spiral coating)	R25	0.53	9.8	IP40
E32-D36T	-40 to +70°C		Plastic (polyethylene coating)	R4	---	29.4	IP67
E32-D82F1	-40 to +200°C		Tip: Glass and fluororesin coating Amplifier insert: Plastic (fluororesin coating)	R40	0.29	29.4	IP68
E32-D82F2	-40 to +200°C		(Fluororesin coating)	R40	0.29	29.4	IP68
E32-G14	-40 to +70°C		Plastic (polyethylene coating)	R25	0.49	29.4	IP67
E32-L16-N	-40 to +70°C		Plastic (polyethylene coating)	R25	0.29	29.4	IP40
E32-L25T	-40 to +70°C		Plastic (polyethylene coating)	R10	---	9.8	IP50
E32-L66	-40 to +300°C		Glass (SUS spiral coating)	R25	0.53	9.8	IP40
E32-T14	-40 to +70°C		Plastic (polyethylene coating)	R25	0.49	29.4	IP67













# Dimensions

(Unit: mm)  
Tolerance class IT16 applies to dimensions in this data sheet unless otherwise specified.

**Through-beam Fiber Units** Through-beam models consist of two parts: an emitter and a receiver.

Standard Standard/Flexible Models

**R** Flexible **B** Break-resistant **U** Fluororesin coating **R** Standard  
**Free-cut** Cutting free (Cutter provided)



# Through-beam Fiber Units


Through-beam models consist of two parts: an emitter and a receiver.

## Standard Standard/Flexible Models

**R** Flexible **B** Break-resistant **U** Fluororesin coating **R□** Standard  
**Free-cut** Cutting free (Cutter provided)


E32-T24 **R10**  
E32-T24R **R**

Free-cut



E32-T15Y **R25**  
E32-T15YR **R**


Free-cut



Note: 1. Set of two symmetrical parts.  
2. Mounting screws (countersunk screw M2 × 8 4 pcs) included

E32-T25Y **R10**  
E32-T25YR **R**


Free-cut



Note: 1. Set of two symmetrical parts.  
2. Mounting screws (countersunk screw M2 × 8 4 pcs) included

E32-T15Z **R25**  
E32-T15ZR **R**


Free-cut



Note: 1. Set of two symmetrical parts.  
2. Mounting screws (countersunk screw M2 × 8 4 pcs) included


E32-T25Z **R10**  
E32-T25ZR **R**

Free-cut



Note: 1. Set of two symmetrical parts.  
2. Mounting screws (countersunk screw M2 × 8 4 pcs) included

## Mounting hole dimensions (recommended)



### <Screw-mounting Model>

(Unit:mm)

Outer diameter of fiber unit	M3	M4	M6	M14
F dimensions	3 <sup>+0.5</sup> <sub>0</sub> dia.	4 <sup>+0.5</sup> <sub>0</sub> dia.	6 <sup>+0.5</sup> <sub>0</sub> dia.	14 <sup>+1</sup> <sub>0</sub> dia.

Example: Head size of E32-TC200 is M4. Open the mounting holes with 4 to 4.5 dia.


### <Cylindrical Model>

(Unit:mm)

Outer diameter of fiber unit	1 dia.	1.5 dia.	2 dia.	3 dia.
F dimensions	1.2 <sup>+0.2</sup> <sub>0</sub> dia.	1.7 <sup>+0.2</sup> <sub>0</sub> dia.	2.2 <sup>+0.2</sup> <sub>0</sub> dia.	3.2 <sup>+0.2</sup> <sub>0</sub> dia.
Outer diameter of fiber unit	3.5 dia.	4 dia.	5 dia.	6 dia.
F dimensions	4 <sup>+0.5</sup> <sub>0</sub> dia.	4.5 <sup>+0.5</sup> <sub>0</sub> dia.	5.5 <sup>+0.5</sup> <sub>0</sub> dia.	6.5 <sup>+0.5</sup> <sub>0</sub> dia.

Example: Head size of E32-T22 is 2 dia.. Open the mounting holes with 2.2 to 2.4 dia.

## Minimum bending radius



**R** Flexible **B** Break-resistant **U** Fluororesin coating **R□** Standard  
(Unit:mm)


Type	A Minimum bending radius	B unbendable
(except E32-C11N, E32-C31N and E32-CC200)	1	0
(E32-C11N, E32-C31N, E32-CC200R)	4	0
<b>B</b> <b>U</b> <b>R4</b>	4	10
<b>R10</b>	10	10
<b>R25</b>	25	10
<b>R30</b>	30	10
<b>R35</b>	35	10
<b>R40</b>	40	10

Standard Models Break-resistant/Coated Models

**R** Flexible **B** Break-resistant **U** Fluororesin coating **R** Standard  
**Free-cut** Cutting free (Cutter provided)


E32-T11 **B**  
 E32-T11U **U**

Free-cut




E32-T21 **B**

Free-cut




E32-T12B **B**

Free-cut




E32-T221B **B**

Free-cut




E32-T22B **B**

Free-cut



E32-T15XB **B**


Free-cut



Note: 1. Set of two symmetrical parts.  
 2. Mounting screws (countersunk screw M2 x 8 4 pcs) included

E32-T25XB **B**

Free-cut



Note: 1. Set of two symmetrical parts.  
 2. Mounting screws (countersunk screw M2 x 8 4 pcs) included


# Through-beam Fiber Units

Through-beam models consist of two parts: an emitter and a receiver.

## Special-beam Models Long-distance/High-power Models


R Flexible 
 B Break-resistant 
 U Fluororesin coating 
 R□ Standard 
 Free-cut Cutting free (Cutter provided)

### E32-T17L R25




Free-cut

### E32-T14 R25




Free-cut

### E32-T11L R25




Free-cut

### E32-T12L R25




Free-cut

### E32-T21L R10




Free-cut

### E32-T22L R10



Free-cut

## Mounting hole dimensions (recommended)



### <Screw-mounting Model>

(Unit:mm)

Outer diameter of fiber unit	M3	M4	M6	M14
F dimensions	3 <sup>+0.5</sup> <sub>0</sub> dia.	4 <sup>+0.5</sup> <sub>0</sub> dia.	6 <sup>+0.5</sup> <sub>0</sub> dia.	14 <sup>+1</sup> <sub>0</sub> dia.

Example: Head size of E32-TC200 is M4. Open the mounting holes with 4 to 4.5 dia.


### <Cylindrical Model>

(Unit:mm)

Outer diameter of fiber unit	1 dia.	1.5 dia.	2 dia.	3 dia.
F dimensions	1.2 <sup>+0.2</sup> <sub>0</sub> dia.	1.7 <sup>+0.2</sup> <sub>0</sub> dia.	2.2 <sup>+0.2</sup> <sub>0</sub> dia.	3.2 <sup>+0.2</sup> <sub>0</sub> dia.
Outer diameter of fiber unit	3.5 dia.	4 dia.	5 dia.	6 dia.
F dimensions	4 <sup>+0.5</sup> <sub>0</sub> dia.	4.5 <sup>+0.5</sup> <sub>0</sub> dia.	5.5 <sup>+0.5</sup> <sub>0</sub> dia.	6.5 <sup>+0.5</sup> <sub>0</sub> dia.

Example: Head size of E32-T22 is 2 dia.. Open the mounting holes with 2.2 to 2.4 dia.

## Minimum bending radius



R Flexible 
 B Break-resistant 
 U Fluororesin coating 
 R□ Standard 
 (Unit:mm)

Type	A Minimum bending radius	B unbendable
(except E32-C11N, E32-C31N and E32-CC200)	1	0
(E32-C11N, E32-C31N, E32-CC200R)	4	0
<span style="border: 1px solid black; border-radius: 50%; padding: 2px;">B</span> <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">U</span> <span style="border: 1px solid black; border-radius: 50%; padding: 2px;">R4</span>	4	10
<span style="border: 1px solid black; border-radius: 50%; padding: 2px;">R10</span>	10	10
<span style="border: 1px solid black; border-radius: 50%; padding: 2px;">R25</span>	25	10
<span style="border: 1px solid black; border-radius: 50%; padding: 2px;">R30</span>	30	10
<span style="border: 1px solid black; border-radius: 50%; padding: 2px;">R35</span>	35	10
<span style="border: 1px solid black; border-radius: 50%; padding: 2px;">R40</span>	40	10

# Through-beam Fiber Units


Through-beam models consist of two parts: an emitter and a receiver.

## Special-beam Models Ultracompact/Thin-sleeve Models

**R** Flexible **B** Break-resistant **U** Fluororesin coating **R10** Standard  
**Free-cut** Cutting free (Cutter provided)


E32-T223R **R**

**Free-cut**




E32-T33-S5 **R10**

**Free-cut**




E32-T333-S5 **R10**



\*The Fiber Attachment is attached with adhesive and cannot be removed.

E32-T334-S5 **R10**




\*The Fiber Attachment is attached with adhesive and cannot be removed.

## Special-beam Models Fine-beam (narrow vision field) Models


E32-T22S **R10**

**Free-cut**



E32-T24S **R10**

**Free-cut**




## Special-beam Models Area-sensing Models


E32-T16W **R10**

**Free-cut**

E32-T16WR **R**



E32-M21 **R25**




\*One set of silicon tubes is black and the other set is gray. Use this difference to distinguish between the emission and reception sides.



# Special-beam Models Area-sensing Models


E32-T16P (R10)  
E32-T16PR (R)

(Free-cut)




E32-T16J (R10)  
E32-T16JR (R)

(Free-cut)




E32-T16 (R25)

(Free-cut)



## Mounting hole dimensions (recommended)



### <Screw-mounting Model>

(Unit:mm)

Outer diameter of fiber unit	M3	M4	M6	M14
F dimensions	$3^{+0.5}_{-0}$ dia.	$4^{+0.5}_{-0}$ dia.	$6^{+0.5}_{-0}$ dia.	$14^{+1}_{-0}$ dia.

Example: Head size of E32-TC200 is M4. Open the mounting holes with 4 to 4.5 dia.


### <Cylindrical Model>

(Unit:mm)

Outer diameter of fiber unit	1 dia.	1.5 dia.	2 dia.	3 dia.
F dimensions	$1.2^{+0.2}_{-0}$ dia.	$1.7^{+0.2}_{-0}$ dia.	$2.2^{+0.2}_{-0}$ dia.	$3.2^{+0.2}_{-0}$ dia.
Outer diameter of fiber unit	3.5 dia.	4 dia.	5 dia.	6 dia.
F dimensions	$4^{+0.5}_{-0}$ dia.	$4.5^{+0.5}_{-0}$ dia.	$5.5^{+0.5}_{-0}$ dia.	$6.5^{+0.5}_{-0}$ dia.

Example: Head size of E32-T22 is 2 dia.. Open the mounting holes with 2.2 to 2.4 dia.

## Minimum bending radius



(R) Flexible (B) Break-resistant (U) Fluororesin coating (R□) Standard (Unit:mm)

Type	A Minimum bending radius	B unbendable
(except E32-C11N, E32-C31N and E32-CC200)	1	0
(E32-C11N, E32-C31N, E32-CC200R)	4	0
(B) (U) (R4)	4	10
(R10)	10	10
(R25)	25	10
(R30)	30	10
(R35)	35	10
(R40)	40	10


# Through-beam Fiber Units

Through-beam models consist of two parts: an emitter and a receiver.

## Environment-resistant Models Heat-resistant Models


**R** Flexible **B** Break-resistant **U** Fluororesin coating **R** Standard  
**Free-cut** Cutting free (Cutter provided)

E32-T51 (R35)




Note: The maximum allowable temperature is 150°C. The maximum allowable temperature for continuous operation is 130°C.

E32-T54 (R35)




Note: The maximum allowable temperature is 150°C. The maximum allowable temperature for continuous operation is 130°C.

E32-T81R-S (R10)




Note: The maximum allowable temperatures for sections A and B are 200°C and 110°C, respectively. The section inserted into the Amplifier Unit (indicated by \*), however, must stay within the Amplifier Unit's operating temperature range.

E32-T84S-S (R25)



Note: The maximum allowable temperatures for sections A and B are 200°C and 110°C, respectively. The section inserted into the Amplifier Unit (indicated by \*), however, must stay within the Amplifier Unit's operating temperature range.


E32-T61-S (R25)




Note: The maximum allowable temperatures for sections A and B are 200°C and 110°C, respectively. The section inserted into the Amplifier Unit (indicated by \*), however, must stay within the Amplifier Unit's operating temperature range.

## Environment-resistant Models Chemical-resistant Models


E32-T11F (R4)




E32-T12F (R40)




E32-T14F (R40)



E32-T51F (R40)




E32-T81F-S (R10)




Note: The maximum allowable temperatures for sections A and B are 200°C and 110°C, respectively. The section inserted into the Amplifier Unit (indicated by \*), however, must stay within the Amplifier Unit's operating temperature range.

# Environment-resistant Models Vacuum-resistant Models


## E32-T51V (R30)




## E32-T54V (R30)



## E32-T84SV (R25)




## E39-F1V




Material:  
Aluminum for body and optical glass for the lens itself.

## E32-VF4




- Note 1. Perform mounting so that the V40 O-ring is on the atmospheric-pressure side of the vacuum chamber wall.  
2. Mounting-hole cutout dimensions: 38 dia.  $\pm 0.5$  mm

## E32-VF1




- Note 1. Perform mounting so that the V15 O-ring is on the atmospheric-pressure side of the vacuum chamber wall.  
2. Mounting-hole cutout dimensions: 14.5 dia.  $\pm 0.2$  mm

## E32-T10V-2M (R25)




## E39-L54V



Material: Stainless steel (SUS304)

## Mounting hole dimensions (recommended)



### <Screw-mounting Model>

(Unit:mm)

Outer diameter of fiber unit	M3	M4	M6	M14
F dimensions	$3^{+0.5}_{-0}$ dia.	$4^{+0.5}_{-0}$ dia.	$6^{+0.5}_{-0}$ dia.	$14^{+1}_{-0}$ dia.

Example: Head size of E32-TC200 is M4. Open the mounting holes with 4 to 4.5 dia.


### <Cylindrical Model>

(Unit:mm)

Outer diameter of fiber unit	1 dia.	1.5 dia.	2 dia.	3 dia.
F dimensions	$1.2^{+0.2}_{-0}$ dia.	$1.7^{+0.2}_{-0}$ dia.	$2.2^{+0.2}_{-0}$ dia.	$3.2^{+0.2}_{-0}$ dia.
Outer diameter of fiber unit	3.5 dia.	4 dia.	5 dia.	6 dia.
F dimensions	$4^{+0.5}_{-0}$ dia.	$4.5^{+0.5}_{-0}$ dia.	$5.5^{+0.5}_{-0}$ dia.	$6.5^{+0.5}_{-0}$ dia.

Example: Head size of E32-T22 is 2 dia.. Open the mounting holes with 2.2 to 2.4 dia.

## Minimum bending radius













(R) Flexible (B) Break-resistant (U) Fluororesin coating (R) Standard (Unit:mm)

Type	A Minimum bending radius	B un Bendable
(except E32-C11N, E32-C31N and E32-CC200)	1	0
(E32-C11N, E32-C31N, E32-CC200R)	4	0
(B) (U) (R4)	4	10
(R10)	10	10
(R25)	25	10
(R30)	30	10
(R35)	35	10
(R40)	40	10







# Fiber Units with Reflective Sensors

## Standard Models Standard/Flexible Models


**R** Flexible **B** Break-resistant **U** Fluororesin coating **R□** Standard  
**Free-cut** Cutting free (Cutter provided)



**R** Flexible **B** Break-resistant **U** Fluororesin coating **R□** Standard  
**Free-cut** Cutting free (Cutter provided)



## Mounting hole dimensions (recommended)



### <Screw-mounting Model>

(Unit:mm)

Outer diameter of fiber unit	M3	M4	M6	M14
F dimensions	3 <sup>+0.5</sup> <sub>0</sub> dia.	4 <sup>+0.5</sup> <sub>0</sub> dia.	6 <sup>+0.5</sup> <sub>0</sub> dia.	14 <sup>+1</sup> <sub>0</sub> dia.

Example: Head size of E32-TC200 is M4. Open the mounting holes with 4 to 4.5 dia.


### <Cylindrical Model>

(Unit:mm)

Outer diameter of fiber unit	1 dia.	1.5 dia.	2 dia.	3 dia.
F dimensions	1.2 <sup>+0.2</sup> <sub>0</sub> dia.	1.7 <sup>+0.2</sup> <sub>0</sub> dia.	2.2 <sup>+0.2</sup> <sub>0</sub> dia.	3.2 <sup>+0.2</sup> <sub>0</sub> dia.
Outer diameter of fiber unit	3.5 dia.	4 dia.	5 dia.	6 dia.
F dimensions	4 <sup>+0.5</sup> <sub>0</sub> dia.	4.5 <sup>+0.5</sup> <sub>0</sub> dia.	5.5 <sup>+0.5</sup> <sub>0</sub> dia.	6.5 <sup>+0.5</sup> <sub>0</sub> dia.

Example: Head size of E32-T22 is 2 dia.. Open the mounting holes with 2.2 to 2.4 dia.

## Minimum bending radius



**R** Flexible **B** Break-resistant **U** Fluororesin coating **R□** Standard  
 (Unit:mm)


Type	A Minimum bending radius	B unbendable
(except E32-C11N, E32-C31N and E32-CC200)	1	0
(E32-C11N, E32-C31N, E32-CC200R)	4	0
<b>B</b> <b>U</b> (R4)	4	10
(R10)	10	10
(R25)	25	10
(R30)	30	10
(R35)	35	10
(R40)	40	10

# Fiber Units with Reflective Sensors


## Standard Models Break-resistant/Coated Models

**R** Flexible **B** Break-resistant **U** Fluororesin coating **R** Standard  
**Free-cut** Cutting free (Cutter provided)


E32-D11 **B**  
E32-D11U **U**




E32-D21B **B**




E32-D21 **B**




### Enlarged illustration of sensing surface



E32-D221B **B**




E32-D22B **B**




\*The Attachment is attached with adhesive and cannot be removed.

### Enlarged illustration of sensing surface




E32-D15XB **B**



Note: Mounting screws (countersunk screw M2 x 8 2 pcs) included

E32-D25XB **B**




Note: Mounting screws (countersunk screw M2 x 8 2 pcs) included

## Special-beam Models Long-distance/High-power Models


E32-D16 **B**

(Free-cut)




E32-D11L **R25**

(Free-cut)




E32-D21L **R10**

(Free-cut)



E32-D22L **R10**


(Free-cut)




## Special-beam Models Ultracompact/Thin-sleeve Models

E32-D33 **R4**

(Free-cut)




E32-D331 **R4**



\*The Attachment is attached with adhesive and cannot be removed.

## Mounting hole dimensions (recommended)



### <Screw-mounting Model>

(Unit:mm)

Outer diameter of fiber unit	M3	M4	M6	M14
F dimensions	3 <sup>+0.5</sup> <sub>0</sub> dia.	4 <sup>+0.5</sup> <sub>0</sub> dia.	6 <sup>+0.5</sup> <sub>0</sub> dia.	14 <sup>+1</sup> <sub>0</sub> dia.

Example: Head size of E32-TC200 is M4. Open the mounting holes with 4 to 4.5 dia.


### <Cylindrical Model>

(Unit:mm)

Outer diameter of fiber unit	1 dia.	1.5 dia.	2 dia.	3 dia.
F dimensions	1.2 <sup>+0.2</sup> <sub>0</sub> dia.	1.7 <sup>+0.2</sup> <sub>0</sub> dia.	2.2 <sup>+0.2</sup> <sub>0</sub> dia.	3.2 <sup>+0.2</sup> <sub>0</sub> dia.
Outer diameter of fiber unit	3.5 dia.	4 dia.	5 dia.	6 dia.
F dimensions	4 <sup>+0.5</sup> <sub>0</sub> dia.	4.5 <sup>+0.5</sup> <sub>0</sub> dia.	5.5 <sup>+0.5</sup> <sub>0</sub> dia.	6.5 <sup>+0.5</sup> <sub>0</sub> dia.

Example: Head size of E32-T22 is 2 dia.. Open the mounting holes with 2.2 to 2.4 dia.

## Minimum bending radius



**R** Flexible **B** Break-resistant **U** Fluororesin coating **R□** Standard (Unit:mm)

Type	A Minimum bending radius	B unbendable
(except E32-C11N, E32-C31N and E32-CC200)	1	0
(E32-C11N, E32-C31N, E32-CC200R)	4	0
<b>B</b> <b>U</b> <b>R4</b>	4	10
<b>R10</b>	10	10
<b>R25</b>	25	10
<b>R30</b>	30	10
<b>R35</b>	35	10
<b>R40</b>	40	10




# Fiber Units with Reflective Sensors

## Special-beam Models Coaxial/Small-spot Models


**R** Flexible **B** Break-resistant **U** Fluororesin coating **R** Standard  
**Free-cut** Cutting free (Cutter provided)

### E32-C11N **R**



Free-cut

### E32-C31N **R**




Free-cut

Note: The Emitter fiber is shown with a white line.  
 M3 nuts (brass/nickel plating)  
 Washer (brass/nickel plating) included (2 of each)

### E32-CC200 **R25**


### E32-CC200R **R**



Free-cut

Note: There is a white line on the fiber that is inserted in the emitter-side port.


### E32-D32L **R25**



Free-cut

Note: There is a yellow dotted line on the fiber that is inserted in the emitter-side port.


### E32-C31 **R25**



Free-cut

Note: There is a white line on the cable fiber that is inserted in the emitter-side port.


### E32-D32 **R25**



Free-cut


Note: There is a white line on the cable fiber that is inserted in the emitter-side port.

### E32-C41 **R25**



\* The Fiber Attachment is attached with adhesive and cannot be removed.

### E32-C42 **R25**



\* The Fiber Attachment is attached with adhesive and cannot be removed.




# Fiber Units with Reflective Sensors


## Special-beam Models Convergent-reflective Models

**R** Flexible **B** Break-resistant **U** Fluororesin coating **R** Standard  
**Free-cut** Cutting free (Cutter provided)


### E32-L24S (R10)




### E32-L16-N (R25)




### E32-L24L (R10)



### E32-L25L (R10)




### E32-L25 (R25)



Note: There is a white line on the fiber that is inserted in the emitter-side port.

### E32-L25A (R25)




Note: There is a white line on the fiber that is inserted in the emitter-side port.

# Special-beam Models Convergent-reflective Models


**R** Flexible **B** Break-resistant **U** Fluororesin coating **R□** Standard  
**Free-cut** Cutting free (Cutter provided)

## E32-L86 (R25)




Note: The maximum allowable temperatures for sections A and B are 200°C and 110°C, respectively. The section inserted into the Amplifier Unit (indicated by \*), however, must stay within the Amplifier Unit's operating temperature range.



## E32-L64 (R25)




Note: The maximum allowable temperatures are 300°C for section A and 110°C for section B (section inserted into the Amplifier Unit).



## E32-A10 (R25)



## Mounting hole dimensions (recommended)



### <Screw-mounting Model>

(Unit:mm)

Outer diameter of fiber unit	M3	M4	M6	M14
F dimensions	3 <sup>+0.5</sup> <sub>0</sub> dia.	4 <sup>+0.5</sup> <sub>0</sub> dia.	6 <sup>+0.5</sup> <sub>0</sub> dia.	14 <sup>+1</sup> <sub>0</sub> dia.

Example: Head size of E32-TC200 is M4. Open the mounting holes with 4 to 4.5 dia.


### <Cylindrical Model>

(Unit:mm)

Outer diameter of fiber unit	1 dia.	1.5 dia.	2 dia.	3 dia.
F dimensions	1.2 <sup>+0.2</sup> <sub>0</sub> dia.	1.7 <sup>+0.2</sup> <sub>0</sub> dia.	2.2 <sup>+0.2</sup> <sub>0</sub> dia.	3.2 <sup>+0.2</sup> <sub>0</sub> dia.
Outer diameter of fiber unit	3.5 dia.	4 dia.	5 dia.	6 dia.
F dimensions	4 <sup>+0.5</sup> <sub>0</sub> dia.	4.5 <sup>+0.5</sup> <sub>0</sub> dia.	5.5 <sup>+0.5</sup> <sub>0</sub> dia.	6.5 <sup>+0.5</sup> <sub>0</sub> dia.

Example: Head size of E32-T22 is 2 dia.. Open the mounting holes with 2.2 to 2.4 dia.

## Minimum bending radius





**R** Flexible **B** Break-resistant **U** Fluororesin coating **R□** Standard  
 (Unit:mm)

Type	A Minimum bending radius	B unbendable
(except E32-C11N, E32-C31N and E32-CC200)	1	0
(E32-C11N, E32-C31N, E32-CC200R)	4	0
<b>B</b> <b>U</b> <b>R4</b>	4	10
<b>R10</b>	10	10
<b>R25</b>	25	10
<b>R30</b>	30	10
<b>R35</b>	35	10
<b>R40</b>	40	10

# Fiber Units with Reflective Sensors


## Environment-resistant Models Heat-resistant Models

**R** Flexible **B** Break-resistant **U** Fluororesin coating **R** Standard  
**Free-cut** Cutting free (Cutter provided)




Using the E32-D81R

- Note 1. The maximum allowable temperatures for sections A and B are 200°C and 110°C, respectively. The section inserted into the Amplifier Unit (indicated by \*), however, must stay within the Amplifier Unit's operating temperature range.
2. Order the Fiber Unit based on the Amplifier Unit. Use the E32-D81R-S if the E3X-DA□-S, E3X-MDA□, or E3X-DAC□-S is used. Use the E32-D81R if any other Amplifier is used.



Using the E32-D61



- Note 1. The maximum allowable temperatures for sections A and B are 350°C and 110°C, respectively. The section inserted into the Amplifier Unit (indicated by \*), however, must stay within the Amplifier Unit's operating temperature range.
2. Order the Fiber Unit based on the Amplifier Unit. Use the E32-D61-S if the E3X-DA□-S, E3X-MDA□, or E3X-DAC□-S is used. Use the E32-D61 if any other Amplifier is used.



Using the E32-D73

- Note 1. The maximum allowable temperatures for sections A, B, and C are 400°C, 300°C, and 110°C, respectively. The section inserted into the Amplifier Unit (indicated by \*), however, must stay within the Amplifier Unit's operating temperature range.
2. Order the Fiber Unit based on the Amplifier Unit. Use the E32-D□-S if the E3X-DA□-S, E3X-MDA□, or E3X-DAC□-S is used. Use the E32-D□ if any other Amplifier is used.

## Environment-resistant Models Chemical-resistant Models






# Fiber Units with Reflective Sensors

## Application-corresponding Fiber Units


### Liquid-level Detection Models

R Flexible 
 B Break-resistant 
 U Fluororesin coating 
 R Standard 
 Free-cut Cutting free (Cutter provided)

#### E32-A01 R4




#### E32-A02 R4



#### E32-D82F1 R40

#### E32-D82F2 R40




Note: The maximum allowable temperatures for sections A and B are 200°C and 85°C, respectively.

### Models for Glass-substrate Alignment/Mapping

#### E32-A08 R25

#### E32-A07E1 R25


#### E32-A07E2 R25



\*1 The E32-A07E1/E32-A07E2 has a reception fiber and an emission fiber. Use the fiber with a model display tube (fiber with blue dotted line) as light emitting side.


\*2 E32-A08 : Countersinks on one side  
E32-A07E1/E32-A07E2 : Countersinks on both sides

#### E32-L66 R25



Note: The maximum allowable temperatures for sections A and B are 300°C and 110°C, respectively. The section inserted into the Amplifier Unit (indicated by \*), however, must stay within the Amplifier Unit's operating temperature range.



#### E32-A08H2 R25







Note: The maximum allowable temperatures for sections A and B are 300°C and 110°C, respectively.




**R** Flexible **B** Break-resistant **U** Fluororesin coating **R□** Standard  
**Free-cut** Cutting free (Cutter provided)



## Wafer-mapping Models



## Mounting hole dimensions (recommended)



### <Screw-mounting Model>

(Unit:mm)

Outer diameter of fiber unit	M3	M4	M6	M14
F dimensions	3 <sup>+0.5</sup> <sub>0</sub> dia.	4 <sup>+0.5</sup> <sub>0</sub> dia.	6 <sup>+0.5</sup> <sub>0</sub> dia.	14 <sup>+1</sup> <sub>0</sub> dia.

Example: Head size of E32-TC200 is M4. Open the mounting holes with 4 to 4.5 dia.


### <Cylindrical Model>

(Unit:mm)

Outer diameter of fiber unit	1 dia.	1.5 dia.	2 dia.	3 dia.
F dimensions	1.2 <sup>+0.2</sup> <sub>0</sub> dia.	1.7 <sup>+0.2</sup> <sub>0</sub> dia.	2.2 <sup>+0.2</sup> <sub>0</sub> dia.	3.2 <sup>+0.2</sup> <sub>0</sub> dia.
Outer diameter of fiber unit	3.5 dia.	4 dia.	5 dia.	6 dia.
F dimensions	4 <sup>+0.5</sup> <sub>0</sub> dia.	4.5 <sup>+0.5</sup> <sub>0</sub> dia.	5.5 <sup>+0.5</sup> <sub>0</sub> dia.	6.5 <sup>+0.5</sup> <sub>0</sub> dia.

Example: Head size of E32-T22 is 2 dia.. Open the mounting holes with 2.2 to 2.4 dia.

## Minimum bending radius




**R** Flexible **B** Break-resistant **U** Fluororesin coating **R□** Standard  
 (Unit:mm)

Type	A Minimum bending radius	B unbendable
(except E32-C11N, E32-C31N and E32-CC200)	1	0
(E32-C11N, E32-C31N, E32-CC200R)	4	0
<b>B</b> <b>U</b> (R4)	4	10
(R10)	10	10
(R25)	25	10
(R30)	30	10
(R35)	35	10
(R40)	40	10

# Accessories

## Lens Units


### Lens Units E39-F1



Material:  
Brass for the body and optical glass for the lens itself.

Note: Two per set.


### Side-view Units E39-F2



Material:  
Brass for the body and optical glass for the lens itself.

Note: Two per set.


### Reflection Unit with Lens E39-F3



Material:  
Brass for the body and aluminum for the base.

\* Secure the fiber head with the slotted-head set screws. Do not insert a lens (E39-F1).


### Lens Unit for Reflective Fiber Units E39-F3A



Material:  
Aluminum for body and optical glass for lens.

Note: This is the Lens Unit for the E32-D32 and E32-C42.


### Lens Unit for Reflective Fiber Units E39-F3A-5



Material:  
Aluminum for body and optical glass for lens

Note: This is the Lens Unit for the E32-C31 and E32-C41.


### Lens Unit for Reflective Fiber Units E39-F3B



Material:  
Aluminum for body and optical glass for lens.

Note: This is the Lens Unit for the E32-C31 and E32-C41.

### Lens Unit for Reflective Fiber Units E39-F3C




Material:  
Aluminum for body and optical glass for lens.

Note: This is the Lens Unit for the E32-C31 and E32-C41.



## Protective Spiral Tubes

### E39-F32A/F32A5 E39-F32B/F32B5




Note 1. The length L is 1,000 for the E39-F32A/-F32B and 500 for the E39-F32A5/-F32B5.  
2. The E39-F32B(5) consists of two E39-F32A(5)s.

### E39-F32C/F32C5



Note: The length L is 1,000 for the E39-F32C and 500 for the E39-F32C5.

### E39-F32D/F32D5




Note: The length L is 1,000 for the E39-F32D and 500 for the E39-F32D5.


## Accessories

### Other Accessories

#### Fiber Cutter E39-F4




#### Thin-fiber Attachments E39-F9





Material: ABS


Note: Two per set.  
\*Provided with thin-fiber models.



#### Fiber Connector E39-F10




#### Fiber Connector E39-F13 E39-F14 E39-F15





Note: Dimension A varies with the model number as shown in the following table.

Model	Dimension A
E39-F13	2.4
E39-F14	1.2
E39-F15	2.4/1.2

#### Sleeve Bender E39-F11



#### Mounting Bracket E39-L83



## Safety Precautions

Refer to **Warranty and Limitations of Liability**.

### WARNING

This product is not designed or rated for ensuring safety of persons either directly or indirectly. Do not use it for such purposes.



### Precautions for Correct Use

Do not use the product in atmospheres or environments that exceed product ratings.


#### Fiber Units

##### ● Mounting


##### Tightening Force

The tightening force used to mount the Fiber Unit must not be more than the value given in Ratings/Characteristics.

##### Screw-mounting Model




##### Cylindrical Model



##### Chemical-resistive Models

The following method is recommended to prevent the fluororesin case from cracking when the Sensor is being secured. Be especially careful not to crack the case when using screws to secure the Sensor.



### Fiber Cutting Procedure


Cut a thin fiber as follows:

(1)	The fiber is shipped loosely tightened as shown in the figure at the right.	<p>Thin fiber attachment (E39-F9) Temporarily fitted</p>
(2)	Adjust the fiber to the desired length and then tighten it securely.	
(3)	Insert the fiber to be cut into the E39-F4.	<p>Cutter (E39-F4) Two holes for thin fiber Three holes for standard fiber (2.2-mm dia.)</p>
(4)	Finished state (proper cutting state)	<p>Approx. 0.5 mm Insertion direction Note: Insert the fiber into the amplifier the direction indicated by the arrow.</p>


### Connection

- Do not excessively pull or press the Fiber Unit. Use a pulling force no higher than what is given in *Ratings/Characteristics*.
- Do not bend the Fiber Unit beyond the permissible bending radius given under *Ordering Information*.
- Do not bend the edge of the Fiber Units (excluding the E32-T□R and E32-D□R).

#### Correct




#### Incorrect



- Do not apply excess force on the Fiber Units.


#### Correct



#### Incorrect




The Fiber Head could be broken by excessive vibration. To prevent this, the following is effective:



### E39-F11 Sleeve Bender

- The bending radius of the stainless steel tube should be as large as possible. The smaller the bending radius becomes, the shorter the sensing distance will be.
- Insert the tip of the stainless steel tube to the Sleeve Bender and bend the stainless steel tube slowly along the curve of the Sleeve Bender.




### Heat-resistant Fiber Units

(E32-D51 and E32-T51)

- The fibers of these Units cannot be extended using the E39-F10 Fiber Connector.
- The maximum allowable temperature for continuous operation with these Units is 130°C. It is 150°C for short-term use.

### E32-T14 and E32-G14

These Units may enter the light-ON state if there are reflecting objects at the ends of the lenses. In this case, attach the black stickers provided to the ends of the lenses.




### Wafer Sensors (E32-L25(A))

- To ensure correct performance, insert the fiber with a white line into the emitter-side port of the Amplifier Unit.

### E32-T16 and E32-T16P

#### Example

E32-T16's sensing head



To use the slit provided, peel off the backing sheet, align it with the edges of the sensing surface, and attach it to the sensing head. Use the slit in applications where saturation occurs (i.e., changes in light intensity cannot be obtained) due to short sensing distances.

### E32-M21

Separate the 4 fibers by distances sufficient to prevent interference.

### Vacuum-resistant Fiber Units (E32-V)

Although Flanges, Fiber Units on the vacuum side, and Lens Units have been cleaned, as an extra precaution, clean these products with alcohol before use in high-vacuum environments to ensure that they are properly degreased.

### Liquid-level Detection Sensors (E32-D82F)


- Secure the Fiber Unit using the unbendable section. Otherwise, the liquid-level detection position may be displaced.
- For applications in hazardous environments, install the Fiber Unit in the hazardous environment but install the Amplifier Unit in a safe environment.

### Liquid-level Detection Sensors: Tube-mounting Models

- Ensure that the tube is not deformed when using a band to secure the Fiber Unit.
- Drops of water, bubbles, or haze inside the tube may cause malfunctions.

### E32-A07E1(E2)

There is a difference in sensing object angle between E32-A07E1 and E32-A07E2. Select a model in accordance with the bending direction of a sensing object. Use the fiber with a model display tube as light emitting side.




### ● Adjustment

#### E32-G14

When a Digital Fiber Amplifier is used, the sensing distance is short, making the incident light intensity large. This makes it impossible to teach without a workpiece.

### Liquid-level (E32-D82F) Detection Position

The liquid-level detection position is at a distance of  $5.2 \pm 2$  mm from the end of the fluororesin section. (Refer to the diagram on the right.)



The liquid-level detection position varies with the surface tension of the liquid and the degree of wetness at the Fiber Unit's detection position.

### ● Other Considerations

#### Liquid Level (E32-D82F)

- Operation may become unstable in the following cases:
  - ① Bubbles stick to the cone of the sensing head.
  - ② Solute is deposited on the cone of the sensing head.
  - ③ The liquid has a high viscosity.
- There are some liquids, such as milky white liquids, for which detection is not possible.
- Do not let the end of the fluororesin section bump into another object. Damage to, or deformation of, the sensing head may result in unstable operation.

### Heat-resistant Fiber Units (E32-D81R(-S), E32-D61(-S), and E32-D73(-S))

The pitch of the emission-side and reception-side fiber-insertion ports varies with the Amplifier Unit. Be sure to use an appropriate Fiber Unit.

Amplifier Unit	Fiber Unit
E3X-DA□-S E3X-MDA□	E32-D□-S
E3X-DA□-N E3X-NA□	E32-D□

### Chemical-resistant Fiber and Liquid Level (E32-D82F)

Fluororesin has high chemical resistance. However, applications in the atmosphere of vaporized chemicals (gases) or steam may cause malfunction or damage inside sensors. Run a full check before using in such environments.


## ■ Accessories

### Use of E39-R3 Reflector


1. Use detergent, etc., to remove any dust or oil from the surfaces where tape is applied. Adhesive tape will not be attached properly if oil or dust remains on the surface.
2. The E39-R3 cannot be used in places where it is exposed to oil or chemicals.

### E39-F32□ Protective Spiral Tubes


1. Insert a fiber to the Protective Spiral Tube from the head connector side (screwed) of the tube.




2. Push the fiber into the Protective Spiral Tube. The tube should be straight so that the fiber is not twisted when inserted. Then turn the end cap of the spiral tube.



3. Secure the Protective Spiral Tube on a suitable place with the attached nut.




4. Use the attached saddle to secure the end cap of the Protective Spiral Tube. To secure the Protective Spiral Tube at a position other than the end cap, apply tape to the tube so that the portion becomes thicker in diameter.



### E39-F10 Fiber Connector

Mount the Fiber Connector as shown in the following illustrations.

1. Insert the Fiber Unit into the retention clip.
2. Insert the retention clip into the splice.



- The Fiber Units should be as close as possible when they are connected. Sensing distance will be reduced by approximately 25% when fibers are connected.
- Only 2.2-mm dia. fibers can be connected.





## **READ AND UNDERSTAND THIS DOCUMENT**

Please read and understand this document before using the products. Please consult your OMRON representative if you have any questions or comments.

## **WARRANTY**

OMRON's exclusive warranty is that the products are free from defects in materials and workmanship for a period of one year (or other period if specified) from date of sale by OMRON.

OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, REGARDING NON-INFRINGEMENT, MERCHANTABILITY, OR FITNESS FOR PARTICULAR PURPOSE OF THE PRODUCTS. ANY BUYER OR USER ACKNOWLEDGES THAT THE BUYER OR USER ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE. OMRON DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED.

## **LIMITATIONS OF LIABILITY**

OMRON SHALL NOT BE RESPONSIBLE FOR SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED ON CONTRACT, WARRANTY, NEGLIGENCE, OR STRICT LIABILITY.

In no event shall responsibility of OMRON for any act exceed the individual price of the product on which liability is asserted.

IN NO EVENT SHALL OMRON BE RESPONSIBLE FOR WARRANTY, REPAIR, OR OTHER CLAIMS REGARDING THE PRODUCTS UNLESS OMRON'S ANALYSIS CONFIRMS THAT THE PRODUCTS WERE PROPERLY HANDLED, STORED, INSTALLED, AND MAINTAINED AND NOT SUBJECT TO CONTAMINATION, ABUSE, MISUSE, OR INAPPROPRIATE MODIFICATION OR REPAIR.

## **SUITABILITY FOR USE**

THE PRODUCTS CONTAINED IN THIS DOCUMENT ARE NOT SAFETY RATED. THEY ARE NOT DESIGNED OR RATED FOR ENSURING SAFETY OF PERSONS, AND SHOULD NOT BE RELIED UPON AS A SAFETY COMPONENT OR PROTECTIVE DEVICE FOR SUCH PURPOSES. Please refer to separate catalogs for OMRON's safety rated products.

OMRON shall not be responsible for conformity with any standards, codes, or regulations that apply to the combination of products in the customer's application or use of the product.

At the customer's request, OMRON will provide applicable third party certification documents identifying ratings and limitations of use that apply to the products. This information by itself is not sufficient for a complete determination of the suitability of the products in combination with the end product, machine, system, or other application or use.

The following are some examples of applications for which particular attention must be given. This is not intended to be an exhaustive list of all possible uses of the products, nor is it intended to imply that the uses listed may be suitable for the products:

- Outdoor use, uses involving potential chemical contamination or electrical interference, or conditions or uses not described in this document.
- Nuclear energy control systems, combustion systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equipment, and installations subject to separate industry or government regulations.
- Systems, machines, and equipment that could present a risk to life or property.

Please know and observe all prohibitions of use applicable to the products.

NEVER USE THE PRODUCTS FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCT IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

## **PERFORMANCE DATA**

Performance data given in this document is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of OMRON's test conditions, and the users must correlate it to actual application requirements. Actual performance is subject to the OMRON Warranty and Limitations of Liability.

## **CHANGE IN SPECIFICATIONS**

Product specifications and accessories may be changed at any time based on improvements and other reasons.

It is our practice to change model numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the product may be changed without any notice. When in doubt, special model numbers may be assigned to fix or establish key specifications for your application on your request. Please consult with your OMRON representative at any time to confirm actual specifications of purchased products.

## **DIMENSIONS AND WEIGHTS**

Dimensions and weights are nominal and are not to be used for manufacturing purposes, even when tolerances are shown.

## **ERRORS AND OMISSIONS**

The information in this document has been carefully checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical, or proofreading errors, or omissions.

## **PROGRAMMABLE PRODUCTS**

OMRON shall not be responsible for the user's programming of a programmable product, or any consequence thereof.

## **COPYRIGHT AND COPY PERMISSION**

This document shall not be copied for sales or promotions without permission.

This document is protected by copyright and is intended solely for use in conjunction with the product. Please notify us before copying or reproducing this document in any manner, for any other purpose. If copying or transmitting this document to another, please copy or transmit it in its entirety.